

PTC Double Air Speed Heating Air Curtain

PTC双风速热风幕机



Ambient without heating 普通风



PTC heater 6 ~ 12kw PTC发热体功率 6 ~ 12kw



High or low air speed settings meets different needs in the application.

具有高速和低速两档调节，适合不同场所的需要。



The un-electrified-surface PTC heater ensure safer operation, quick temperature rising and auto-temperature-control performance for users.

采用表面不带电的PTC发热体，具有安全性能极高、升温快和自动恒温功能，形成很好的热空气幕墙



Strong and quick heat generating, stable performance, low electricity consumption, can work on temperature -18°C.

制热能力强，性能稳定，耗电少，制热迅速，在零下18°C可以照常启动



Electronic control, either ambient air or heating air mode can be selected.

电脑板控制，可单独运行普通风或热风



Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm, 1800mm, 2000mm.

多种机身长度规格：900mm、1000mm、1200mm、1500mm、1800mm、2000mm。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specifications (mm)	额定电压/频率/相数 Voltage/ Frequency/ Phase	安装高度 Installation Height (m)	出风口温度 Outlet Temperature (°C)	风速 Air Speed (m/s)		发热体参数 PTC Heater Parameters		电机功率 Motor Power (W)		风量 Air Flow (m³/h)	噪音 Noise (dB)	外形尺寸 Unit Size (mm)	净重 Net Weight (kg)
					低档 Low	高档 High	发热体功率 PTC Heating Power (W)	每相电流 Amp/Phase (A)	低档 Low	高档 High				
RM125-09-D/Y-B-2-S RM125-09-D/Y-B-2-L	900	220V ~ / 50Hz / 1Ph	2.3 ~ 3.0	50 ~ 60	6.0	7.5	6000	27	96	156	912	55	900 x 221 x 183	14.9
RM125-10-D/Y-B-2-S RM125-10-D/Y-B-2-L	1000						6000	29	113	167	1040	56	1000 x 221 x 183	16.1
RM125-12-D/Y-B-2-S RM125-12-D/Y-B-2-L	1200						7200	33	126	178	1280	57	1200 x 221 x 183	19.0
RM125-15-D/Y-B-2-S RM125-15-D/Y-B-2-L	1500						9000	41	154	207	1670	59	1500 x 221 x 183	23.3
RM125-18-D/Y-B-2-S RM125-18-D/Y-B-2-L	1800						12000	55	130	200	2000	60	1800 x 221 x 183	28.1
RM125-20-D/Y-B-2-S RM125-20-D/Y-B-2-L	2000						12000	55	246	300	2110	62	2000 x 221 x 183	30.5
RM125-09-3D/Y-B-2-S RM125-09-3D/Y-B-2-L	900	380V ~ / 50Hz / 3Ph	2.3 ~ 3.0	50 ~ 60	6.0	7.5	6000	9	96	156	912	55	900 x 221 x 183	14.9
RM125-10-3D/Y-B-2-S RM125-10-3D/Y-B-2-L	1000						6000	10	113	167	1040	56	1000 x 221 x 183	16.1
RM125-12-3D/Y-B-2-S RM125-12-3D/Y-B-2-L	1200						7200	11	126	178	1280	57	1200 x 221 x 183	19.0
RM125-15-3D/Y-B-2-S RM125-15-3D/Y-B-2-L	1500						9000	14	154	207	1670	59	1500 x 221 x 183	23.3
RM125-18-3D/Y-B-2-S RM125-18-3D/Y-B-2-L	1800						12000	18	130	200	2000	60	1800 x 221 x 183	28.1
RM125-20-3D/Y-B-2-S RM125-20-3D/Y-B-2-L	2000						12000	18	246	300	2110	62	2000 x 221 x 183	30.5

Remark: Customized rated voltage and frequency are available.

备注: 可根据客户的额定电压和频率来订做合适的产品。