


embraco
Nidec

COMPRESSORS EUROPE



Maximum energy optimization
from production to product.

- R134a/R513A
- R404A /R507/R452A/R448A/449A
- R290
- R600a

 cantas



embraco
Nidec

01

ABOUT EMBRACO

02

OUR PRODUCTS

03

APPLICATION
GUIDE

04

NOMENCLATURE

05

TECHNICAL
INFORMATION

06

GENERAL DATA
& PERFORMANCE

07

EXTERNAL VIEWS &
WIRING DIAGRAMS

EMBRACO is a global refrigeration compressors and condensing units manufacturer. Since 1971 it provides innovative solutions for household and light commercial refrigeration attending customers' most challenging demands.

With a production capacity of 60 million units of motors and compressors per year, Embraco directly employs approximately 14 thousand people, has 11 business units (among factories, sales offices and a global business shared services) located in Brazil, China, Italy, Mexico, Slovakia, USA and Russia, and is commercially present in more than 80 countries. Since July, 2019, we are part of **Nidec Corporation**, the world's leading comprehensive motor manufacturer (www.nidec.com)



INNOVATION

With an innovative DNA, Embraco has close to 500 professionals dedicated exclusively to this area, with 120 partners from leading engineering universities around the world, as well as over 50 research laboratories on four continents. The company invests 3% to 4% of its net revenue in R&D annually and is among the private companies with the highest number of patents in force in Brazil and the United States, reaching the 1,200 patents granted globally.



EFFICIENCY

For more than 20 years, we have used natural refrigerants in our portfolio for commercial and household as an alternative to reduce the negative effects on the ozone layer, greenhouse effects and to improve the equipment's energy efficiency.



11 Manufacturing plants



Presence in more than 80 countries with solutions and services



Over 50 research laboratories on four continents



500 people engaged in R&D activities, approximately 100 within University partners



1,200 patents granted worldwide (over 3,000 in total)



Yearly production capacity: 60 million units of motors and compressors/year



EMBRACO DIGITAL TOOLS: discover everything our digital solutions can do for you.



embraco toolboxapp

EMBRACO TOOLBOX APP

Available in all countries and in more than 10 languages, the Embraco Toolbox App has 7 functionalities which help refrigeration professionals on their daily routine. Download the App now for Android or iOS systems.



Find inside:

- CROSS-REFERENCE
- PRODUCT CATALOGUE
- DISTRIBUTOR LOCATOR
- UNIT CONVERTER
- REFRIGERANT SLIDER
- REFRIGERATION CLUB
- TROUBLESHOOTING




REFRIGERATION CLUB

Exclusive content for refrigeration professionals in a global channel. Keep updated and join us at: www.refrigerationclub.com



PRODUCT SELECTOR SOFTWARE

Choose the best solution for your cooling system at Embraco's official portfolio platform. Access: products.embraco.com



OUR PRODUCTS



SINGLE SPEED COMPRESSORS

EM		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Small size • Low noise • Best in class up to 11 cm³	Refrigerators and freezers Water cooler; Beer dispenser; Reach-in; Chest freezer Vending machine; Wine coolers; Small dispenser; Food exhibitor Beverage cooler; Ice maker
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 75 - 390 HBP: 250 - 800	LBP: 1.8 HBP: 2.62	1.17 - 11.14	R134a/R513A; R404A; R290; R600a;

NE		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Low noise	Beverage cooler; Ice maker Beer dispenser; Reach-in; Chest freezer Upright cabinets; Professional kitchen Slushy machine; Show cases Refrigerators and freezers;
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 187 - 950 HBP: 516 - 2292	LBP: 1.56 HBP: 2.79	4.40 - 16.80	R134a/R513A; R404A/R507/R452A/R449A/R448A; R290

F		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Small size	Water cooler; Beverage coolers; Ice maker Beer dispenser; Reach-in; Chest freezer Professional Kitchen; Vending machine Wine coolers; Heat pumps Food exhibitor; Refrigerated island; Show cases
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 115 - 490 HBP: 670 - 1575	LBP: 1.58 HBP: 2.92	6 - 12.92	R134a/R513A; R290

NT		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Low noise • Best in class up to 27.80 cm³ • Designed for Medical & Scientific ULT	Beverage coolers; Ice maker Beer dispenser; Reach-in; Chest freezers Upright cabinets Ultra low temperature refrigerators; Professional kitchen Slushy machine
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 576 - 1670 HBP: 1607 - 3885	LBP: 1.47 HBP: 2.81	12.60 - 27.80	R134a/R513A; R404A/R507/R452A/R449A/R448A; R290

NTU		FEATURES	APPLICATIONS
		• High efficiency • High robustness level for severe application • Continuous liquid return acceptance • Wide application range • Smallest size in this cooling capacity	Beverage coolers; Ice maker Beer dispenser; Reach-in Upright cabinets Ultra low temperature refrigerators Professional kitchen Chest freezers
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
HBP: 2424 - 5333	HBP: 3.09	20.40 - 27.80	R134a/R513A; R404A/ R507/R452A/R449A/R448A

NJ		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Low noise • Up to 2 hp	Beverage cooler; Ice maker Reach-in; Chest freezer Ultra low temperature Upright cabinet (air curtain) Cold rooms
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 568 - 2164 HBP: 2547 - 5914	LBP: 1.50 HBP: 2.92	21.60 - 37.9	R134a/R513A; R404A/ R507/R452A/R449A/R448A

VARIABLE CAPACITY COMPRESSOR

VES		FEATURES	APPLICATIONS
		• High efficiency • Small size • Very low noise • Better temperature control • Wide voltage range • Speed range: 1300-4500 rpm	Refrigerators and Freezers Wine cooler; Heat pumps Beverage coolers; Reach-in Chest freezer; Medical coolers
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 50-270 MBP: 38-270	LBP: 2.26 MBP: 3.25	3 - 11	R600a

VEM		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Low noise • Better temperature control • Wide voltage range	Refrigerators and Freezers Wine cooler; Heat pumps Beverage coolers; Reach-in Chest freezer; Medical coolers
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 41 - 250 HBP: 345 - 820	LBP: 1.96 HBP: 3.50	3 - 11	R134a; R290; R600a

FMF		FEATURES	APPLICATIONS
		• High efficiency • Robustness • Wide application range • Low noise • Better temperature control • Dual voltage and frequency on the same sku	Frozen Islands ; Beverage cooler Ice Maker Chest Freezer Reach-in Vertical Ice-cream cabinets; Medical cooler
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
L/MBP: 140 - 998	L/MBP: 1.84	6 - 13	R290

VNE		FEATURES	APPLICATIONS
		• Best in class in its range of cooling capacity • Robustness • Wide application range • Low noise • Better temperature control • Dual voltage and frequency on the same sku	Beverage cooler; Vertical Reach-in Beer dispenser Ice maker Reach-in Big chest freezer Frozen Islands
CAPACITY W	MAX EFFICIENCY W/W	DISPLACEMENT cm³	REFRIGERANTS
LBP: 420-1100	LBP: 1.8 HBP: 2.62	7 - 16.8	R134a, R404A, R507, R452A, R290

APPLICATION GUIDE



BEVERAGE COOLERS - 50Hz

GROSS VOLUME (l)		100 - 150		150 - 200		200 - 250		250 - 300		300 - 350			350 - 450		450 - 600		600 - 750		750 - 1000		1000 - 1400		1400 - 1700		1700 - 2000	
DOOR TYPE		SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS		SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS
R134a	PREMIUM EFFICIENCY	VEMY6HH	VEMY6HH	VEMY6HH	VEMY6HH	VEMY6HH	VEMY6HH	VEMY6HH	VEMY6HH	VEGT8HB	VEGT8HB		VEGT8HB	VEGT8HB												
	HIGH EFFICIENCY	EMT37HDP	EMT37HDP	EMT37HDP	EMT45HDR	EMT45HDR	EMT6144Z	EMT6144Z	EMT6160Z	EMT6160Z	EMT6170Z		EMT6170Z	NEU6187Z	NEU6210Z	NEU6212Z	NEU6212Z	NEU6214Z	NEU6214Z	NEU6214Z	NT6217Z	NT6217Z	NTU6222Z	NTU6222Z	NJ6226Z	NJ6226Z
R600a	HIGH EFFICIENCY	EMX32CLC	EMT45CDP	EMZ46CLC	EMZ46CLC	EMX55CLC	EMX55CLC	EMX3118Y	EMX3118Y	EMX3118Y	EMX3118Y		NBY5170Y	NBY5170Y												
R290	PREMIUM EFFICIENCY						EMC3119U	EMC3119U	EMC3119U	EMC3119U	EMC3119U		EMC3121U	EMC3125U												
	HIGH EFFICIENCY	EMI5oUER	EMI5oUER	EMX6144U	EMX6144U	EMX6144U	EMX6152U	EMX6152U	EMX6181U	EMX6181U	EMX6210U		EMX6181U	EMX6210U	NEU6212U	NEU6212U	NEU6212U	NEU6212U	NEU6214U	NEU6214U	NEU6214U	NEU6217U				
R404A	HIGH EFFICIENCY																		NEK6213GK	NEK6213GK	NE9213GK	NEK6213GK	NEK6217GK	NEK6217GK	NT6224GK	NT6224GK

AVERAGE BOTTLE COOLER SPECIFICATION	
Starting Type	LST
Application	MBP
Cooling Type	Fan
Door Type	Solid or Glass
Temperature	0 to 6°C

UPRIGHT FREEZERS
(ICE-CREAM AND FROZEN FOOD) - 50Hz

GROSS VOLUME (l)		<100	100-200	200 - 300	300 - 400	400 - 500		500 - 600	600 -700	700-800	800-1000	1000 <
R290	PREMIUM EFFICIENCY			FMFT406U	FMFT406U	VNEU217U		VNEU217U	VNEU217U			
	HIGH EFFICIENCY	EMT2121U	EMT2125U	NEU2140U	NEU2155U	NEU2168U		NT2180U	NT2210U	NT2210U		
R404A	PREMIUM EFFICIENCY			VNEK206GK	VNEK212GK	VNEK212GK						
	HIGH EFFICIENCY			NEU2140GK	NEU2155GK	NEU2168GK						
	STANDARD EFFICIENCY			NEK2134GK	NEK2150GK	NEK2168GK		NT2180GK	NT2180GK	NT2192GK	NT2212GK	NJ2212GK
R134a	PREMIUM EFFICIENCY	VEGT8HB	VEGT8HB									
	STANDARD EFFICIENCY	NE2121Z	NEU4130Z	NEK2140Z								

AVERAGE ICE CREAM FREEZERS SPECIFICATION	
Starting Type	HST
Application	LBP
Cooling Type	Fan
Door Type	Glass/Solid
Food Temp.	<-20°C

ICE MAKERS (CUBERS) - 50Hz

ICE/DAY		UP TO 25 Kg	25-40 Kg	40-60 Kg	60-90 Kg	90-120 Kg	120-150 Kg	150-170 Kg		170-210 Kg	210-250 Kg	250-280 Kg	280-320 Kg	320-360 Kg	360-400 Kg	400-450 Kg	450-550 Kg	550 - 700 Kg
R290	HIGH EFFICIENCY	EMX6144U	EMX6144U	EMX6210U	NEU6214U	NEU6217U	NEU6220U	NT6222U		NT6224U								
R404A		EMT6152GK	EMT6165GK	NEK6210GK	NEK6210GK	NEK6217GK	NT6220GKV	NT6222GKV		NT6224GK	NT6226GKV	NTU6232GK	NTU6234GKV	NTU6240GKV				
R134a		EMT6160Z	NEU6187Z	NEU6212Z	NEU6214Z	NT6217ZV	NT6220ZV	NTU6222ZV		NTU6224ZV								

ICE MAKERS (FLAKED) - 50Hz

ICE/DAY		60-90 Kg	90-120 Kg	120-150 Kg	150-170 Kg	170-210 Kg		210-250 Kg	250-280 Kg	280-320 Kg	320-360 Kg	360-400 Kg	400-450 Kg	450-500 Kg
R290	HIGH EFFICIENCY	EMX6210U	NEU6214U	NEU6217U	NT6220U	NT6222U		NT6224U						
R404A		NEK6210GK	NEU6215GK	NT6217GKV	NT6220GKV	NT6222GKV		NT6224GK	NT6226GKV	NJ2212GK	NJ2212GK	NJ2212GK		
R134a		NEU6212Z	NEU6214Z	NT6217ZV	NT6220ZV	NTU6222ZV		NTU6224ZV						

AVERAGE ICE MAKER SPECIFICATION	
Starting Torque	HST
Application	MBP
Cooling Type	FAN

COMMERCIAL KITCHEN APPLICATIONS - 50HZ LBP

(Low temperature refrigerators)

GROSS VOLUME (RANGE OF SIZES)	REACH-IN FREEZER	< 250 l	250 - 325 l	325 - 425 l		425 - 550 l	550 - 650 l	650 - 850 l	850 - 1150 l	1150 - 1500 l	1500 - 1700 l	1700 - 1900 l
	UNDERCOUNTER FREEZER	< 120 l	120 - 175 l	175 - 275 l		275 - 350 l	350 - 450 l	450 - 500 l	500 - 600 l	-	-	-
	WORKTOP FREEZER BLAST CHILLER	-	-	-		-	-	-	10 Kg	15 Kg	20 Kg	25 Kg
R290	PREMIUM EFFICIENCY - FULLMOTION INVERTER (VARIABLE SPEED COMPRESSOR)	VEGT8U	VEGT8U	VEGT8U		VEGT8U	FMFT413U	FMFT413U	FMFT413U	VNEU217U	VNEU217U	
	PREMIUM EFFICIENCY	EMC3121U	EMC3125U	EMC3130U		NEU2140U	NEU2155U	NEU2168U				
		EM2X3121U	EM2X3125U	EMT2130U		EMX3134U						
	HIGH EFFICIENCY	EMT2121U	NEMT2125U				NEK2150U	NEK2160U	NT2180U	NT2180U	NT2210U	NT2210U
R134a	PREMIUM EFFICIENCY - FULLMOTION INVERTER (VARIABLE SPEED COMPRESSOR)	VEGT8HB	VEGT11HB	VEGT11HB								
	HIGH EFFICIENCY	NE2121Z	NE2130Z	NE2134Z		NEK2140Z						
R404A	STANDARD EFFICIENCY	NEK2121GK	NEK2125GK	NEK2125GK		NEK2134GK	NEK2150GK	NEK2168GK	NEK2178GK	NT2180GK	NT2192GK	NT2212GK

COMMERCIAL KITCHEN APPLICATIONS - 50HZ MBP

(Medium temperature refrigerators)

GROSS VOLUME (RANGE OF SIZES)	REACH-IN REFRIGERATOR	200 - 275 l	275 - 375 l	175 - 500 l		550 - 700 l	700 - 950 l	950 - 1200 l	1200 - 1500 l
	FOOD PREPARATION TABLE REFRIGERATOR	70 cm	115 cm	140 cm		165 cm	190 cm	240 cm	300 cm
	UNDERCOUNTER REFRIGERATOR	100 - 200 l	200 - 350 l	350 - 500 l		~500 l	-	-	-
	WORKTOP REFRIGERATOR								
R290	PREMIUM EFFICIENCY - FULLMOTION INVERTER (VARIABLE SPEED COMPRESSOR)			VEGT8U		VEGT8U	VEGT8U	VEGT8U	
	PREMIUM EFFICIENCY			EMC3119U		EMC3121U	EMC3125U	EMC3130U	
	HIGH EFFICIENCY		EMI50UER	EMX6144U		EMX6165U	EMX6181U	NEU6212U	NEU6214U
R134a	PREMIUM EFFICIENCY - FULLMOTION INVERTER (VARIABLE SPEED COMPRESSOR)	VEMY6HH	VEMY6HH	VEMY6HH		VEGT8HB	VEGT11HB	VEGT11HB	VNEK614Z
	HIGH EFFICIENCY	EMT45HDR	EMT6144Z	EMT6160Z		EMT6170Z	NEU6187Z	NEU6212Z	NEU6214Z
R404A	STANDARD EFFICIENCY	NEK6144GK	NEK6152GK	NEK6165GK		NEK6181GK	NEK6210GK	NEK6213GK	NEK6213GK

AVERAGE PROF. KITCHEN REFRIGERATOR SPECIFICATION		
Evap. Temperature	-30 to -15°C	-15 to -5°C
Application	LBP	MBP
Starting Type	LST	LST
Cooling Type	Fan	Fan
Door Type	Solid	Solid

COLD ROOM

Cooling - temperature inside room +2°C (meat, milk products, packaged goods).

GROSS VOLUME m³	up to 3	3 - 5	5 - 10		10 - 13	13 - 17	17 - 23	23 - 35
DIMENSIONS (example) m	1 x 1,5 x 2	1,25 x 2 x 2	2 x 2 x 2,5		2 x 2,6 x 2,5	2 x 3,4 x 2,5	3 x 3 x 2,5	3,5 x 4 x 2,5
R404A	NEU6210GK	NEU6212GK	NEU6215GK		NT6220GK	NT6224GK	NJ9232GK	NJ9238GK
R134a	NEU6210Z	NEU6212Z	NEU6214Z		NT6220Z	NJ6226Z		

Freezer - temperature inside room -24°C (frozen, packaged goods)

GROSS VOLUME m³	up to 3	3 - 5	5 - 8		8 - 12	12 - 15
DIMENSIONS (example) m	1 x 1,5 x 2	1,25 x 2 x 2	2 x 2 x 2,5		2 x 2,6 x 2,5	2 x 3,4 x 2,5
R404A	NT2180GK	NJ2192GK	NJ2212GK		2 x NT180GK	2 x NJ2212GK
R290	NEU2178U	NEU2178U	NT2210U			

REFRIGERATED ISLAND

GROSS VOLUME (l)		400 - 500	500 - 600		600 - 700	700 - 800	800 - 900	900 - 1000	1000 - 1100	1100 <
R404A	PREMIUM EFFICIENCY	VNEK206GK	VNEK212GK		VNEK212GK	NT6220GK	NT6224GK	NJ9232GK	NJ9238GK	
	HIGH EFFICIENCY	NEU2140GK	NEU2140GK		NEU2168GK	NT2180GK	NJ2192GK	NT2212GK	NT2212GK	NJ2212GK
R290	PREMIUM EFFICIENCY	NEU6210Z	NEU6212Z		FMFT413U	FMFT413U	FMFT413U	FMFT413U	VNEU217U	VNEU217U
	HIGH EFFICIENCY	NEU2140U	NEU2140U		NEU2168U	NEU2178U	NT2210U	NT2210U		


HORIZONTAL FREEZER (SOLID DOOR + GLASS DOOR)

GROSS VOLUME (l)		up to 150		150 - 200		200 - 250		250 - 300		300 - 350			350 - 400		400 - 450		450 - 500		500 - 550		550 - 600		600...	
DOOR TYPE		SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS		SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS	SOLID	GLASS
R134a	STANDARD EFFICIENCY	EMT36HLP	EMT36HLP	EMT36HLP	EMT49HLP	EMT49HLP	EMT60HLP	EMT60HLP	NEK2118Z	NEK2118Z	NE2121Z		NE2121Z	NE2130Z	NE2130Z	NE2130Z	NE2130Z	NE2134Z	NE2134Z	NE2134Z	NEK2140Z	NEK2140Z		
R404A	STANDARD EFFICIENCY				EMT2117GK	EMT2117GK	EMT2125GK	EMT2125GK	EMT2125GK	EMT2130GK	EMT2130GK		EMT2130GK	EMT2130GK	EMT2130GK	EMT2130GK	NEU2140GK	NEU2140GK	NEU2140GK	NEU2140GK	NEU2140GK	NEU2155GK	NEU2155GK	NEU2168GK
R290	PREMIUM EFFICIENCY					EMC3119U	EMC3119U	EMC3119U	EMC3121U	EMC3121U	EMC3121U		EMC3121U	EMC3121U	EMC3125U	EMC3130U	EMC3130U	EMC3130U	EMC3134U	NEU1140U	NEU1140U	NEU1140U	NEU1140U	NEU2155U
	HIGH EFFICIENCY					EMT2117U	EMT2117U	EMT2121U	EMT2121U	EMT21215U	EMT2125U		EMT2125U	EMT2125U	EMT2125U	EMT2130U	EMT2130U	EMX3134U	NEK2134U	NEK2134U	NEK2134U	NEK2134U	NEK2150U	NEK2168U
R600	PREMIUM EFFICIENCY	EMC32CLT	EMD32CLT	EMC46CLT	EMC55CLT	EMC55CLT	EMC66CLT	EMC66CLT	EMC70CLT	EMC70CLT	EMC80CLT		EMC80CLT	EGX100CLC	EGX100CLC									
	HIGH EFFICIENCY	EMX32CLC	EMX32CLC	EMX55CLC	EMX55CLC	EMX66CLC	EMX66CLC	EMX66CLC	EMX70CLC	EMX70CLC	EMX3118Y		EMX3118Y	NBY1118Y										

NOMENCLATURE




EM / NE / NT / NJ




The V letter at the end of the compressor name stands for IPR valve.
*According to the refrigerant used


EM EUROPE BASE



EM / EG BRAZIL BASE




VNE / FMF




NOMENCLATURE

F



COMPRESSOR BILL OF MATERIAL CODE *



* Valid for European Products




TECHNICAL INFORMATION




OPERATING ENVELOPE

EMC, EMX, NE, NT, NJ, VNE


LBP
R134a - R600a




LBP
R404A/R507/R452A - R290




L/MBP
R290/R134a/R600a




ULBP
R508B/R170 - second stage of cascade



MBP
R404A/R507/R452A - R290




HBP
R134a - R600a




EM, EG, F, VEM, FMF, VES

Ambient temperature: 42°C - Return temperature: 32°C


LBP
R290 - R134a - R600a




L-MBP (STANDARD)
R290 - R134a




L-MBP EXTENDED RANGE FFUS, EM2, EM3
R290 - R134a - R600a



L-M-HBP
R134a



M-HBP
R134a



■ Operation Condition
■ Transient Condition

Tc Condensing Temperature °C
k Ambient 32°C and return gas 20°C
Te Evaporating Temperature °C
m Ambient 32°C and return gas 20°C (for transitory period)

NOTE: usage of compressors outside the intended working range causes the lapse of the warranty, or should be consulted with Technical support.

ALTERNATIVE REFRIGERANTS

R452A, R449A, R448A, R513A AND R450A CHARACTERISTICS

ACCORDING TO EN378	R452A	R449A	R448A	R513A	R450A
Chemical Name	Mixture R32/R125/R1234yf	Mixture R32/R125/R1234yf/R134a	Mixture R32/R125/R1234yf/R134a/R1234ze(E)	Mixture R134a/R1234yf	Mixture R134a/R1234ze(E)
Molecular Formula	weight % (11/59/30)	weight % (24.3/24.7/25.3/25.7)	weight % (26/26/20/21/7)	weight % (44/56)	weight % (42/58)
Safety Class	A1	A1	A1	A1	A1
PED fluid group	2	2	2	2	2
Practical Limit [kg/m³]	0.423	0.357	0.388	0.319	0.319
ATEL/ODL [kg/m³]	0.423	0.357	0.388	0.319	0.345
LFL [kg/m³]	NF (*)	NF (*)	NF (*)	NF (*)	NF (*)
Vapour density 25°C, 101.3 kPa [kg/m³]	4.30	3.62	3.58	4.256	4.54
Molecular Mass [g/mol]	103.51	87.21	86.28	108.4	108.67
Normal Boiling Point [°C]	-47 to -43.2	-46 to -39.9	-45.9 to -39.8	-29.05	-23.4 to -22.8
ODP	0	0	0	0	0
GWP [100 yr ITH]	2140	1397	1387	631.4	604.7
Autoignition temperature [°C]	ND	ND	ND	ND	ND
Critical Temperature [°C]	74.9	81.5	83.7	96.5	104.4
Critical Pressure [kPa abs]	4001.7	4447	4660	3766	3820
Temperature glide at 1 bar abs pressure [K]	3.8	6.1	6.3	0.1	0.8

(*) NF means non-flammable.
Note: HFC refrigerants (R452A, R449A, R448A, R513A and R450A) are classified in Safety Class A1 - lower toxicity, no flame propagation, (according to ISO817).

R404A

R452A is presenting the same or lower thermal profile when compared with R404A. Therefore, Embraco approves R452A as an alternative refrigerant for all Embraco R404A compressor series and authorizes its use, both in LBP and MBP applications, maintaining the same operating envelope of R404A refrigerant and other Embraco application guidelines as for example the system charge limitations defined for each Embraco compressor family.

R448A and **R449A** tests show relatively higher temperature levels then R404A. Usage of those refrigerants may require system changes, such as system condensing temperature reduction (larger condenser, improved ventilation) or return gas temperature reduction in order to achieve a similar thermal profile as with R404A refrigerant. To maintain Embraco warranty, final application needs to be validated by Embraco Technical Support Team case by case. Usage in systems operating under high compression ratio conditions in particular should be avoided.


R134a

Embraco approves **R513A** as well as **R450A** as alternative refrigerants for Embraco R134a compressors and authorizes their usage, both in LBP and HBP applications, maintaining the same operating envelope of R134a refrigerant and other Embraco application guidelines, such as the system charge limitations defined for each Embraco compressor family.

Refrigerant R513A, according to the calorimetric evaluation, is showing low impact on cooling capacity, while refrigerant R450A is showing drop of cooling capacity about 12% in average when tested at calorimeter. Actual impact on performances has to be verified on specific application. Embraco R134a compressors, using R450A and R513A, are maintain the same electrical components and are show the same reliability as with R134a refrigerant.

RESTRICTED OPERATING ENVELOPE

MBP R449A/R448A (max return 20 deg C)



For more information consult R449A/R448A ECN.

Customer always have the possibility of converting the system for use of **R134a** in place of **R404A** for this transition period, just by changing compressor model and relative system design adjustment.

EMBRACO COMPRESSORS INSTALLATION INSTRUCTIONS

The Installation Instructions apply to the Embraco on-off compressors produced in Europe (the country of origin is indicated on the compressor label). They are addressed to professional users, refrigeration system manufacturers/ installers and maintenance technicians and they are intended to provide instructions/recommendations on the proper use of Embraco compressors regarding reliability, performance and safety aspects. It's available on: products.embraco.com



APPLICATIONS

ULBP	ULTRA LOW BACK PRESSURE	APPLICATIONS:
	Evaporating temperature between -95 °C and -65 °C	medical appliances.
LBP	LOW BACK PRESSURE	APPLICATIONS:
	Evaporating temperature lower than -20 °C	refrigerators, frozen food cabinets, frozen food display case, display windows, etc.
L/MBP	LOW/MEDIUM BACK PRESSURE	APPLICATIONS:
	Evaporating temperature between -35 °C and 0 °C	professional kitchen coolers, icecream freezers, bottle coolers, chest freezers, etc.
MBP	MEDIUM BACK PRESSURE	APPLICATIONS:
	Evaporating temperature between -20 °C and 0 °C	fresh food cabinets, drink coolers, ice makers, etc.
M/HBP	MEDIUM/HIGH BACK PRESSURE	APPLICATIONS:
	Evaporating temperature between -20 °C and +10 °C	coolers, merchandisers, etc.
HBP	HIGH BACK PRESSURE	APPLICATIONS:
	Evaporating temperature between -15 °C and +10 °C	fresh food cabinets, bottle coolers, dehumidifiers, etc.

EXPANSION DEVICE

C	Capillary Tube.
V	Expansion Valve.

TEST CONDITIONS

TEST CONDITIONS	APPLICATION	EVAPORATING TEMPERATURE °C	CONDENSING TEMPERATURE °C	RETURN GAS TEMPERATURE °C	SUB-COOLING	AMBIENT TEMPERATURE °C
EN 12900	LBP	-35	40	20 (*)	0	32
	MBP	-10	45			
	HBP	5	50			
ARI 540	LBP	-23,3	48,9	4,4	0	35
	MBP	-6,7	48,9	4,4		
	HBP	7,2	54,4	18,3		
ASHRAE SUBCOOLED	LBP	-23,3	54,4	32,2	22,2K	32,2
	MBP and HBP	7,2	54,4	35	8,3K	35
CECOMAF	LBP	-25	55	32	0	32

(*) For EMT and NE models return gas temperature is 32°C.

UNIT CONVERSION TABLE

UNIT CONVERSION	
1 watt	3,41 Btu/h
1 watt	0,86 kcal/h
1 kcal/h	3,97 Btu/h

COOLING TYPE

STATIC (S)	Compressor doesn't require forced cooling, but its installation is requiring adequate cool by ambient air to avoid overheating.
FAN (F)	Compressor requires forced cooling through the use of a fan.

OIL TYPE (the number indicates the viscosity)

AB	Alkylbenzene and Alquilb
POE	Ester
MIN	Mineral

MOTOR TORQUE

LST	LOW STARTING TORQUE Compressor with RSIR-RSCR-PSC electrical motor for systems with capillary tube and with equalized pressures at start up.
HST	HIGH STARTING TORQUE Compressor with CSIR-CSR and3ph electrical motor for systems with equalized or not equalized pressures at start up.

ELECTRICAL MOTOR TYPES

RSIR	Resistance Start – Inductive Run This motor type, used iinto low power compressors, has a low starting torque (LST) and must be applied only to capillary tube systems where the pressures equalize. The motor is characterized by a start winding with high ohmic resistance and must be disconnected when it reaches the stabilized rotational speed. An electromagnetic relay, calibrated for the motor current, disconnects the start winding at the end of the start up. An alternative to the electromagnetic relay is, for some models, a PTC solid state-starting device.
RSCR	Resistance Start – Capacitive Run Similar to RSIR motor version but uses a PTC solid state starting device and a permanently connected run capacitor to improve its efficiency.
CSIR	Capacitive Start – Inductive Run Similar to RSIR motor, with a different start winding in series with a start capacitor of suitable capacitance to get a high starting torque.
CSR	Capacitive Start & Run CSR version with capacitive run and start windings. Same as PSC motor but with a start capacitor in series with the start winding. A potential starting relay, calibrated for each motor, disconnects the start capacitor at the end of the start. The motor is characterized by a high starting torque (HST) and high efficiency.
PSC	Permanent Split Capacitor PSC version with capacitive run winding. This motor is characterized by the run capacitor permanently connected in series with the start winding; both remain connected even after the motor starts. The starting torque is enough to guarantee that the compressor starts only with balanced pressures in capillary tubes systems or with a pressure equalizer.
3Ø	Three Phase Three-phase windings with star connections.
BLDC	Brushless DC motor - motor with permanent magnets Motor-compressor with this type of motor is provided with inverter drive which allows motor-compressor to work in various RPM (rotation per minute). RPM modulation result in cooling capacity adjustment according actual appliance needs which results in energy savings and more precise temperature regulation.

ELECTRICAL COMPONENTS

TYPE OF MOTOR	STARTING DEVICE					CAPACITORS	
	Overload Protector (*)	Current Relay	Voltage Relay	PTC	TSD	Start	Run
RSIR	√	√	X	√	X	X	X
RSCR	√	X	X	√	√	X	√
CSIR	√	√	X	X	X	√	X
CSR	√	X	√	X	X	√	√
PSC	√	X	X	X	X	X	√
3-Phases	√	X	X	X	X	X	X

(*) Some models approved with Internal OLP

VOLTAGE & FREQUENCY

Code	Voltage & Frequency	Voltage Working Range		Minimum Start Voltage	
		50Hz	60Hz	50Hz	60Hz
A	220 - 240V 50Hz 1 ~	198V ÷ 254V		187V	
B	200 - 230V 50Hz / 208 - 230V 60Hz 1 ~	180V ÷ 244V	187V ÷ 244V	170V	177V
C	220V 50Hz 1 ~	200V ÷ 242V		187V	
D	208 - 230V 60Hz 1 ~		187V ÷ 244V		177V
E	115 - 127V 60Hz 1 ~		103V ÷ 134V		98V
F	100V 50Hz / 100 - 127V 60Hz 1 ~	90V ÷ 110V	90V ÷ 134V	85V	85V
G	115V 60Hz 1 ~		103V ÷ 127V		98V
I	220 - 240V 50/60Hz 1 ~	198V ÷ 254V	198V ÷ 254V	187V	187V
J	230V 60Hz 1 ~		207V ÷ 253V		195V
K	200 - 220 V 50Hz / 230 V 60 Hz 1~	180V ÷ 234V	207V ÷ 253V	170V	195V
M	380 - 420V 50Hz / 440 - 480V 60 Hz 3 ~	332V ÷ 445V	396V ÷ 509V	323V	374V
N	200 - 240V 50Hz / 230V/60Hz 1 ~	180V ÷ 254V	207V ÷ 253V	170V	195V
P	380V 60Hz 3 ~		342V ÷ 418V		323V
Q	100V 50/60Hz 1~	90V ÷ 110V	90V ÷ 110V	85V	85V
R	200V 50/60Hz 3 ~	180V ÷ 220V	180V ÷ 220V	170V	170V
S**	400V 50Hz / 440V 60Hz 3 ~	360V ÷ 440V	396V ÷ 484V	340V	374V
V	230V 50Hz 1 ~	207V ÷ 253V		195V	
X	220 - 240V 50/60Hz 1 ~	150V (160V*) ÷ 240V		150V (160V*)	
Z	200 - 230V 60Hz 1 ~		180V ÷ 244V		170V

* Depending on compressor family, for details contact Technical Support.

** For specific model refer to datasheet or consult with Embraco technical support team.

COMPRESSOR FIXING & VALVE TYPE


FIXING TYPE	EM / VES	NE / VNE	NT	NJ
A	Grommets & Sleeves	Grommets & Sleeves	Grommets & Sleeves	Grommets & Sleeves
P	Grommets & Snap On	Grommets & Snap On	X	X

VALVE TYPE	EM / VES	NE / VNE	NT	NJ
V	X	X	X	Rotolock Valve Threated Connection
Z	X	X	X	Rotolock Valve Brazed Connection


IDENTIFICATION LABEL



- 1 Compressor model
- 2 Supply Voltage
- 3 Bill of Materials code
- 4 Serial Number
- 5 Agency Approval Marks
- 6 Date code or Production date
- 7 Oil type and quantity
- 8 Refrigerant type
- 9 Current Consumption (Rated Load Amperage, when applicable)
- 10 Locked Rotor Amperage (when applicable)



- 1 Compressor model
- 2 Supply Voltage
- 3 Bill of Materials code
- 4 Serial Number
- 5 Agency Approval Marks
- 6 Date code or Production date
- 8 Refrigerant type
- 10 Locked Rotor Amperage (when applicable)



PACKAGING

EMT / EMY / EMX / EMC / VES					
PACKAGING TYPE	CODE	QUANTITY PER PALLET	ELECTRICAL COMPONENTS		NOTE
			ASSEMBLED	NOT ASSEMBLED	
SINGLE PACK	A	70	√	X	
	J	56	√	X	
MULTIPLE PACK	R	100	X	√	Electrical components and accessories delivered separately
	S	120	X	√	
	G	100	√	X	Accessories delivered separately
	O	74	√	X	
	W	88	√	X	
	V	100	√	X	
	E	120	√	X	

NE / NEK / NEU / VNEK / VNEU					
PACKAGING TYPE	CODE	QUANTITY PER PALLET	ELECTRICAL COMPONENTS		NOTE
			ASSEMBLED	NOT ASSEMBLED	
SINGLE PACK	A	56	√	√	
	F	44	√	√	CSR electrical box included
	J	56	√	X	
MULTIPLE PACK	H	28	√	X	CSR electrical box included
	M	80	X	√	Electrical components and accessories delivered separately
	N	40	X	√	
	O	74	√	X	
	Q	37	√	X	

NT / NTU					
PACKAGING TYPE	CODE	QUANTITY PER PALLET	ELECTRICAL COMPONENTS		NOTE
			ASSEMBLED	NOT ASSEMBLED	
SINGLE PACK	A	44	√	√	
	F	44	√	√	CSR electrical box included
MULTIPLE PACK	C	36	X	√	Electrical components and accessories delivered separately
	Z	24	√	X	

NJ					
PACKAGING TYPE	CODE	QUANTITY PER PALLET	ELECTRICAL COMPONENTS		NOTE
			ASSEMBLED	NOT ASSEMBLED	
SINGLE PACK	A	33	X	√	
	F	33	X	√	CSR electrical box included
MULTIPLE PACK	C	36	X	√	Electrical components and accessories delivered separately
	Y	28	√	X	

F / EG / VEG / VEM / VES				
PACKAGING TYPE	CODE	QUANTITY PER PALLET	ELECTRICAL COMPONENTS	
			ASSEMBLED	NOT ASSEMBLED
MULTIPLE PACK	F / EG / VEG	72	√	X
		80	X	√
	VEM	100	√	√
	VES	120	√	√

GENERAL DATA & PERFORMANCE



VARIABLE CAPACITY COMPRESSOR WITH INVERTER
(FULLMOTION)

R134a • L/M/HBP • 50 - 60Hz

MODEL	DISPL. cm ³	VOLTAGE FREQUENCY	MOTOR TYPE	TORQUE	APPL.	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - EN12900 5 °C / 50 °C		SPEED RANGE RPM	WEIGHT kg	MAX HEIGHT A mm	LRA A		COOLING TYPE	FAN AIR FLOW m ³ /h	OIL CHARGE cm ³	OIL TYPE	EXP. DEVICE	DRAWINGS		INVERTER				MODEL
						CAPACITY RANGE W	EFFICIENCY RANGE W/W	CAPACITY RANGE W	EFFICIENCY RANGE W/W											EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	INPUT VOLTAGE FREQUENCY	MODEL	OUTPUT POWER W	CONTROL MODE	
VEMY3H	3,00	230 V 53-150Hz 3 ~	BPM	LST	LBP	41-126	1,48-1,55	-	-	1600-4500	7,5	180	2,1		S		220	POE10	C	DWG23	CON01-02-03-04-05	220-240V 50/60Hz	VCC3	200	Drop-in, Frequency	VEMY3H
VEMY4H	3,97	230 V 53-150Hz 3 ~	BPM	LST	LBP	63-170	1,55-1,66	-	-	1600-4500	7,5	180	2,1		S		220	POE10	C	DWG23	CON01-02-03-04-05	220-240V 50/60Hz	VCC3	200	Drop-in, Frequency	VEMY4H
VEMY5H	4,99	230 V 53-150Hz 3 ~	BPM	LST	LBP	84-206	1,60-1,76	-	-	1600-4500	7,5	180	2,1		S		220	POE10	C	DWG23	CON01-02-03-04-05	220-240V 50/60Hz	VCC3	200	Drop-in, Frequency	VEMY5H
VEMY6HH	5,72	230 V 53-150Hz 3 ~	BPM	LST	L/M/HBP	113-229	1,60-1,68	-	-	1600-4500	7,5	180	2,1		F	520	220	POE10	C	DWG23	CON01-02-03-04-05	220-240V 50/60Hz	VCC3-CO	320	Drop-in, Serial, Frequency	VEMY6HH
VEGT7H	7,15	230 V 53-150Hz 3 ~	BPM	LST	LBP	129-290	1,46-1,62	-	-	1600-4500	10	200	3,3		S		430	POE10	C	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	VCC3	200	Drop-in, Frequency	VEGT7H
VEGT8HB	7,95	230 V 53-150Hz 3 ~	BPM	LST	L/MBP	137-340	1,55-1,76	-	-	1600-4500	10	200	3,3		F	520	430	POE10	C	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	VCC3-CO	320	Drop-in, Frequency	VEGT8HB
VEGT11HB	10,61	230 V 53-150Hz 3 ~	BPM	LST	L/MBP	191-429	1,49-1,66	-	-	1800-4500	10	200	3,3		F	520	430	POE10	C	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	VCC3-CO	320	Drop-in, Frequency	VEGT11HB
VNEK610Z	10,00	220-240V 50/60Hz 1 ~	BPM	HST	HBP	-	-	630-1231	2,55-2,07	2000-4500	11,6	206	-		F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	HP	800	Drop-in, Serial, Frequency	VNEK610Z
VNEK614Z	14,30	220-240V 50/60Hz 1 ~	BPM	HST	HBP	-	-	905-1637	2,46-1,9	2000-4500	11,6	206	-		F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	HP	1000	Drop-in, Serial, Frequency	VNEK614Z

R404A/R507/R452A • LBP - MBP • 50 - 60Hz

MODEL	DISPL. cm ³	VOLTAGE FREQUENCY	MOTOR TYPE	TORQUE	APPL.	RATED POINT - EN12900 -35 °C / 40 °C		RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - EN12900 -10 °C / 45 °C		SPEED RANGE RPM		WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m ³ /h	OIL CHARGE cm ³	OIL TYPE	EXP. DEVICE	DRAWINGS		INVERTER			MODEL	
						CAPACITY RANGE W	EFFICIENCY RANGE W/W	CAPACITY RANGE W	EFFICIENCY RANGE W/W	CAPACITY RANGE W	EFFICIENCY RANGE W/W											EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	INPUT VOLTAGE FREQUENCY	MODEL	OUTPUT POWER W		CONTROL MODE
VNEK206GK	6,2	220-240V 50/60Hz 1 ~	BPM	HST	LBP	126-262	0,93-0,99	226-468	1,21-1,26			2000-4500		11,6	206	-	F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	500	Drop-in, Serial, Frequency	VNEK206GK
VNEK606GK	6,2	220-240V 50/60Hz 1 ~	BPM	HST	MBP					380-801	1,55-1,78	2000-4500		11,6	206	-	F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	800	Drop-in, Serial, Frequency	VNEK606GK
VNEK609GK	8,8	220-240V 50/60Hz 1 ~	BPM	HST	MBP					534-1084	1,64-1,83	2000-4500		11,6	206	-	F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VNEK609GK
VNEK212GK	12,1	220-240V 50/60Hz 1 ~	BPM	HST	LBP	245-465	1,01-1,11	442-860	1,26-1,33			2000-4500		11,6	206	-	F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VNEK212GK

R290 • LBP - MBP • 50 - 60Hz

MODEL	DISPL. cm ³	VOLTAGE FREQUENCY	MOTOR TYPE	TORQUE	APPL.	RATED POINT - EN12900 -35 °C / 40 °C		RATED POINT - ASHRAE -23,3 °C / 54,4 °C		SPEED RANGE RPM	WEIGHT kg	MAX HEIGHT A mm	LRA A		COOLING TYPE	FAN AIR FLOW m ³ /h	OIL CHARGE cm ³	OIL TYPE	EXP. DEVICE	DRAWINGS		INVERTER				MODEL
						CAPACITY RANGE W	EFFICIENCY RANGE W/W	CAPACITY RANGE W	EFFICIENCY RANGE W/W											EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	INPUT VOLTAGE FREQUENCY	MODEL	OUTPUT POWER W	CONTROL MODE	
FMFT406U	6,44	103-140V 60Hz 1 ~	BPM	LST/HST	L/MBP	-	-	140-510	1,74-1,86	1400-4500	10,28	201			F		430	POE 22	C/V	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	VCC3-CO	320	Drop-in, Serial, Frequency	FMFT406U
FMFT406U	6,44	220-240V 50/60Hz 1 ~	BPM	LST/HST	L/MBP	-	-	140-510	1,74-1,86	1400-4500	10,28	201			F		430	POE 22	C/V	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	FMFT406U
VNEK207U	7,3	220-240V 50/60Hz 1 ~	BPM	HST	LBP	131-286	1,05-1,14	-	-	2000-4500	11,6	206	-		F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VNEK207U
VEGT8U	7,95	220-240V 50/60Hz 1 ~	BPM	LST	L/MBP	-	-	239-647	1,73-1,74	1800-4500	10,28	201			F		430	POE 22	C/V	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VEGT8U
FMFT411U	11,14	220-240V 50/60Hz 1 ~	BPM	LST/HST	L/MBP	208-501	1,47-1,57	349-867	1,76-1,84	1800-4500	10,9	201	6,5		F		430	POE 22	C/V	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	FMFT411U
FMFT413U	12,92	220-240V 50/60Hz 1 ~	BPM	LST/HST	L/MBP	234-572	1,46-1,54	403-998	1,72-1,84	1800-4500	10,9	201	6,5		F		430	POE 22	C/V	DWG09	CON01-02-03-10-11	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	FMFT413U
VNEK213U	13,5	220-240V 50/60Hz 1 ~	BPM	HST	LBP	255-525	1,14-1,25	419-908	1,36-1,44	2000-4500	11,6	206	-		F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VNEK213U
VNEU213U	13,5	220-240V 50/60Hz 1 ~	BPM	HST	LBP	262-574	1,22-1,28	-	-	2000-4500	11,4	206	-		F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VNEU213U
VNEU217U	16,8	220-240V 50/60Hz 1 ~	BPM	HST	LBP	346-699	1,20-1,29	-	-	2000-4500	11,4	206	-		F	520	500	POE 22	C/V	DWG04	CON07-08-09	220-240V 50/60Hz	CF10	1000	Drop-in, Serial, Frequency	VNEU217U

R600A • LBP - L/MBP • 50 - 60Hz

MODEL	DISPL. cm ³	VOLTAGE FREQUENCY	MOTOR TYPE	TORQUE	APPL.	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - CECOMAF -25 °C / 55 °C		SPEED RANGE RPM	WEIGHT kg	MAX HEIGHT A mm	LRA A		COOLING TYPE	FAN AIR FLOW m ³ /h	OIL CHARGE cm ³	OIL TYPE	EXP. DEVICE	DRAWINGS		INVERTER				MODEL
						CAPACITY RANGE W	EFFICIENCY RANGE W/W	CAPACITY RANGE W	EFFICIENCY RANGE W/W											EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	INPUT VOLTAGE FREQUENCY	MODEL	OUTPUT POWER W	CONTROL MODE	
VESD3C	3,0	220-240V 50/60Hz 1 ~	BPM	LST	LBP	8-44	1,18-1,27	6-26	0,96-1,05	1300-4500	6	135	2,1		S	-	200	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESD3C
VESA5C	5,2	220-240V 50/60Hz 1 ~	BPM	LST	L/MBP	33-117	1,69-1,65	24-86	1,33-1,28	1300-4500	6,1	135	2,1		S	-	200	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Frequency	VESA5C
VESD5C	5,2	220-240V 50/60Hz 1 ~	BPM	LST	L/MBP	34-126	1,77-1,73	25-93	1,37-1,35	1300-4500	6,5	135	2,1		S	-	190	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESD5C
VESA7C	7,2	220-240V 50/60Hz 1 ~	BPM	LST	LBP	47-179	1,65-1,78	34-133	1,29-1,39	1300-4500	6	135	2,1		S	-	200	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Frequency	VESA7C
VESD7C	7,2	220-240V 50/60Hz 1 ~	BPM	LST	LBP	49-184	1,82-1,86	36-138	1,42-1,47	1300-4500	6,8	135	2,1		S	-	190	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESD7C
VESA9C	9,0	220-240V 50/60Hz 1 ~	BPM	LST	LBP	66-223	1,73-1,71	49-168	1,38-1,35	1300-4500	6	135	2,1		S	-	200	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Frequency	VESA9C
VESC9C	9,0	220-240V 50/60Hz 1 ~	BPM	LST	LBP	66-230	1,80-1,76	49-174	1,41-1,39	1300-4500	6,5	135	2,1		S	-	190	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESC9C
VESD9C	9,0	220-240V 50/60Hz 1 ~	BPM	LST	LBP	66-230	1,86-1,79	49-174	1,46-1,41	1300-4500	6,8	135	2,1		S	-	190	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESD9C
VESC11C	11,1	220-240V 50/60Hz 1 ~	BPM	LST	LBP	86-276	1,89-1,76	64-209	1,49-1,38	1300-4500	6,5	135	2,1		S	-	190	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESC11C
VESD11C	11,1	220-240V 50/60Hz 1 ~	BPM	LST	LBP	86-276	1,93-1,78	64-209	1,52-1,41	1300-4500	6,8	135	2,1		S	-	190	AB 5	C	DWG22	CON04-05-06	220-240V 50/60Hz	VES	200	Drop-in, Serial, Frequency	VESD11C

R508B/R170 • ULBP • 50 Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	REFRIGERANT	RATED POINT - EN12900 -85 °C / -30 °C			CONDENSING TEMP. °C	EVAPORATING TEMPERATURE °C W			WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
								CAPACITY W	EFFICIENCY W/W			-95	-85	-75						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
NT2178ULT	17.4	1	220-240V 50Hz 1 ~	CSR	HST	ULBP	R508B	429	1.27		-30	180	422	919	17.8	220	21.5	F	520	450	POE 22	C/V	DWG16	SM26	NT2178ULT
							R170	399	1.21			204	401	813											
NT2192ULT	22.4	1	220-240V 50Hz 1 ~	CSR	HST	ULBP	R508B	545	1.30		-30	236	561	1097	17.8	234	29	F	520	450	POE 22	C/V	DWG16	SM26	NT2192ULT
							R170	516	1.24			216	501	926											
NT2212ULT	27.8	1 1/2	220-240V 50Hz 1 ~	CSR	HST	ULBP	R508B	702	1.32		-30	318	665	1220	17.8	234	27	F	520	450	POE 22	C/V	DWG16	SM26	NT2212ULT
							R170	663	1.29			311	670	1230											

R508B/R170 • ULBP • 60 Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	REFRIGERANT	RATED POINT - EN12900 -85 °C / -30 °C			CONDENSING TEMP. °C	EVAPORATING TEMPERATURE °C W			WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
								CAPACITY W	EFFICIENCY W/W			-95	-85	-75						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
NT2178ULT	17.4	1	115V 60Hz 1 ~	CSR	HST	ULBP	R508B	516	1.26		-30	232	528	1015	17.8	220	54	F	520	450	POE 22	C/V	DWG16	SM26	NT2178ULT
							R170	471	1.21			230	464	814											
NT2178ULT	17.4	1	208-230V 60Hz 1 ~	CSR	HST	ULBP	R508B	534	1.27		-30	223	544	1037	16.9	220	28	F	520	450	POE 22	C/V	DWG16	SM26	NT2178ULT
							R170	464	1.18			161	471	930											
NT2192ULT	22.4	1	208-230V 60Hz 1 ~	CSR	HST	ULBP	R508B	676	1.27		-30	339	676	1232	17.8	234	35	F	520	450	POE 22	C/V	DWG16	SM26	NT2192ULT
							R170	594	1.21			290	587	1048											

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R134a • LBP - L/MBP • 50Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - EN12900 -35°C / 40 °C		COOLING CAPACITY EN12900							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL	
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W										CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE		
													-30	-25	-20	-15	-10												-5
EMY3109Z	4,0	1/10	220-240V 50Hz 1 ~	RSIR	LST	L/MBP	105	1,37	-	-	55		-	-	-	-	-	-	7,3	166	4,0	S	-	150	POE 10	C	DWG01	SM00	EMY3109Z
											45		-	-	-	-	-	-											
EMY3111Z	4,5	1/8	220-240V 50Hz 1 ~	RSIR	LST	L/MBP	129	1,41	62	1,01	55		81	113	153	202	260	325	7,7	171	5,0	S	-	150	POE 10	C	DWG01	SM00	EMY3111Z
											45		90	123	165	216	275	343											
EMY3115Z	6,1	1/6	220-240V 50Hz 1 ~	RSIR/RSCR	LST	L/MBP	163 / 171	1,39 / 1,51	-	-	55		-	-	-	-	-	-	7,6	171	-	S		150	POE 10	C	DWG01	SM00-SM01	EMY3115Z
											45		-	-	-	-	-	-											
NEK1116Z	7,4	1/5	220-240V 50Hz 1 ~	RSIR/RSCR	LST	LBP	194	1,44	93	1,12	55		-	141	262	245	312	390	10,8	200	5,3	S	-	350	POE 22	C	DWG02	SM00-SM01	NEK1116Z
											45		126	172	225	291	367	460											
NEK2116Z	7,4	1/5	220-240V 50Hz 1 ~	CSIR	HST	LBP	187	1,22	93	0,89	55		-	136	184	241	305	378	10,4	187	10,0	S	-	350	POE 22	C/V	DWG03	SM05	NEK2116Z
											45		121	166	221	284	357	436											
NEK1118Z	8,4	1/4	220-240V 50Hz 1 ~	RSIR/RSCR	LST	LBP	224	1,43	111	1,08	55		-	163	217	283	357	446	10,7	200	6,9	S	-	350	POE 22	C	DWG02	SM00-SM01	NEK1118Z
											45		144	195	256	328	417	519											
NE1121Z	9,3	1/4	220-240V 50Hz 1 ~	RSIR	LST	LBP	253	1,28	125	0,89	55		-	186	246	319	403	500	10,9	200	16,5	F	520	350	POE 22	C	DWG03	SM03	NE1121Z
											45		166	220	288	370	464	572											
NE1121Z	9,3	1/4	200-220V 50Hz / 230V 60Hz 1 ~	RSIR	LST	LBP	253	1,28	126	0,93	55		-	217	288	373	472	584	10,9	200	18,0	F	520	350	POE 22	C	DWG03	SM03	NE1121Z
											45		193	258	337	433	544	669											
NE2121Z	9,3	1/4	220-240V 50Hz 1 ~	CSIR	HST	LBP	250	1,23	124	0,86	55		-	183	245	317	403	500	10,9	200	12,6	F	520	350	POE 22	C/V	DWG03	SM05-SM29	NE2121Z
											45		163	217	285	368	465	575											
NE2121Z	9,3	1/4	200-220V 50Hz / 230V 60Hz 1 ~	CSIR	HST	LBP	253	1,28	126	0,90	55		-	186	246	319	403	500	11,6	206	15,0	F	520	350	POE 22	C/V	DWG03	SM05-SM29	NE2121Z
											45		166	220	288	370	464	572											
EMY3125Z*	10,6		220-240V 50Hz 1 ~	RSIR	LST	L/MBP	UD	UD	UD	UD	55		-	-	-	-	-	-	UD	UD	UD	F	270	150	POE 10	C	DWG01	SM00	EMY3125Z*
											45		-	-	-	-	-	-											
NE1130Z	12,1	1/3	220-240V 50Hz 1 ~	RSIR	LST	LBP	323	1,32	161	0,85	55		-	238	313	402	506	624	10,9	200	16,3	F	520	350	POE 22	C	DWG03	SM03	NE1130Z
											45		211	281	366	466	583	715											
NE1130Z	12,1	1/3	200-220V 50Hz / 230V 60Hz 1 ~	RSIR	LST	LBP	323	1,24	161	0,86	55		-	238	313	402	506	624	10,9	200	22,0	F	520	350	POE 22	C	DWG03	SM03	NE1130Z
											45		211	281	366	466	583	715											
NE2130Z	12,1	1/3	220-240V 50Hz 1 ~	CSIR	HST	LBP	343	1,32	171	0,85	55		-	255	332	426	536	660	10,9	200	13,2	F	520	350	POE 22	C/V	DWG03	SM05-SM29	NE2130Z
											45		227	298	386	491	613	753											
NE2130Z	12,1	1/3	100V 50/60Hz 1 ~	CSIR	HST	LBP	323	1,20	161	1,16	55		-	230	305	391	490	601	10,9	200	39,0	F	520	350	POE 22	C/V	DWG03	SM05	NE2130Z
											45		204	268	348	444	555	684											
NEU4130Z	12,1	1/3	220-240V 50Hz 1 ~	CSIR	HST	L/MBP	346	1,31	172	0,96	55		-	-	-	-	-	-	10,0	187	13,0	F	520	350	POE 22	C/V	DWG03	SM05	NEU4130Z
											45		-	-	-	-	-	-											
NE2134Z	14,3	1/3	220-240V 50Hz 1 ~	CSIR	HST	LBP	359	1,23	179	0,90	55		-	267	351	453	571	711	11,6	206	17,0	F	520	350	POE 22	C/V	DWG03	SM05	NE2134Z
											45		234	313	410	526	662	822											
NEK2140Z	16,8	1/2	220-240V 50Hz 1 ~	CSIR	HST	LBP	429	1,31	217	1,02	55		-	319	421	543	686	820	11,6	206	17	F	520	350	POE 22	C/V	DWG03	SM05	NEK2140Z
											45		274	372	493	635	799	991											

R134a • LBP - L/MBP - L/M/HBP • 50Hz - BR portfolio

MODEL	DISPL. cm ³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		CONDENSING TEMPERATURE °C		COOLING CAPACITY ASHRAE LBP								WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m ³ /h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W			EVAPORATING TEMPERATURE °C W													OIL			EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
											-35	-30	-25	-20	-15	-10	-5	0						CHARGE cm ³	TYPE				
EM20HHR	2,27	1/12	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	50	0,86	55		17	28	42	59	80	105	135	170	6,8	158	6,5	S/F	520	160	POE 22	C	DWG10	SM07	EM20HHR
EMIE30HER	2,83	1/10	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	73	1,16	55		26	44	65	90	120	155	196	-	7,2	158	7	S/F	520	180	POE 10	C	DWG10	SM07	EMIE30HER
EMIS30HHR	3,00	1/10	220V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	79	0,93	55		27	46	69	95	126	163	207	260	6,8	158	9	S/F	520	160	POE 22	C	DWG10	SM07	EMIS30HHR
EMIE40HJP	3,40	1/8	220V 50/60Hz 1 ~	RSIR	LST	LBP	95	1,15	55		40	65	97	132	166	196	-	-	6,6	158	4,2	S	-	180	POE 10	C	DWG10	SM07	EMIE40HJP
EMI45HER	3,77	1/8	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	100	1,21	55		43	66	92	123	161	208	-	-	7,7	167	10	S	-	160	POE 22	C	DWG10	SM07	EMI45HER
EM45HHR	3,77	1/8	220-240V 50Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	102	1,03	55		43	62	86	117	155	201	256	321	7,7	171	9	S/F	520	160	POE 22	C	DWG10	SM07	EM45HHR
EM50HNP	4,99	1/8	220-240V 50Hz 1 ~	RSIR/RSCR	LST	LBP	126	1,22	55		45	75	109	149	197	256	-	-	7,7	167	10	S	-	160	POE 22	C	DWG10	SM07	EM50HNP
EMIE65HER	5,19	1/6	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	149	1,22	55		71	100	136	179	231	290	-	-	8,3	166	12,5	S/F	520	180	POE 10	C	DWG10	SM07	EMIE65HER
EGAS70HLR	5,56	1/5+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	164	1,47	55		68	102	147	202	265	337	-	-	10,4	195	14,4	S	-	230	POE 10	C	DWG09	SM09	EGAS70HLR
EMI70HER	5,89	1/5	220V 50Hz 1 ~	RSIR/CSIR	LST	LBP	166	1,18	55		71	100	136	179	231	290	-	-	8,3	166	12,5	S	-	180	POE 22	C	DWG10	SM07	EMI70HER
EMU65HLP	5,96	1/4	200-230V 50Hz 1 ~	RSIR	LST	LBP	185	1,45	55		92	127	169	219	278	345	-	-	7,9	166	7,5	S	-	180	POE 22	C	DWG10	SM07	EMU65HLP
EMYE70HEP	5,96	1/5	220-240V 50/60Hz 1 ~	RSIR	LST	LBP	168	1,43	55		92	127	169	219	278	345	-	-	7,9	166	7,5	S	-	180	POE 10	C	DWG10	SM07	EMYE70HEP
EGAS80HLR	6,36	1/4+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	195	1,52	55		80	125	173	228	293	372	-	-	10	195	14,5	S/F	520	230	POE 10	C	DWG09	SM09	EGAS80HLR
FFU70HAK	6,36	1/4	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	185	1,43	55		80	119	166	224	293	375	471	-	10,7	201	12,8	S/F	520	280	POE 10	C	DWG09	SM08	FFU70HAK
FFUS70HAK	6,36	1/4	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	191	1,42	55		77	124	170	222	285	363	462	587	10,2	201	14,5	S/F	520	230	POE 10	C	DWG09	SM08	FFUS70HAK
FFUS80HAK	6,76	1/4+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	201	1,37	55		95	133	183	244	319	407	509	626	10	201	14,5	S/F	520	230	POE 10	C	DWG09	SM08	FFUS80HAK
FF7,5HBK	6,92	1/5+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	154	1,00	55		71	106	149	202	263	341	431	537	10,7	195	16,7	S	-	280	POE 22	C	DWG09	SM08	FF7,5HBK
EGAS90HLR	7,15	1/3-	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	219	1,50	55		97	144	198	261	336	426	-	-	10,5	195	14,3	S	-	230	POE 10	C	DWG09	SM09	EGAS90HLR
EGAS100HLP	7,95	1/3	220-240V 50Hz 1 ~	RSIR/RSCR	LST	LBP	241	1,58	55		108	157	222	304	402	514	-	-	11	201	8,5	S	-	230	POE 10	C	DWG09	SM09	EGAS100HLP
EGAS100HLR	7,95	1/3	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	251	1,52	55		108	164	226	299	384	485	-	-	11	201	16,9	F	520	230	POE 10	C	DWG09	SM09	EGAS100HLR
FFUS100HAK	7,95	1/3	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	248	1,43	55		123	167	226	302	393	500	623	763	10,6	201	17,6	S/F	520	350	POE 10	C	DWG09	SM08	FFUS100HAK
FF8,5HBK	7,95	1/4	220-240V 50Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	194	1,11	55		82	119	168	230	306	398	506	632	10,8	195	18,2	S/F	520	280	POE 22	C	DWG09	SM08	FF8,5HBK
FFI10HAK	9,04	1/3	220-230V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	249	1,30	55		106	154	220	302	400	512	636	-	10,9	201	18	S/F	520	280	POE 22	C	DWG09	SM08	FFI10HAK
EGU130HLR	10,61	1/3+	220-240V 50Hz 1 ~	RSIR/CSIR	LST	LBP	313	1,50	55		141	211	288	378	489	626	-	-	10,8	201	17,5	F	520	230	POE 10	C	DWG09	SM09	EGU130HLR
FFU130HAX	10,61	1/3+	220-240V 50Hz 1 ~	CSIR	LST/HST	L/MBP	309	1,38	55		132	203	280	370	477	607	764	-	11,3	201	17,5	F	520	280	POE 10	C/V	DWG09	SM08	FFU130HAX
FFI12HBK	11,14	1/3+	220-240V 50Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	319	1,25	55		152	210	287	382	498	633	790	968	11,5	201	20	F	520	280	POE 22	C	DWG09	SM08	FFI12HBK
FFU160HAX	12,92	1/2	220-240V 50Hz 1 ~	CSIR	LST/HST	L/MBP	374	1,42	55		188	268	356	460	584	736	918	1139	10,8	201	17,7	F	520	280	POE 22	C/V	DWG09	SM08	FFU160HAX

R134a • HBP • 50Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7.2 °C / 54.4 °C		RATED POINT - EN12900 5 °C / 50 °C		COOLING CAPACITY EN12900						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL		
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W									CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE			
													-15	-10	-5	0												5	10
EMT37HDP	3.4	1/8	220-240V 50Hz 1 ~	RSIR	LST	HBP	351	2.55	321	2.46	55 45		- 142	153 181	194 228	241 245	294 343	355 412	7.2	158	4.3	S	-	180	POE 22	C	DWG01	SM00	EMT37HDP
EMT45HDR	4.0	1/8	220-240V 50Hz 1 ~	CSIR	HST	HBP	421	2.66	379	2.58	55 45		- 146	150 184	189 229	237 284	298 402	361 423	7.7	166	5.4	S	-	180	POE 10	C/V	DWG01	SM05	EMT45HDR
EMT50HDP	4.5	1/6	220-240V 50Hz 1 ~	RSIR	LST	HBP	475	2.58	423	2.47	55 45		- 191	203 242	256 303	318 374	388 456	472 549	7.7	166	5.4	S	-	180	POE 22	C	DWG01	SM00	EMT50HDP
EMT6144Z	5.2	1/5	220-240V 50Hz 1 ~	CSIR	HST	HBP	577	2.6	519	2.53	55 45		- 232	250 294	313 367	388 395	474 549	573 661	7.8	166	8.5	F	270	180	POE 22	C/V	DWG01	SM05	EMT6144Z
EMT6160Z	6.8	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	720	2.4	648	2.34	55 45		- 298	322 377	403 469	495 504	600 696	718 830	7.8	166	9.8	F	520	180	POE 22	C/V	DWG01	SM05	EMT6160Z
NEK6160Z	7.3	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	716	2.41	663	2.41	55 45		- 281	296 355	376 448	472 481	586 687	716 834	10.4	187	11.5	F	520	350	POE 22	C/V	DWG03	SM05	NEK6160Z
NEK6160Z	7.3	1/4	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	717	2.41	663	2.41	55 45		- 277	290 350	371 442	470 478	586 684	720 833	10.4	187	13.5	F	520	350	POE 22	C/V	DWG03	SM05	NEK6160Z
EMT6170Z	7.7	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	806	2.26	725	2.18	55 45		- 330	358 418	448 522	550 559	663 771	789 915	7.8	166	10.4	F	520	180	POE 22	C/V	DWG01	SM05	EMT6170Z
EMY6170Z	8.0	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	835	2.56	712	2.39	55 45		- -	- 508	435 628	540 766	659 921	794 921	7.7	171	10.5	F	520	145	POE 10	C/V	DWG01	SM05	EMY6170Y
NEK6170Z	8.4	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	882	2.35	775	2.45	55 45		- 336	360 422	453 527	562 572	689 798	833 964	10.2	200	14	F	520	350	POE 22	C/V	DWG03	SM05	NEK6170Z
NEK6170Z	8.4	1/4	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	841	2.44	775	2.46	55 45		- 335	358 420	451 526	563 573	693 802	841 971	10.8	200	18	F	520	350	POE 22	C/V	DWG03	SM05	NEK6170Z
NEK6170Z	8.4	1/4	100V 50/60Hz 1 ~	CSIR	HST	HBP	823	2.18	762	2.16	55 45		- 337	313 367	384 445	496 505	650 742	844 958	10.4	187	31	F	520	350	POE 22	C/V	DWG03	SM05	NEK6170Z
NEK6187Z	10.0	1/3	220-240V 50Hz 1 ~	CSIR	HST	HBP	1019	2.29	896	2.38	55 45		- 378	402 477	511 600	642 654	793 918	965 1113	11	200	15	F	520	350	POE 22	C/V	DWG03	SM05	NEK6187Z
NEK6187Z	10.0	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	965	2.39	894	2.4	55 45		- 375	439 479	538 606	657 669	796 928	955 1123	11.6	206	18	F	520	350	POE 22	C/V	DWG03	SM05	NEK6187Z
NEU6187Z	10.0	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	1014	2.44	-	-	55 45		- -	- -	- -	- -	- -	- -	10.5	200	16	F	520	350	POE 22	C/V	DWG03	SM05	NEU6187Z
NEU6187Z	10.0	1/3	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	HBP	1018	2.44	917	2.4	55 45		- 408	442 517	560 650	697 806	855 987	1033 1190	10.5	187	13	F	520	350	POE 22	C/V	DWG03	SM05	NEU6187Z
NEK6210Z	12.1	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	1105	2.13	1024	2.16	55 45		- 469	454 523	554 637	699 711	891 1031	1128 1314	11.6	206	24	F	520	350	POE 22	C/V	DWG03	SM05	NEK6210Z
NEK6210Z	12.1	1/3	220-240V 50Hz 1 ~	CSIR	HST	HBP	1129	2.27	1046	2.29	55 45		- 456	480 578	619 726	773 787	942 1097	1127 1319	11	200	20	F	520	350	POE 22	C/V	DWG03	SM05	NEK6210Z
NEU6210Z	12.1	1/2	220-240V 50Hz 1 ~	CSIR	HST	HBP	1231	2.37	1102	2.33	55 45		- 489	530 615	663 770	825 955	1016 1170	1235 1414	10.6	200	18.5	F	520	350	POE 22	C/V	DWG03	SM05	NEU6210Z
NEU6210Z	12.1	1/2	220-240V 50Hz 1 ~	CSR	HST	HBP	1247	2.58	1109	2.48	55 45		- 483	530 618	672 780	839 969	1032 1186	1250 1431	10.6	200	18.5	F	520	350	POE 22	C/V	DWG03	SM06	NEU6210Z
NEU6210Z	12.1	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	1222	2.38	1136	2.33	55 45		- -	- -	- -	- -	- -	- -	11	200	21	F	520	350	POE 22	C/V	DWG03	SM05	NEU6210Z
NEU6210Z	12.1	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	HBP	1234	2.57	1148	2.52	55 45		- -	- -	- -	- -	- -	- -	11	200	21	F	520	350	POE 22	C/V	DWG03	SM06	NEU6210Z
NEK6212Z	14.3	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	HBP	1302	2.12	1206	2.14	55 45		- 521	565 662	712 830	882 898	1076 1249	1291 1498	11.6	206	21	F	520	350	POE 22	C/V	DWG03	SM06	NEK6212Z
NEK6212Z	14.3	1/2	220-240V 50Hz 1 ~	CSIR	HST	HBP	1314	2.09	1217	2.12	55 45		- 534	562 665	708 828	881 897	1081 1248	1308 1504	11.2	206	22.5	F	520	350	POE 22	C/V	DWG03	SM05	NEK6212Z
NEU6212Z	14.3	1/2	220-240V 50Hz 1 ~	CSIR	HST	HBP	1420	2.26	1271	2.22	55 45		- 556	595 706	767 892	965 1111	1188 1365	1437 1653	11.2	200	20	F	520	350	POE 22	C/V	DWG03	SM05	NEU6212Z
NEU6212Z	14.3	1/2	220-240V 50Hz 1 ~	CSR	HST	HBP	1456	2.52	1288	2.41	55 45		- -	- -	- -	- -	- -	- -	11.2	200	20	F	520	350	POE 22	C/V	DWG03	SM06	NEU6212Z
NEU6212Z	14.3	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	1444	2.36	1343	2.31	55 45		- -	- -	- -	- -	- -	- -	11.6	206	26	F	520	350	POE 22	C/V	DWG03	SM05	NEU6212Z
NEU6212Z																													

R134a • L/M/HBP - M/HBP - HBP • 50Hz - BR portfolio

MODEL	DISPL. cm ³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		COOLING CAPACITY ASHRAE HBP32							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		Evaporating Temperature °C W										CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
											-5	0	5	10	15											
EM20HHR	2,27	1/12	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	246	2,51	55		135	170	212	260	315	6,8	158	6,5	S/F	520	160	POE 22	C	DWG10	SM07	EM20HHR
EMIS30HHR	3,00	1/10	220V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	363	2,60	55		217	271	332	401	478	6,8	158	9	S/F	520	160	POE 22	C	DWG10	SM07	EMIS30HHR
EM45HHR	3,77	1/8	220-240V 50Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	440	2,63	55		256	321	397	486	587	7,7	171	9	S/F	520	160	POE 22	C	DWG10	SM07	EM45HHR
EM55HHR	4,60	1/6	220-240V 50/60Hz 1 ~	RSIR	LST	HBP	533	2,69	55		327	401	487	585	696	7,6	171	10	F	520	160	POE 22	C	DWG10	SM07	EM55HHR
EM65HHR	5,54	1/6+	220V 50/60Hz 1 ~	RSIR/CSIR	LST	M/HBP	645	2,45	55		389	486	594	713	844	7,2	171	14,3	F	520	160	POE 22	C	DWG10	SM07	EM65HHR
FF7,5HBK	6,92	1/5+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	810	2,76	55		431	537	659	801	962	10,7	195	16,7	S	-	280	POE 22	C	DWG09	SM08	FF7,5HBK
FF8,5HBK	7,95	1/4	220-240V 50Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	844	2,49	55		506	632	776	940	1124	10,8	195	18,2	S/F	520	280	POE 22	C	DWG09	SM08	FF8,5HBK
FFI12HBK	11,14	1/3+	220-240V 50Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	1316	2,61	55		790	968	1167	1390	1635	11,5	201	20	F	520	280	POE 22	C	DWG09	SM08	FFI12HBK

R134a • LBP • 60Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23.3 °C / 54.4 °C		RATED POINT - ARI540 -23.3 °C / 48.9 °C		CONDENSING TEMPERATURE °C		COOLING CAPACITY ARI540						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			EVAPORATING TEMPERATURE °C W											CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
													-30	-25	-20	-15	-10	-5											
NEK2116Z	7.4	1/5	115V 60Hz 1 ~	CSIR	HST	LBP	216	1.17	171	0.92	55		86	127	180	247	328	424	10	188	22	S	-	350	POE 22	C/V	DWG04	SM04	NEK2116Z
											45		122	169	229	300	385	478											
NE2121Z	9.3	1/4	115V 60Hz 1 ~	CSIR	HST	LBP	278	1.09	204	0.81	55		109	147	195	252	319	395	11	200	29	F	520	350	POE 22	C/V	DWG04	SM04	NE2121Z
											45		132	176	230	295	371	457											
NE2130Z	12.1	1/3	100V 50/60Hz 1 ~	CSIR	HST	LBP	367	1.19	269	1.16	55		166	227	300	383	479	586	11	200	39	F	520	350	POE 22	C/V	DWG04	SM04	NE2130Z
											45		205	268	348	443	553	679											
NE2130Z	12.1	1/3	115V 60Hz 1 ~	CSIR	HST	LBP	367	1.19	269	0.88	55		166	227	300	383	479	586	11	200	38	F	520	350	POE 22	C/V	DWG04	SM04	NE2130Z
											45		205	268	348	443	553	679											
NE2134Z	14.3	1/3	115V 60Hz 1 ~	CSIR	HST	LBP	425	1.23	312	0.91	55		191	257	334	424	533	660	11	200	33	F	520	350	POE 22	C/V	DWG04	SM04	NE2134Z
											45		228	303	392	495	618	764											
NEK2140Z	16.8	1/2	115V 60Hz 1 ~	CSIR	HST	LBP	500	1.19	390	0.94	55		236	314	417	546	698	876	11	206	40	F	520	350	POE 22	C/V	DWG04	SM04	NEK2140Z
											45		279	378	503	653	828	1030											
NEU2140Z	16.8	1/2	115-127V 60Hz 1 ~	CSIR	HST	LBP	512	1.28	405	0.98	55		-	-	-	-	-	-	11.1	206	40	F	520	350	POE 22	C/V	DWG04	SM04	NEU2140Z
											45		-	-	-	-	-	-											
NEU2140Z	16.8	1/2	115-127V 60Hz 1 ~	CSR	HST	LBP	516	1.37	407	1.04	55		-	-	-	-	-	-	11.1	206	40	F	520	350	POE 22	C/V	DWG04	SM06	NEU2140Z
											45		-	-	-	-	-	-											
NT2152ZV	26.2	1/2	115V 60Hz 1 ~	CSR	HST	LBP	681	1.31	610	1.07	55		200	425	646	871	1104	1351	18.2	250	70	F	520	450	POE 22	C/V	DWG17	SM26	NT2152ZV
											45		380	593	814	1048	1303	1582											

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R134a • LBP - L/MBP - L/M/HBP • 60Hz - BR portfolio

MODEL	DIS CM3	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		CONDENSING TEMPERATURE °C		COOLING CAPACITY ASHRAE LBP								WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W			EVAPORATING TEMPERATURE °C W													CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
											-35	-30	-25	-20	-15	-10	-5	0											
EM20HHR	2,27	1/12	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	59	0,89	55		16	34	53	74	98	127	161	202	6,8	158	6	S/F	520	160	POE 22	C	DGW10	SM07	EM20HHR
EMIS20HHR	2,27	1/12	220V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	59	0,81	55		19	33	52	75	103	137	178	226	6,8	158	9,1	S/F	520	160	POE 22	C	DGW10	SM07	EMIS20HHR
EMIS20HHR	2,27	1/12	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	59	0,88	55		16	30	48	70	97	129	168	215	6,8	158	11,6	S/F	520	160	POE 22	C	DGW10	SM07	EMIS20HHR
EMIE30HER	2,83	1/10	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	88	1,26	55		44	150	65	90	120	155	196	-	7,2	158	7	S	-	180	POE 10	C	DGW10	SM07	EMIE30HER
EMIS30HHR	3,00	1/10	220V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	100	1,14	55		35	59	85	117	154	199	251	314	6,8	158	8,8	S/F	520	160	POE 22	C	DGW10	SM07	EMIS30HHR
EMIS30HHR	3,00	1/10	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	100	1,10	55		35	57	84	115	153	198	251	313	6,8	158	16	S/F	520	160	POE 22	C	DGW10	SM07	EMIS30HHR
EMIE40HJP	3,40	1/8	220V 50/60Hz 1 ~	RSIR	LST	LBP	115	1,28	55		54	79	109	145	187	237	-	-	6,6	158	3,7	S	-	180	POE 10	C	DGW10	SM07	EMIE40HJP
EMI45HER	3,77	1/8	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	123	1,32	55		47	75	110	151	197	249	-	-	7,7	167	9,3	S	-	160	POE 22	C	DGW10	SM07	EMI45HER
EM45HHR	3,77	1/8	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	123	1,15	55		48	80	114	153	197	249	310	381	7,2	166	17	S/F	520	160	POE 22	C	DGW10	SM07	EM45HHR
EMIE65HER	5,19	1/6	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	185	1,33	55		124	124	168	220	282	356	-	-	8,3	166	11,5	S/F	520	180	POE 10	C	DGW10	SM07	EMIE65HER
EGAS70HLR	5,56	1/5+	220-240V 50/60Hz 1 ~	RSIR	LST	LBP	203	1,57	55		83	125	178	244	324	420	-	-	10	195	13,4	S	-	230	POE 10	C	DWG09	SM09	EGAS70HLR
EMI70HER	5,89	1/5	220V 60Hz 1 ~	RSIR/CSIR	LST	LBP	207	1,34	55		100	143	190	244	310	391	-	-	7,7	166	12,5	S	-	160	POE 22	C	DGW10	SM07	EMI70HER
EMYE70HEP	5,96	1/5	220-240V 50/60Hz 1 ~	RSIR	LST	LBP	201	1,53	55		100	141	184	234	295	373	-	-	7,8	166	6,5	S	-	180	POE 10	C	DGW10	SM07	EMYE70HEP
EGAS80HLR	6,36	1/4+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	240	1,61	55		90	143	207	283	373	476	-	-	10	195	13,5	S/F	520	230	POE 10	C	DWG09	SM09	EGAS80HLR
FFUS70HAK	6,36	1/4	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	222	1,51	55		91	140	198	267	350	449	566	705	10,2	201	12,1	S/F	520	230	POE 10	C	DWG09	SM08	FFUS70HAK
FFUS70HAK	6,36	1/4	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/MBP	229	1,52	55		99	146	205	277	363	466	585	721	10,9	201	24,7	S/F	520	280	POE 10	C	DWG09	SM08	FFUS70HAK
FFUS80HAK	6,76	1/4+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	236	1,47	55		108	155	213	284	369	470	589	727	10	201	12,1	S/F	520	230	POE 10	C	DWG09	SM08	FFUS80HAK
FFUS80HAK	6,76	1/4+	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/MBP	236	1,44	55		111	157	214	285	371	474	596	740	10	201	32	S/F	520	230	POE 10	C	DWG09	SM08	FFUS80HAK
FF7,5HBK	6,92	1/5+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	206	1,15	55		80	122	174	236	310	397	499	618	10,7	195	15,8	S	-	280	POE 22	C	DWG09	SM08	FF7,5HBK
EGAS90HLR	7,15	1/3-	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	271	1,59	55		-	-	-	-	-	-	-	-	10,5	195	13,5	S	-	230	POE 10	C	DWG09	SM09	EGAS90HLR
EGAS100HLR	7,95	1/3	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	LBP	308	1,60	55		132	201	278	367	471	595	-	-	11	201	16	S	-	230	POE 10	C	DWG09	SM09	EGAS100HLR
FFUS100HAK	7,95	1/3	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	295	1,52	55		142	195	268	361	470	596	737	892	10,6	201	16,6	S/F	520	350	POE 10	C	DWG09	SM08	FFUS100HAK
FFUS100HAK	7,95	1/3	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/MBP	297	1,47	55		139	195	268	357	465	592	740	908	10,5	201	30	S/F	520	350	POE 10	C	DWG09	SM08	FFUS100HAK
FF8,5HBK	7,95	1/4	220V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	217	1,11	55		103	145	197	261	341	437	552	687	10,9	195	18,5	S/F	520	280	POE 22	C	DWG09	SM08	FF8,5HBK
FFI10HAK	9,04	1/3	220-230V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	302	1,42	55		115	188	270	364	473	601	751	-	10,9	201	17,5	S/F	520	280	POE 22	C	DWG09	SM08	FFI10HAK
FFI10HAK	9,04	1/3	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/MBP	302	1,42	55		115	189	271	364	473	601	751	-	10,9	201	32,5	S/F	520	280	POE 22	C	DWG09	SM08	FFI10HAK
FFU130HAX	10,61	1/3+	115-127V 60Hz 1 ~	CSIR	LST/HST	L/MBP	366	1,41	55		153	230	328	450	596	767	965	-	10,8	201	40,3	F	520	280	POE 10	C/V	DWG09	SM08	FFU130HAX
FFI12HBX	11,14	1/3+	220V 60Hz 1 ~	CSIR	HST	L/M/HBP	349	1,18	55		156	223	311	421	556	716	903	1119	11,5	201	26,5	F	520	280	POE 22	C/V	DWG09	SM08	FFI12HBX
FFU160HAX	12,92	1/2	220V 60Hz 1 ~	CSIR	LST/HST	L/MBP	449	1,45	55		219	319	434	569	726	910	1124	1374	10,9	201	19	F	520	280	POE 22	C/V	DWG09	SM08	FFU160HAX

R134a • HBP • 60Hz - EU portfolio

											COOLING CAPACITY ARI 540																											
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - ARI 540 7,2 °C / 54,4 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL									
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-15	-10	-5	0	5	10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE										
NEK6132Z	4,5	1/6	115V 60Hz 1 ~	CSIR	HST	HBP	516	2,13	431	1,77	55		-	192	248	315	393	482	10	187	26	S	-	350	POE 22	C/V	DWG04	SM04	NEK6132Z									
											45		177	231	297	376	466	569																				
NEK6144Z	5,4	1/6	115V 60Hz 1 ~	CSIR	HST	HBP	640	2,18	532	1,8	55		-	244	313	394	488	549	10,1	187	26	F	520	350	POE 22	C/V	DWG04	SM04	NEK6144Z									
											45		226	291	368	460	565	683																				
NEK6160Z	7,3	1/4	115V 60Hz 1 ~	CSIR	HST	HBP	845	2,35	758	2,11	55		-	354	450	563	694	846	10,4	187	28,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK6160Z									
											45		327	418	529	657	803	967																				
NEK6160Z	7,3	1/4	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	845	2,41	758	2,17	55		-	351	450	563	693	839	10,4	187	13,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK6160Z									
											45		330	415	522	650	799	966																				
NEU6160Z	7,3	1/4	115-127V 60Hz 1 ~	CSIR	HST	HBP	910	2,58	855	2,42	55		-	390	497	625	773	941	10	187	25	F	520	350	POE 22	C/V	DWG04	SM04	NEU6160Z									
											45		360	460	582	727	894	1083																				
NEU6160Z	7,3	1/4	115-127V 60Hz 1 ~	CSR	HST	HBP	920	2,79	865	2,6	55		-	395	503	633	783	954	10	187	25	F	520	350	POE 22	C/V	DWG04	SM06	NEU6160Z									
											45		357	464	591	737	903	1088																				
NEK6170Z	8,4	1/4	115V 60Hz 1 ~	CSIR	HST	HBP	978	2,34	878	2,1	55		-	423	527	655	804	974	10,4	187	28,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK6170Z									
											45		396	493	616	762	932	1126																				
NEK6170Z	8,4	1/4	100V 50/60Hz 1 ~	CSIR	HST	HBP	959	2,35	738	1,95	55		-	382	461	585	759	988	10,4	187	31	F	520	340	POE 22	C/V	DWG04	SM04	NEK6170Z									
											45		404	448	535	673	866	1119																				
NEK6170Z	8,4	1/4	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	981	2,38	881	2,14	55		-	428	532	657	804	970	10,8	200	18	F	520	350	POE 22	C/V	DWG04	SM04	NEK6170Z									
											45		393	495	620	767	937	1130																				
NEK6187Z	10,0	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	1115	2,3	1000	2,06	55		-	477	603	750	918	1109	11,6	206	18	F	520	350	POE 22	C/V	DWG04	SM04	NEK6187Z									
											45		426	549	693	857	1044	1253																				
NEK6187Z	10,0	1/3	115V 60Hz 1 ~	CSIR	HST	HBP	1122	2,31	1007	2,07	55		-	476	597	746	921	1124	11	200	37	F	520	350	POE 22	C/V	DWG04	SM04	NEK6187Z									
											45		442	555	697	868	1068	1295																				
NEU6187Z	10,0	1/3	115-127V 60Hz 1 ~	CSIR	HST	HBP	1211	2,42	1154	2,23	55		-	501	680	908	1129	1278	10,7	200	39	F	520	350	POE 22	C/V	DWG04	SM04	NEU6187Z									
											45		498	586	783	1031	1274	1455																				
NEU6187Z	10,0	1/3	115-127V 60Hz 1 ~	CSR	HST	HBP	1225	2,6	1163	2,35	55		-	500	682	916	1145	1312	10,7	200	39	F	520	350	POE 22	C/V	DWG04	SM06	NEU6187Z									
											45		503	592	792	1044	1291	1475																				
NEU6187Z	10,0	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	-	-	1021	2,04	55		-	469	594	745	920	1120	10,5	200	16	F	520	350	POE 22	C/V	DWG04	SM04	NEU6187Z									
											45		438	560	708	882	1082	1308																				
NEU6187Z	10,0	1/3	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	HBP	1186	2,31	-	-	55		-	-	-	-	-	-	10,5	187	13	F	520	350	POE 22	C/V	DWG03	SM04	NEU6187Z									
											45		-	-	-	-	-	-																				
NEK6210Z																																						

R134a • HBP • 60Hz - EU portfolio

...FOLLOW

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - ARI 540 7,2 °C / 54,4 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL									
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-15	-10	-5	0	5	10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE										
NEU6212Z	14,3	1/2	115-127V 60Hz 1 ~	CSR	HST	HBP	1691	2,44	1591	2,29	55		-	754	946	1177	1444	1749	11,5	206	40	F	520	350	POE 22	C/V	DWG04	SM06	NEU6212Z									
											45		668	857	1084	1349	1650	1989																				
NEU6212Z	14,3	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	HBP	1660	2,18	1494	1,96	55		-	-	-	-	-	-	11,6	206	26	F	520	350	POE 22	C/V	DWG04	SM04	NEU6212Z									
											45		-	-	-	-	-	-																				
NEU6212Z	14,3	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	HBP	1698	2,45	1528	2,21	55		-	-	-	-	-	-	11,6	206	26	F	520	350	POE 22	C/V	DWG04	SM06	NEU6212Z									
											45		-	-	-	-	-	-																				
NEK6214Z	16,8	1/2	208-230V 60Hz 1 ~	CSIR	HST	HBP	1697	1,97	1523	1,77	55		-	731	921	1143	1396	1677	11,4	206	30	F	520	350	POE 22	C/V	DWG04	SM04	NEK6214Z									
											45		671	851	1068	1321	1610	1933																				
NEK6214Z	16,8	1/2	208-230V 60Hz 1 ~	CSR	HST	HBP	1712	2,11	1537	1,89	55		-	740	929	1153	1410	1698	11,4	206	30	F	520	350	POE 22	C/V	DWG04	SM06	NEK6214Z									
											45		686	865	1081	1331	1617	1937																				
NEK6214Z	16,8	1/2	115V 60Hz 1 ~	CSR	HST	HBP	1746	2,05	1568	1,84	55		-	748	948	1180	1443	1734	11,6	206	48	F	520	350	POE 22	C/V	DWG04	SM06	NEK6214Z									
											45		689	875	1098	1357	1652	1980																				
NEU6214Z	16,8	1/2	115-127V 60Hz 1 ~	CSIR	HST	HBP	1884	2,09	1776	1,97	55		-	846	1067	1325	1618	1947	11,6	206	50	F	520	350	POE 22	C/V	DWG04	SM04	NEU6214Z									
											45		763	973	1222	1512	1841	2210																				
NEU6214Z	16,8	1/2	115-127V 60Hz 1 ~	CSR	HST	HBP	1913	2,26	1799	2,13	55		-	847	1074	1338	1640	1978	11,6	206	50	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214Z									
											45		765	978	1230	1522	1854	2225																				
NEU6214Z	16,8	1/2	208-230V 60Hz 1 ~	CSIR	HST	HBP	1876	2,03	1803	1,95	55		-	842	1066	1328	1628	1968	11,5	206	30	F	520	350	POE 22	C/V	DWG04	SM04	NEU6214Z									
											45		762	979	1233	1525	1854	2221																				
NEU6214Z	16,8	1/2	208-230V 60Hz 1 ~	CSR	HST	HBP	1919	2,28	1831	2,14	55		-	849	1078	1345	1650	1994	11,5	206	30	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214Z									
											45		768	983	1239	1536	1874	2253																				
NEU6214Z	16,8	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	HBP	1897	2,25	1802	2,12	55		-	-	-	-	-	-	11,6	206	25	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214Z									
											45		-	-	-	-	-	-																				
NT6215Z	17,4	1/2	208-230V 60Hz 1 ~	CSIR	HST	HBP	1876	2,25	1634	1,92	55		-	785	989	1228	1501	1808	17	207	20,8	F	520	450	POE 22	C/V	DWG15	SM20	NT6215Z									
											45		718	919	1157	1433	1747	2099																				
NT6215Z	17,4	1/2	115V 60Hz 1 ~	CSIR	HST	HBP	1942	2,4	1709	2,04	55		-	790	1005	1258	1550	1881	16,5	207	44	F	520	450	POE 22	C/V	DWG15	SM20	NT6215Z									
											45		734	940	1192	1489	1833	2222																				
NT6215Z	17,4	1/2	115V 60Hz 1 ~	CSR	HST	HBP	2016	2,61	1754	2,28	55		-	801	1021	1283	1588	1934	16,5	207	44	F	520	450	POE 22	C/V	DWG15	SM23	NT6215Z									
											45		746	961	1220	1523	1870	2262																				
NT6215Z	17,4	1/2	115-127V 60Hz 1 ~	CSIR	HST	HBP	1942	2,4	1925	2,37	55		-	893	1146	1439	1772	2144	16,5	207	44	F	520	450	POE 22	C/V	DWG15	SM20	NT6215Z									
											45		818	1059	1334	1642	1985	2361																				
NT6217Z	20,4	3/4	115V 60Hz 1 ~	CSR	HST	HBP	2189																															

R134a • L/M/HBP - M/HBP - HBP • 60Hz - BR portfolio

MODEL	DISPL. cm ³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		COOLING CAPACITY ASHRAE HBP32							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m ³ /h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		Evaporating Temperature °C W										CHARGE cm ³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
											-5	0	5	10	15											
EM20HHR	2,27	1/12	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	292	2,48	55		161	202	252	312	382	6,8	158	6,5	S/F	520	160	POE 22	C	DWG10	SM07	EM20HHR
EMIS20HHR	2,27	1/12	220V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	308	2,36	55		178	226	281	345	417	6,8	158	9,1	S/F	520	160	POE 22	C	DWG10	SM07	EMIS20HHR
EMIS20HHR	2,27	1/12	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	308	2,49	55		168	215	271	337	414	6,8	158	11,6	S/F	520	160	POE 22	C	DWG10	SM07	EMIS20HHR
EMIS30HHR	3,00	1/10	220V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	434	2,68	55		251	314	387	473	572	6,8	158	9	S/F	520	160	POE 22	C	DWG10	SM07	EMIS30HHR
EMIS30HHR	3,00	1/10	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	434	2,67	55		251	313	385	468	562	6,8	158	16	S/F	520	160	POE 22	C	DWG10	SM07	EMIS30HHR
EM45HHR	3,77	1/8	115-127V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	520	2,53	55		310	381	463	559	669	7,2	166	17	S/F	520	160	POE 22	C	DWG10	SM07	EM45HHR
EM55HHR	4,60	1/6	220-240V 50/60Hz 1 ~	RSIR	LST	HBP	630	2,60	55		378	472	581	703	840	7,6	171	9,5	F	520	160	POE 22	C	DWG10	SM07	EM55HHR
EM55HHR	4,60	1/6	115V 60Hz 1 ~	RSIR	LST	HBP	630	2,52	55		366	456	562	684	821	7,6	171	24,5	F	520	160	POE 22	C	DWG10	SM07	EM55HHR
EM65HHR	5,54	1/6+	220V 50/60Hz 1 ~	RSIR/CSIR	LST	M/HBP	766	2,55	55		474	582	707	847	1003	7,2	171	13,9	F	520	160	POE 22	C	DWG10	SM07	EM65HHR
FF7,5HBK	6,92	1/5+	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	850	2,29	55		499	618	755	912	1089	10,7	195	16,7	S	-	280	POE 22	C	DWG09	SM08	FF7,5HBK
FF8,5HBK	7,95	1/4	220V 60Hz 1 ~	RSIR/CSIR	LST	L/M/HBP	920	2,24	55		552	688	847	1031	1243	10,9	195	18,5	S/F	520	280	POE 22	C	DWG09	SM08	FF8,5HBK
FF12HBX	11,14	1/3+	220V 60Hz 1 ~	CSIR	HST	L/M/HBP	1553	2,28	55		903	1119	1364	1641	1950	11,5	201	26,5	F	520	280	POE 22	C/V	DWG09	SM08	FF12HBX

R404A/R507/R452A • LBP • 50Hz - EU portfolio

											COOLING CAPACITY EN12900																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - EN12900 -35 °C / 40 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL	
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-40	-35	-30	-25	-20	-15						-10	CHARGE cm³		TYPE	EXTERNAL VIEW REFERENCE		WIRING DIAGRAM REFERENCE
NEK2117GK	4,5	1/4	220-240V 50Hz 1~	CSIR	HST	LBP	235	1,29	125	0,94	55		-	-	117	154	197	247	303	10,4	188	9,6	S	-	350	POE 22	C/V	DWG02	SM05	NEK2117GK
											45		80	111	149	194	246	306	374											
EMT2117GK	4,5	1/4	220-240V 50Hz 1~	CSIR	HST	LBP	244	1,35	141	1,09	55		-	-	127	166	211	264	326	7,8	166	7,7	S	-	180	POE 22	C/V	DWG01	SM05	EMT2117GK
											45		91	125	164	210	265	330	408											
EMT2121GK	5,2	1/3	220-240V 50Hz 1~	CSIR	HST	LBP	300	1,4	174	1,12	55		-	-	168	212	264	327	400	7,8	166	8,5	F	270	180	POE 22	C/V	DWG01	SM05	EMT2121GK
											45		120	159	204	258	322	398	487											
NEK2121GK	5,4	1/3	220-240V 50Hz 1~	CSIR	HST	LBP	282	1,29	156	0,99	55		-	-	143	188	241	303	375	10,4	188	9,6	S	-	350	POE 22	C/V	DWG02	SM05	NEK2121GK
											45		104	139	184	238	302	377	463											
EMT2125GK	6,0	1/3	220-240V 50Hz 1~	CSIR	HST	LBP	351	1,4	204	1,15	55		-	-	190	242	303	375	458	7,8	166	9,8	F	520	180	POE 22	C/V	DWG01	SM05	EMT2125GK
											45		140	185	238	301	373	462	562											
NEK2125GK	6,2	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	LBP	313	1,23	-	-	55		-	-	-	-	-	-	-	10,4	188	13	F	520	350	POE 22	C/V	DWG03	SM05	NEK2125GK
											45		-	-	-	-	-	-	-											
NEK2125GK	6,2	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	LBP	317	1,33	-	-	55		-	-	-	-	-	-	-	10,4	188	13	F	520	350	POE 22	C/V	DWG03	SM06	NEK2125GK
											45		-	-	-	-	-	-	-											
NEK2125GK	6,2	1/3	220-240V 50Hz 1~	CSIR	HST	LBP	341	1,22	178	0,89	55		-	-	168	221	283	354	433	10,4	188	12,4	F	520	350	POE 22	C/V	DWG03	SM05	NEK2125GK
											45		120	160	214	278	353	439	533											
NEK2125GK	6,2	1/3	100V 50/60Hz 1 ~	CSIR	HST	LBP	335	1,13	-	-	55		-	-	-	-	-	-	-	11,2	206	32	F	520	350	POE 22	C/V	DWG03	SM05	NEK2125GK
											45		-	-	-	-	-	-	-											
NEK2125GK	6,2	1/3	100V 50/60Hz 1 ~	CSR	HST	LBP	338	1,24	-	-	55		-	-	-	-	-	-	-	11,2	206	32	F	520	350	POE 22	C/V	DWG03	SM06	NEK2125GK
											45		-	-	-	-	-	-	-											
EMT2130GK	6,8	1/3	220-240V 50Hz 1~	CSIR	HST	LBP	390	1,34	222	1,08	55		-	-	205	263	330	407	497	8	171	12,1	F	520	180	POE 22	C/V	DWG01	SM05	EMT2130GK
											45		150	200	257	326	406	500	605											
NEK2130GK	7,4	1/3	220-240V 50Hz 1~	CSIR	HST	LBP	399	1,32	210	0,99	55		-	-	202	267	341	425	521	10,9	200		F	520	350	POE 22	C/V	DWG03	SM05	NEK2130GK
											45		131	188	255	332	421	523	639											
NEK2134GK	8,8	1/2	220-240V 50Hz 1~	CSIR	HST	LBP	464	1,3	253	1	55		-	-	239	313	401	501	611	11	200	16,1	F	520	350	POE 22	C/V	DWG03	SM05	NEK2134GK
											45		170	227	302	394	501	621	753											
NEK2134GK	8,8	1/2	100V 50/60Hz 1 ~	CSIR	HST	LBP	448	1,19	235	0,86	55		-	-	233	305	390	486	595	11,6	206	34	F	520	350	POE 22	C/V	DWG04	SM04	NEK2134GK
											45		165	223	295	330	486	603	735											
NEK2134GK	8,8	1/2	100V 50/60Hz 1 ~	CSR	HST	LBP	452	1,28	237	0,93	55		-	-	236	309	394	491	600	11,6	206	34	F	520	350	POE 22	C/V	DWG04	SM06	NEK2134GK
											45		169	225	297	332	487	606	741											
NEU2140GK	8,8	1/2	220-240V 50Hz 1~	CSIR	HST	LBP	486	1,36	275	1,13	55		-	-	260	339	432	536	654	10,6	200	13,5	F	520	350	POE 22	C/V	DWG03	SM05	NEU2140GK
											45		183	246	326	421	531	658	801											
NEU2140GK	8,8	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	LBP	480	1,34	270	1,11	55		-	-	-	-	-	-	-	11,2	200	18	F	520	350	POE 22	C/V	DWG03	SM05	NEU2140GK
											45		-	-	-	-	-	-	-											
NEK2150GK	12,1	3/4	220-240V 50Hz 1~	CSIR	HST	LBP	605	1,24	304	0,91	55		-	-	326	419	529	657	807	11,6	206	19,5	F	520	350	POE 22	C/V	DWG03	SM05	NEK2150GK
											45		235	313	408	522	657	814	995											
NEK2150GK	12,1	1/2	100V 50/60Hz 1 ~	CSR	HST	LBP	604	1,28	304	0,8	55		-	-	299	395	509	640	788	11,6	206	44	F	520	350	POE 22	C/V	DWG04	SM06	NEK2150GK
											45		212	286	381	429	634	791	969											
NEU2155GK	12,1	3/4	220-240V 50Hz 1~	CSIR	HST	LBP	658	1,32	368	1,08	55		-	-	413	477	546	713	870	11,1	206	18	F	520	350	POE 22	C/V	DWG03	SM05	NEU2155GK
											45		246	328	432	557	705	875	1067											
NEK2168GK	14,3	3/4	220-240V 50Hz 1~	CSIR	HST	LBP	688	1,13	360	0,95	55		-	-	358	468	596	743	909	11,6	206	24	F	520	350	POE 22	C/V	DWG03	SM05	NEK2168GK
											45		259	345	454	587	742	921	1123											
NEK2168GK	14,3	3/4	220-240V 50Hz 1~	CSR	HST	LBP	707	1,28	380	0,97	55		-	-	371	484	618	771	944	11,6	206	24	F	520	350	POE 22	C/V	DWG03	SM06	NEK2168GK
											45		263	353	466	605	767	955	1166											
NEU2168GK	14,3	3/4	220-240V 50Hz 1~	CSIR	HST	LBP	744	1,27	416	1,08	55		-	-	298	522	661	814	982	11,6	206	22	F	520	350	POE 22	C/V	DWG03	SM05	NEU2168GK
											45		271	372	496	642	810	1000	1213											
NEU2168GJ	14,3	3/4	220-240V 50Hz 1~	CSR	HST	LBP	776	1,44	437	1,21	55		-	-	411	537	684	852	1042	11,6	206	22	F	520	350	POE 22	C/V	DWG03	SM06	NEU2168GJ
											45		293	391	514	664	838	1038	1264											
NT2168GK	14,5	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	LBP	642	1,28	354	1,03	55		-	-	319	422	542	685	859	17	220	25	F	520	450	POE 22	C/V	DWG16	SM19	NT2168GK
											45		206	310	423	549	698	875	1089											
NT2168GK	14,5	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSR	HST	LBP	642	1,28	354	1,03	55		-	-	319	422	542	685	859	17	220	25	F	520	450	POE 22	C/V	DWG16	SM23	NT2168GK
											45		206	310	423	549	698	875	1089											

CONTINUE...

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R404A/R507/R452A • LBP • 50Hz - EU portfolio

...FOLLOW

											COOLING CAPACITY EN12900																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - EN12900 -35 °C / 40 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-40	-35	-30	-25	-20	-15	-10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
NEK2172GK	16,8	3/4	220V 50Hz 1 ~	CSR	HST	LBP	824	1,27	461	1,04	55		-	-	439	570	722	895	1090	11,8	206	26	F	520	350	POE 22	C/V	DWG03	SM06	NEK2172GK
											45		312	420	553	711	894	1103	1336											
NEU2178GK	16,8	1	220-240V 50Hz 1~	CSR	HST	LBP	914	1,42	501	1,14	55				468	605	765	947	1152	11,6	206	21	F	520	350	POE 22	C/V	DWG03	SM06	NEU2178GK
											45		334	447	586	753	947	1168	1416											
NT2178GK	17,4	3/4	220-240V 50Hz 1~	CSIR	HST	LBP	782	1,3	416	0,98	55		-	-	378	502	647	812	997	17	220	25	F	520	450	POE 22	C/V	DWG16	SM19	NT2178GK
											45		273	373	502	659	844	1057	1297											
NT2178GK	17,4	3/4	220-240V 50Hz 1~	CSR	HST	LBP	802	1,42	420	0,91	55		-	-	385	513	663	835	1030	17	220	25	F	520	450	POE 22	C/V	DWG16	SM23	NT2178GK
											45		257	375	513	671	854	1062	1300											
NT2178GK	17,4	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	LBP	800	1,15	419	0,89	55		-	-	399	516	651	806	983	17	220	26	F	520	450	POE 22	C/V	DWG16	SM19	NT2178GK
											45		283	396	526	676	853	1056	1290											
NT2178GK	17,4	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSR	HST	LBP	854	1,47	447	1,14	55		-	-	399	516	651	806	983	17	220	26	F	520	450	POE 22	C/V	DWG16	SM23	NT2178GK
											45		283	396	526	676	853	1056	1290											
NT2178GK	17,4	3/4	100V 50/60Hz 1 ~	CSR	HST	LBP	812	1,3	425	0,98	55		-	-	392	520	674	854	1063	16,7	220	25	F	520	450	POE 22	C/V	DWG17	SM23	NT2178GK
											45		292	394	525	685	878	1105	1372											
NT2180GK	20,4	1	220-240V 50Hz 1~	CSIR	HST	LBP	935	1,25	490	0,95	55		-	-	461	601	767	958	1176	17,4	234	35	F	520	450	POE 22	C/V	DWG16	SM19	NT2180GK
											45		323	453	604	778	977	1203	1458											
NT2180GK	20,4	1	220-240V 50Hz 1~	CSR	HST	LBP	935	1,36	530	1,05	55		-	-	483	640	814	1007	1224	17,4	234	35	F	520	450	POE 22	C/V	DWG16	SM23	NT2180GK
											45		332	468	625	814	1034	1286	1573											
NT2192GK	22,4	1	220-240V 50Hz 1~	CSIR	HST	LBP	1053	1,3	551	1,03	55		-	-	518	675	860	1074	1321	17,5	234	35	F	520	450	POE 22	C/V	DWG16	SM19	NT2192GK
											45		373	506	669	865	1100	1375,03	1693											
NT2192GK	22,4	1	220-240V 50Hz 1~	CSR	HST	LBP	1089	1,47	568	1,06	55		-	-	522	681	867	1083	1330	17,5	234	35	F	520	450	POE 22	C/V	DWG16	SM23	NT2192GK
											45		367	505	672	869	1100	1366	1669											
NT2192GS	22,4	1	200V 50/60Hz 3 ~	3PHASE	HST	LBP	1049	1,35	549	1,07	55		-	-	516	675	860	1072	1315	18,3	250	28	F	520	650	POE 22	C/V	DWG17	SM27	NT2192GS
											45		364	504	673	872	1106	1378	1690											
NJ2192GJ	26,1	1 1/4	220-240V 50Hz 1~	CSR	HST	LBP	1188	1,25	585	0,97	55		-	-	530	722	938	1179	1444	21	277	26	F	800	750	POE 22	C/V	DWG14	SM16	NJ2192GJ
											45		348	509	705	936	1203	1505	1842											
NJ2192GS	26,1	1 1/4	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	LBP	1128	1,23	591	0,85	55		-	-	529	718	939	1198	1497	19,7	265	15	F	800	750	POE 22	C/V	DWG14	SM18	NJ2192GS
											45		320	516	730	968	1235	1533	1868											
NT2210GK	26,2	1 1/3	220-240V 50Hz 1~	CSR	HST	LBP	1306	1,4	685	1,06	55		-	-	640	839	1069	1331	1624	17,9	234	33	F	520	450	POE 22	C/V	DWG17	SM26	NT2210GK
											45		431	597	804	1052	1340	1670	2041											
NT2212GK	27,8	1 1/2	220-240V 50Hz 1~	CSR	HST	LBP	1373	1,37	719	1,07	55		-	-	688	888	1127	1405	1728	18,3	250	33	F	520	650	POE 22	C/V	DWG17	SM26	NT2212GK
											45		503	671	876	1125	1421	1770	2174											
NT2212GS	27,8	1 1/4	200V 50/60Hz 3 ~	3PHASE	HST	LBP	1571	131	-	-	55		-	-	-	-	-	-	-	18	250	-	F	520	650	POE 22	C/V	DWG17	SM27	NT2212GS
											45		-	-	-	-	-	-	-											
NJ2212GJ	34,4	1 1/2	220-240V 50Hz 1~	CSR	HST	LBP	1592	1,31	809	1,06	55		-	-	727	978	1262	1578	1923	21,5	277	36	F	800	750	POE 22	C/V	DWG14	SM16	NJ2212GJ
											45		472	694	961	1276	1637	2040,98	2487											
NJ2212GS	34,4	1 1/2	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	LBP	1481	1,3	796	1	55		-	-	660	919	1220	1565	1953	20,4	277	13	F	800	750	POE 22	C/V	DWG14	SM18	NJ2212GS
											45		506	697	946	1256	1626	2055	2544											
NJX2219GS	38,0	2	400V 50Hz / 440V 60Hz 3 ~	3PHASE	HST	LBP	2164	1,47	1181	1,2	55		-	-	1052	1374	1749	2177	2658	21,8	277	23	F	800	750	POE 22	C/V	DWG14	SM18	NJX2219GS
											45		775	1025	1343	1731	2186	2710	3303											

R404A/R507 • MBP - M/HBP • 50Hz - EU portfolio

											COOLING CAPACITY EN12900																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - EN12900 -10 °C / 45 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-20	-15	-10	-5	0	5	10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
EMT6144GK	4,0	1/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	679	2,39	378	1,9	55 45		- 246	- 307	303 377	370 458	448 551	535 656	634 773	7,8	166	7,7	F	270	180	POE 22	C/V	DWG01	SM05	EMT6144GK
EMT6152GK	4,5	1/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	758	2,3	424	1,85	55 45		- 275	- 344	339 422	413 511	497 614	593 731	699 861	7,8	166	8,5	F	520	180	POE 22	C/V	DWG01	SM05	EMT6152GK
EMT6165GK	5,2	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	877	2,23	484	1,76	55 45		- 315	- 392	384 482	471 586	610 706	682 840	808 989	7,8	166	10,4	F	520	180	POE 22	C/V	DWG01	SM05	EMT6165GK
NEK6165GK	6,2	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	966	2,05	542	1,64	55 45		- 388	- 454	443 542	533 650	639 781	759 931	895 1103	10,4	187	12,4	F	520	350	POE 22	C/V	DWG03	SM05	NEK6165GK
NEU6181GK	6,2	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	MBP	1028	2,26	-	-	55 45		- -	- -	- -	- -	- -	- -	- -	10,7	200	18	F	520	350	POE 22	C/V	DWG03	SM05	NEU6181GK
NEK6181GK	7,3	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	1089	2,12	599	1,66	55 45		- 405	- 491	483 599	587 730	711 882	853 1057	1013 1252	10,4	187	12	F	520	350	POE 22	C/V	DWG03	SM05	NEK6181GK
NEU6210GK	7,3	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	1153	2,3	645	1,76	55 45		- 408	- 517	521 645	642 791	780 956	933 1139	1103 1341	10	200	16	F	520	350	POE 22	C/V	DWG03	SM05	NEU6210GK
NEU6210GK	7,3	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	MBP	1182	2,43	-	-	55 45		- -	- -	- -	- -	- -	- -	- -	11,1	200	21	F	520	350	POE 22	C/V	DWG03	SM05	NEU6210GK
NEU6210GK	7,3	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	MBP	1195	2,62	-	-	55 45		- -	- -	- -	- -	- -	- -	- -	11,1	200	21	F	520	350	POE 22	C/V	DWG03	SM06	NEU6210GK
NEK6210GK	8,8	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1304	2,07	724	1,68	55 45		- 500	- 598	571 724	698 877	849 1058	1021 1265	1216 1499	11	200	16,1	F	520	350	POE 22	C/V	DWG03	SM05	NEK6210GK
NEK6210GK	8,8	1/2	100V 50/60 HZ 1 ~	CSIR	HST	MBP	1340	1,98	733	1,46	55 45		- 468	- 589	586 733	723 900	879 1091	1054 1305	1247 1540	11	200	38	F	520	350	POE 22	C/V	DWG03	SM05	NEK6210GK
NEU6212GK	8,8	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1438	2,23	792	1,74	55 45		- 505	- 638	643 793	788 970	952 1169	1134 1390	1336 1632	10,6	200	19	F	520	350	POE 22	C/V	DWG03	SM05	NEU6212GK
NEU6214GK	10,0	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	MBP	1628	2,27	-	-	55 45		- -	- -	- -	- -	- -	- -	- -	11,6	206	26	F	520	350	POE 22	C/V	DWG03	SM05	NEU6214GK
NEU6214GK	10,0	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	MBP	1659	2,5	-	-	55 45		- -	- -	- -	- -	- -	- -	- -	11,6	206	26	F	520	350	POE 22	C/V	DWG03	SM06	NEU6214GK
NEK6213GK	12,1	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1780	1,9	972	1,46	55 45		- 666	- 804	788 972	958 1171	1150 1403	1366 1666	1603 1963	11,2	206	19,3	F	520	350	POE 22	C/V	DWG03	SM05	NEK6213GK
NEU6215GK	12,1	3/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	1862	1,92	1239	1,99	55 45		- 717	- 889	884 1087	1072 1313	1281 1564	1510 1843	1762 2148	11,5	206	22	F	520	350	POE 22	C/V	DWG03	SM05	NEU6215GK
NEU6215GK	12,1	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	1929	2,23	1267	2,2	55 45		- 728	- 903	904 1108	1098 1342	1318 1605	1566 1898	1840 2221	11,5	206	22	F	520	350	POE 22	C/V	DWG03	SM06	NEU6215GK
NT6217GK	12,6	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	MBP	1819	2,26	915	1,51	55 45		- 585	- 732	699 915	870 1132	1068 1384	1294 1672	1548 1994	17	220	25	F	520	450	POE 22	C/V	DWG16	SM19	NT6217GK
NT6217GK	12,6	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSR	HST	MBP	1890	2,35	891	1,73	55 45		- 535	- 691	692 891	878 1130	1095 1406	1339 1713	1381 2048	17	220	25	F	520	450	POE 22	C/V	DWG16	SM23	NT6217GK
NEK6217GK	14,3	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	2075	2,05	1166	1,69	55 45		- 777	- 954	955 1166	1157 1411	1386 1690	1638 2003	1916 2347	11,6	206	21,5	F	520	350	POE 22	C/V	DWG03	SM06	NEK6217GK
NEU6220GK	14,3	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	2270	2,17	1382	1,8	55 45		- -	- -	- -	- -	- -	- -	- -	11,5	206	25	F	520	350	POE 22	C/V	DWG03	SM06	NEU6220GK
NT6220GK	14,5	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	MBP	2119	2,21	1080	1,67	55 45		- 678	- 858	853 1080	1061 1342	1307 1645	1589 1985	1907 2362	17	220	31	F	520	450	POE 22	C/V	DWG16	SM19	NT6220GK
NT6220GK	14,5	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSR	HST	MBP	2206	2,37	1085	1,73	55 45		- 680	- 870	861 1096	1067 1358	1305 1657	1574 1993	1876 2365	17	220	31	F	520	450	POE 22	C/V	DWG16	SM23	NT6220GK
NT6222GK	17,4	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	MBP	2489	2,09	1280	1,62	55 45		- 835	- 1057	1025 1322	1275 1631	1557 1980	1869 2369	2210 2797	17	220	37	F	520	450	POE 22	C/V	DWG16	SM19	NT6222GK
NT6222GK	17,4	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSR	HST	MBP	2488	2,26	1307	1,7	55 45		- 810	- 1032	1040 1307	1294 1629	1583 1992	1903 2388	2247 2813	17	220	37	F	520	450	POE 22	C/V	DWG16	SM23	NT6222GK
NT6222GK	17,4	3/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	2482	2,02	1287	1,5	55 45		- 839	- 1034	995 1287	1233 1597	1520 1960	1850 2371	2222 2830	17,2	220	30	F	520	450	POE 22	C/V	DWG16	SM19	NT6222GK
NT6222GK	17,4	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	2688	2,41	1332	1,63	55 45		- 846	- 1071	1038 1332	1276 1635	1551 1981	1866 2372	2226 2811	17,2	220	30	F	520	450	POE 22	C/V	DWG16	SM23	NT6222GK
NT6224GK	20,4	1	220-240V 50Hz 1 ~	CSR	HST	MBP	3023	2,38	1573	1,69	55 45		- 996	- 1261	1244 1573	1540 1933	1879 2339	2258 2787	2678 3278	17,2	220	29	F	520	450	POE 22	C/V	DWG17	SM23	NT6224GK
NTU6232GKV	20,4	1	220-240V 50Hz 1 ~	CSR	HST	MBP	3299	2,83	1760	1,97	55 45		- 1148	- 1433	1405 1754	1704 2126	2046 2561	2445 3075	2914 3681	18,4	253	37,5	F	520	650	POE 22	C/V	DWG19	SM26	NTU6232GKV
NJ9226GK	21,7	1	230V 50Hz 1 ~	CSR	HST	M/HBP	3241	2,34	1648	1,7	55 45		- 982	- 1285	1255 1648	1581 2066	1944 2536	2340 3055	2766 3618	20,7	265	27,5	F	800	750	POE 22	C/V	DWG14	SM17	NJ9226GK
NJ9226GŠ	21,7	1	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	M/HBP	3248	2,5	1667	1,79	55 45		- 989	- 1301	1278 1667	1609 2086	1980 2560	2389 3087	2838 3668	19	265	10	F	800	750	POE 22	C/V	DWG14	SM18	NJ9226GŠ
NT6226GK	22,4	1	220-240V 50Hz 1 ~	CSR	HST	MBP	3355	2,44	1752	1,79	55 45		- 1137	- 1420	1412 1753	1724 2143	2091 2597	2518 3122	3014 3724	17,5	234	38	F	520	450	POE 22	C/V	DWG17	SM21	NT6226GK
NTU6234GKV	23,7	1 1/4	220-240V 50Hz 1 ~	CSR	HST	MBP	3835	2,8	2083	2,01	55 45		- 1389	- 1702	1655 2089	2022 2533	2425 3014	2847 3517	3269 4023	18,4	253	37,5	F	520	650	POE 22	C/V	DWG19	SM26	NTU6234GKV
NJ9232GK	26,1	1 1/2	220-240V 50Hz 1 ~	CSR	HST	M/HBP	4030	2,56	1911	1,63	55 45		- 1093	- 1470	1414 1911	1817 2413	2271 2973	3315 3588	4255	21,6	277	43	F	800	750	POE 22	C/V	DWG14	SM17	NJ9232GK
NJ9232GŠ	26,1	1 1/2	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	M/HBP	4030	2,5	1972	1,8	55 45		- 1166	- 1535	1513 1972	1911 2476	2357 3047	2853 3684	3396 4388	20,4	277	13	F	800	750	POE 22	C/V	DWG14	SM18	NJ9232GŠ
NTU6238GKV	26,2	1 1/2	220-240V 50Hz 1 ~	CSR	HST	MBP	4212	2,7	2288	1,99	55 45		- 1523	- 1854	1826 2282	2233 2794	2691 3376	3186 4016	3706 4700	18	253	37,5	F	520	650	POE 22	C/V	DWG19	SM26	NTU6238GKV
NTU6240GKV	27,8	1 1/2	220-240V 50Hz 1 ~	CSR	HST	MBP	4458	2,66	2431	1,98	55 45		- 1622	- 1978	1940 2425	2358 2957	2837 3570	3372 4258	3959 5017	18,4	253	37,5	F	520	650	POE 22	C/V	DWG19	SM26	NTU6240GKV
NJ9238GK	32,7	1 1/2	230V 50Hz 1 ~	CSR	HST	M/HBP	4620	2,09	2424	1,59	55 45		- 1507	- 1939	1895 2424	2323 2970	2804 3583	3347 4272	3958 5044	22,1	277	43	F	800	750	POE 22	C/V	DWG14	SM17	NJ9238GK
NJ9238GŠ	32,7	1 1/2	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	M/HBP	4839	2,55	2506	1,9	55 45		- 1514	- 1979	1883 2506	2345 3091	2863 3735	3435 4441	4062 5207	21,7	277	22	F	800	750</					

* MODEL UNDER DEVELOPMENT

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R404A/R507/R452A • LBP • 60Hz - EU portfolio

											COOLING CAPACITY ARI 540																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - ARI540 -23,3 °C / 48,9 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-40	-35	-30	-25	-20	-15	-10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
NEK2117GK	4,5	1/4	115V 60Hz 1 ~	CSIR	HST	LBP	287	1,19	211	0,89	55		-	-	119	154	195	243	296	10,4	187	28,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK2117GK
											45		92	117	151	197	251	312	379											
NEK2121GK	5,4	1/3	115V 60Hz 1 ~	CSIR	HST	LBP	355	1,24	261	0,92	55		-	-	149	191	240	296	359	10,4	187	26,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK2121GK
											45		118	151	193	245	306	376	454											
NEK2125GK	6,2	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	LBP	-	-	262	0,91	55		-	-	153	202	261	327	402	10,4	188	13	F	520	350	POE 22	C/V	DWG04	SM04	NEK2125GK
											45		110	152	205	269	345	432	530											
NEK2125GK	6,2	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	LBP	-	-	265	0,96	55		-	-	155	207	268	338	418	10,4	188	13	F	520	350	POE 22	C/V	DWG04	SM06	NEK2125GK
											45		111	152	204	269	346	435	537											
NEK2125GK	6,2	1/3	115V 60Hz 1 ~	CSIR	HST	LBP	427	1,32	314	0,99	55		-	-	183	231	287	350	420	10,4	187	26,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK2125GK
											45		141	179	228	288	359	440	530											
NEK2125GK	6,2	1/3	100V 50/60Hz 1 ~	CSIR	HST	LBP	399	1,25	-	-	55		-	-	-	-	-	-	-	11,2	206	32	F	520	350	POE 22	C/V	DWG04	SM04	NEK2125GK
											45		-	-	-	-	-	-	-											
NEK2125GK	6,2	1/3	100V 50/60Hz 1 ~	CSR	HST	LBP	405	1,36	-	-	55		-	-	-	-	-	-	-	11,2	206	32	F	520	350	POE 22	C/V	DWG04	SM06	NEK2125GK
											45		-	-	-	-	-	-	-											
NEK2134GK	8,8	1/2	100V 50/60Hz 1 ~	CSIR	HST	LBP	529	1,24	387	0,93	55		-	-	218	284	357	448	544	11,5	206	34	F	520	350	POE 22	C/V	DWG04	SM04	NEK2134GK
											45		161	224	292	382	482	589	706											
NEK2134GK	8,8	1/2	100V 50/60Hz 1 ~	CSR	HST	LBP	533	1,33	391	1	55		-	-	219	286	362	447	539	11,5	206	34	F	520	350	POE 22	C/V	DWG04	SM06	NEK2134GK
											45		171	222	291	369	469	582	697											
NEK2134GK	8,8	1/2	208-230V 60Hz 1 ~	CSIR	HST	LBP	544	1,3	400	0,97	55		-	-	223	290	368	457	554	11,6	206	20	F	520	350	POE 22	C/V	DWG04	SM04	NEK2134GK
											45		164	220	290	375	472	583	707											
NEK2134GK	8,8	1/2	115V 60Hz 1 ~	CSIR	HST	LBP	571	1,32	420	0,99	55		-	-	236	307	387	476	573	11	200	40	F	520	350	POE 22	C/V	DWG04	SM04	NEK2134GK
											45		173	231	303	387	485	594	714											
NEU2140GK	8,8	1/2	115-127V 60Hz 1 ~	CSIR	HST	LBP	564	1,34	409	0,99	55		-	-	240	317	407	512	630	11,3	200	30	F	520	350	POE 22	C/V	DWG04	SM04	NEU2140GK
											45		175	238	318	413	525	653	797											
NEU2140GK	8,8	1/2	115-127V 60Hz 1 ~	CSR	HST	LBP	573	1,45	414	1,07	55		-	-	244	323	415	520	639	11,3	200	30	F	520	350	POE 22	C/V	DWG04	SM06	NEU2140GK
											45		178	240	320	418	534	667	818											
NEU2140GK	8,8	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	LBP	568	1,36	409	0,99	55		-	-	-	-	-	-	-	11,2	200	18	F	520	350	POE 22	C/V	DWG04	SM04	NEU2140GK
											45		-	-	-	-	-	-	-											
NEK2150GK	12,1	1/2	208-230V 60Hz 1 ~	CSIR	HST	LBP	718	1,25	509	0,89	55		-	-	288	371	468	580	706	11,6	206	20	F	520	350	POE 22	C/V	DWG04	SM04	NEK2150GK
											45		235	297	379	481	603	744	902											
NEK2150GK	12,1	1/2	100V 50/60Hz 1 ~	CSR	HST	LBP	711	1,35	512	0,98	55		-	-	285	372	472	586	711	11,6	206	20	F	520	350	POE 22	C/V	DWG04	SM06	NEK2150GK
											45		213	283	374	482	607	747	901											
NEK2150GK	12,1	1/2	115-127V 60Hz 1 ~	CSIR	HST	LBP	710	1,25	502	0,86	55		-	-	298	385	486	599	725	11,6	206	42	F	520	350	POE 22	C/V	DWG04	SM04	NEK2150GK
											45		231	300	389	496	622	766	927											
NEK2150GK	12,1	1/2	115-127V 60Hz 1 ~	CSR	HST	LBP	724	1,36	498	0,91	55		-	-	325	423	538	669	818	11,6	206	42	F	520	350	POE 22	C/V	DWG04	SM06	NEK2150GK
											45		250	324	421	541	683	848	1036											
NEU2155GK	12,1	3/4	115-127V 60Hz 1 ~	CSIR	HST	LBP	763	1,3	559	0,99	55		-	-	332	435	553	687	836	11,3	206	40	F	520	350	POE 22	C/V	DWG04	SM04	NEU2155GK
											45		240	326	434	564	715	888	1083											
NEU2155GK	12,1	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	774	1,42	563	1,07	55		-	-	331	437	562	707	870	11,3	206	40	F	520	350	POE 22	C/V	DWG04	SM06	NEU2155GK
											45		240	326	435	567	723	901	1104											
NEU2155GK	12,1	3/4	208-230V 60Hz 1 ~	CSIR	HST	LBP	771	1,29	560	0,99	55		-	-	-	-	-	-	-	11,2	206	23	F	520	350	POE 22	C/V	DWG04	SM04	NEU2155GK
											45		-	-	-	-	-	-	-											
NEU2155GK	12,1	3/4	208-230V 60Hz 1 ~	CSR	HST	LBP	784	1,45	570	1,03	55		-	-	-	-	-	-	-	11,2	206	23	F	520	350	POE 22	C/V	DWG04	SM06	NEU2155GK
											45		-	-	-	-	-	-	-											
NEK2168GK	14,3	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	833	1,34	577	0,95	55		-	-	334	443	569	714	875	11,6	206	46	F	520	350	POE 22	C/V	DWG04	SM06	NEK2168GK
											45		244	336	449	585	741	920	1119											
NEK2168GK	14,3	3/4	208-230V 60Hz 1 ~	CSR	HST	LBP	816	1,29	584	0,94	55		-	-	343	456	589	740	911	11,6	206	27	F	520	350	POE 22	C/V	DWG04	SM06	NEK2168GK
											45		244	333	448	588	753	943	1159											
NEU2168GK	14,3	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	900	1,42	649	1,05	55		-	-	389	511	655	820	1007	11,6	206	49	F	520	350	POE 22	C/V	DWG04	SM06	NEU2168GK
											45		285	381	505	655	833	1038	1270											
NEU2168GK	14,3	3/4	208-230V 60Hz 1 ~	CSR	HST	LBP	927	1,44	673	1,03	55		-	-	-	-	-	-	-	11,6	206	29	F	520	350	POE 22	C/V	DWG04	SM06	NEU2168GK
											45		-	-	-	-	-	-	-											

...FOLLOW

R404A/R507/R452A • LBP • 60Hz - EU portfolio

											COOLING CAPACITY ARI 540																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - ARI540 -23,3 °C / 48,9 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-40	-35	-30	-25	-20	-15	-10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
NT2168GK(V)	14,5	3/4	115V 60Hz 1 ~	CSR	HST	LBP	830	1,41	610	1,03	55		-	-	331	455	599	765	954	17	220	54,5	F	520	450	POE 22	C/V	DWG17	SM21	NT2168GK(V)
											45		231	340	470	622	799	1003	1234											
NT2168GK(V)	14,5	3/4	208-230V 60Hz 1 ~	CSR	HST	LBP	838	1,42	616	1,03	55		-	-	305	426	572	746	945	16,7	220	29	F	520	450	POE 22	C/V	DWG16	SM23	NT2168GK(V)
											45		219	323	455	614	801	1015	1257											
NEU2178GK	16,8	1	115-127V 60Hz 1 ~	CSR	HST	LBP	1055	1,35	758	1,00	55		-	-	456	595	758	945	1156	11,6	206	53	F	520	350	POE 22	C/V	DWG04	SM06	NEU2178GK
											45		330	443	586	759	962	1195	1458											
NEU2178GK	16,8	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1055	1,37	763	1,00	55		-	-	466	610	769	945	1136	11,5	206	29	F	520	350	POE 22	C/V	DWG04	SM06	NEU2178GK
											45		343	479	637	817	1018	1242	1488											
NT2178GK(V)	17,4	3/4	100V 50/60Hz 1 ~	CSR	HST	LBP	1013	1,36	583	0,82	55		-	-	378	510	666	848	1055	16,7	220	60	F	520	450	POE 22	C/V	DWG17	SM21	NT2178GK(V)
											45		280	393	535	703	899	1121	1366											
NT2178GK(V)	17,4	1	115V 60Hz 1 ~	CSR	HST	LBP	1050	1,41	772	1,05	55		-	-	422	562	722	901	1098	17	220	66	F	520	450	POE 22	C/V	DWG17	SM21	NT2178GK(V)
											45		288	415	566	744	945	1169	1415											
NT2178GK(V)	17,4	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1070	1,35	750	0,9	55		-	-	418	563	735	935	1166	17	220	35,5	F	520	450	POE 22	C/V	DWG16	SM23	NT2178GK(V)
											45		281	410	570	760	981	1233	1516											
NT2178GK(V)	17,4	1	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	LBP	1006	1,28	-	-	55		-	-	-	-	-	-	-	17	220	26	F	520	450	POE 22	C/V	DWG16	SM20	NT2178GK(V)
											45		-	-	-	-	-	-	-											
NT2178GK(V)	17,4	1	200-240V 50Hz / 230V 60Hz 1 ~	CSR	HST	LBP	1002	1,42	-	-	55		-	-	-	-	-	-	-	17	220	26	F	520	450	POE 22	C/V	DWG16	SM23	NT2178GK(V)
											45		-	-	-	-	-	-	-											
NT2180GK(V)	20,4	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1161	1,32	854	0,99	55		-	-	456	610	782	973	1184	17,5	234	40	F	520	450	POE 22	C/V	DWG16	SM23	NT2180GK(V)
											45		296	440	610	809	1038	1298	1590											
NT2180GK(V)	20,4	1	115V 60Hz 1 ~	CSR	HST	LBP	1204	1,36	902	1,05	55		-	-	458	638	852	1099	1379	17,5	220	66	F	520	450	POE 22	C/V	DWG17	SM21	NT2180GK(V)
											45		294	456	648	870	1122	1404	1716											
NT2180GK(V)	20,4	1	115-127V 60Hz 1 ~	CSR	HST	LBP	1206	1,37	-	-	55		-	-	-	-	-	-	-	16,7	220	57	F	520	450	POE 22	C/V	DWG17	SM21	NT2180GK(V)
											45		-	-	-	-	-	-	-											
NT2192G5	22,4	1	200V 50/60Hz 3 ~	3PHASE	HST	LBP	1220	1,29	897	0,99	55		-	-	492	655	844	1060	1297	18	250	28,5	F	520	650	POE 22	C/V	DWG17	SM27	NT2192G5
											45		347	487	660	867	1104	1372	1668											
NT2192GK(V)	22,4	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1262	1,43	951	1,05	55		-	-	508	706	936	1197	1490	18	234	40	F	520	450	POE 22	C/V	DWG16	SM23	NT2192GK(V)
											45		307	490	708	961	1249	1573	1932											
NT2192GK(V)	22,4	1	115V 60Hz 1 ~	CSR	HST	LBP	1283	1,41	943	1,02	55		-	-	541	710	917	1160	1438	17,5	234	56	F	520	450	POE 22	C/V	DWG17	SM21	NT2192GK(V)
											45		385	535	727	960	1233	1543	1890											
NJ2192GK	26,1	1 1/4	115V 60Hz 1 ~	CSR	HST	LBP	1319	1,3	968	0,96	55		-	-	444	600	783	993	1234	21,7	277	98	F	800	750	POE 22	C/V	DWG14	SM16	NJ2192GK
											45		270	440	624	827	1052	1303	1582											
NJ2192GJ	26,1	1 1/4	208-230V 60Hz 1 ~	CSR	HST	LBP	1399	1,33	970	0,96	55		-	-	405	589	791	1010	1245	21,8	277	44	F	800	750	POE 22	C/V	DWG14	SM16	NJ2192GJ
											45		203	390	594	814	1052	1309	1586											
NJ2192G5	26,1	1 1/4	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	LBP	1319	1,24	970	0,9	55		-	-	444	601	782	993	1232	19,7	265	13	F	800	750	POE 22	C/V	DWG14	SM18	NJ2192G5
											45		270	440	624	827	1052	1303	1582											
NT2212G5	27,8	1 1/3	200V 50/60Hz 3 ~	3PHASE	HST	LBP	1571	1,31	1155	0,98	55		-	-	622	822	1049	1304	1583	18	250	36	F	520	650	POE 22	C/V	DWG17	SM27	NT2212G5
											45		411	607	833	1090	1375	1687	2025											
NT2212GKV	27,8	1 1/2	115V 60Hz 1 ~	CSR	HST	LBP	1649	1,33	1213	0,99	55		-	-	660	878	1135	1432	1768	18,3	250	93	F	520	650	POE 22	C/V	DWG17	SM26	NT2212GKV
											45		446	643	880	1159	1478	1840	2242											
NT2212GK(V)	27,8	1 1/2	208-230V 60Hz 1 ~	CSR	HST	LBP	1673	1,42	1230	1,03	55		-	-	723	959	1233	1545	1894	18,3	250	45	F	520	650	POE 22	C/V	DWG17	SM26	NT2212GK(V)
											45		482	693	949	1249	1592	1980	2412											
NJ2212GK	34,4	1 1/3	115V 60Hz 1 ~	CSR	HST	LBP	1595	1,22	1173	0,9	55		-																	

* MODEL UNDER DEVELOPMENT

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R404A/R507 • MBP - M/HBP • 60Hz - EU portfolio

											COOLING CAPACITY ARI540																				
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - ARI540 -6,7 °C / 48,9 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL	
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-20	-15	-10	-5	0	5	10						CHARGE cm³	TYPE			EXTERNAL VIEW REFERENCE		WIRING DIAGRAM REFERENCE
NEK6144GK	4,5	1/4	115V 60Hz 1~	CSIR	HST	MBP	842	2,14	400	1,28	55		-	-	291	358	435	519	613	10	187	26	F	520	350	POE 22	C/V	DWG04	SM04	NEK6144GK	
											45		238	303	379	467	567	679	802												
NEK6144GK	4,5	1/4	208-230V 60Hz 1 ~	CSIR	HST	MBP	800	2,06	395	1,28	55		-	-	316	384	464	555	661	10,4	187	11,6	F	520	350	POE 22	C/V	DWG04	SM04	NEK6144GK	
											45		250	316	391	476	573	683	807												
NEK6152GK	5,4	1/4	115V 60Hz 1~	CSIR	HST	MBP	1018	2,09	481	1,22	55		-	-	362	441	530	630	741	10,2	187	34	F	520	350	POE 22	C/V	DWG04	SM04	NEK6152GK	
											45		302	375	462	563	678	808	951												
NEK6165GK	6,2	1/3	115V 60Hz 1~	CSIR	HST	MBP	1150	1,97	552	1,23	55		-	-	463	558	667	790	928	10,4	187	26,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK6165GK	
											45		380	458	555	671	806	958	1130												
NEK6181GK	7,3	1/3	115V 60Hz 1~	CSIR	HST	MBP	1247	2,01	616	1,26	55		-	-	511	611	726	856	1006	10,4	187	30,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK6181GK	
											45		418	504	611	738	888	1062	1265												
NEK6181GK	7,3	1/3	115V 60Hz 1~	CSR	HST	MBP	1321	2,33	627	1,34	55		-	-	509	624	756	902	1060	10,4	187	30,5	F	520	350	POE 22	C/V	DWG04	SM06	NEK6181GK	
											45		419	513	633	774	933	1106	1292												
NEK6181GK	7,3	1/3	208-230V 60Hz 1 ~	CSIR	HST	MBP	1290	2,07	610	1,26	55		-	-	506	612	740	886	1048	10,4	187	17,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK6181GK	
											45		432	508	616	752	913	1095	1295												
NEU6181GK	6,2	1/3	115-127V 60Hz 1 ~	CSIR	HST	MBP	1213	2,11	600	1,39	55		-	-	433	544	683	851	1046	10	187	31	F	520	350	POE 22	C/V	DWG04	SM04	NEU6181GK	
											45		379	447	550	690	865	1076	1323												
NEU6181GK	6,2	1/3	115-127V 60Hz 1 ~	CSR	HST	MBP	1237	2,33	599	1,47	55		-	-	445	558	700	872	1074	10	187	31	F	520	350	POE 22	C/V	DWG04	SM06	NEU6181GK	
											45		380	453	563	712	898	1123	1386												
NEU6181GK	6,2	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	MBP	-	-	6,1	1,42	55		-	-	452	559	684	827	988	10,7	200	18	F	520	350	POE 22	C/V	DWG04	SM04	NEU6181GK	
											45		378	459	567	701	861	1049	1263												
NEU6210GK	7,3	1/3	115-127V 60Hz 1 ~	CSIR	HST	MBP	1428	2,38	687	1,41	55		-	-	493	629	799	1005	1243	10,6	200	39	F	520	350	POE 22	C/V	DWG04	SM04	NEU6210GK	
											45		426	507	634	808	1025	1289	1599												
NEU6210GK	7,3	1/3	115-127V 60Hz 1 ~	CSR	HST	MBP	1435	2,56	689	1,51	55		-	-	496	629	796	999	1235	10,6	200	39	F	520	350	POE 22	C/V	DWG04	SM06	NEU6210GK	
											45		423	510	641	817	1038	1303	1612												
NEU6210GK	7,3	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	MBP	-	-	680	1,5	55		-	-	486	615	776	970	1196	11,1	200	21	F	520	350	POE 22	C/V	DWG04	SM04	NEU6210GK	
											45		426	515	641	806	1009	1250	1529												
NEU6210GK	7,3	1/3	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	MBP	-	-	687	1,6	55		-	-	502	631	787	970	1179	11,1	200	21	F	520	350	POE 22	C/V	DWG04	SM06	NEU6210GK	
											45		430	523	651	815	1015	1249	1519												
NEK6210GK	8,8	1/2	100V 50/60 HZ 1 ~	CSIR	HST	MBP	1583	2,07	754	1,32	55		-	-	618	753	905	1074	1256	11	200	38	F	520	350	POE 22	C/V	DWG04	SM04	NEK6210GK	
											45		499	623	770	939	1130	1343	1573												
NEK6210GK	8,8	1/2	115V 60Hz 1~	CSIR	HST	MBP	1569	2,07	753	1,34	55		-	-	621	749	901	1075	1272	11	200	38	F	520	350	POE 22	C/V	DWG04	SM04	NEK6210GK	
											45		511	620	756	918	1105	1317	1555												
NEK6210GK	8,8	1/2	208-230V 60Hz 1 ~	CSIR	HST	MBP	1540	2,1	750	1,34	55		-	-	597	728	878	1048	1239	11,5	206	23	F	520	350	POE 22	C/V	DWG04	SM04	NEK6210GK	
											45		490	606	745	906	1089	1292	1520												
NEK6210GK	8,8	1/2	115V 60Hz 1~	CSR	HST	MBP	1612	2,3	767	1,43	55		-	-	615	757	920	1104	1310	11	200	38	F	520	350	POE 22	C/V	DWG04	SM06	NEK6210GK	
											45		493	618	766	937	1131	1347	1587												
NEU6212GK	8,8	1/2	115-127V 60Hz 1 ~	CSIR	HST	MBP	1676	2,19	831	1,45	55		-	-	582	747	967	1231	1539	10,7	200	39	F	520	350	POE 22	C/V	DWG04	SM04	NEU6212GK	
											45		528	611	754	958	1222	1546	1930												
NEU6212GK	8,8	1/2	115-127V 60Hz 1 ~	CSR	HST	MBP	1703	2,39	841	1,56	55		-	-	594	759	971	1230	1536	10,7	200	39	F	520	350	POE 22	C/V	DWG04	SM06	NEU6212GK	
											45		521	616	767	975	1238	1559	1935												
NEU6212GK	8,8	1/2	208-230V 60Hz 1 ~	CSIR	HST	MBP	1678	2,18	842	1,42	55		-	-	585	749	959	1217	1521	11,5	200	22	F	520	350	POE 22	C/V	DWG04	SM04	NEU6212GK	
											45		522	611	759	964	1228	1549	1928												
NEU6212GK	8,8	1/2	208-230V 60Hz 1 ~	CSR	HST	MBP	1714	2,42	848	1,51	55		-	-	593	758	968	1223	1524	11,5	200	22	F	520	350	POE 22	C/V	DWG04	SM06	NEU6212GK	
											45		516	612	764	972	1236	1556	1932												
NEU6214GK	10,0	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSIR	HST	MBP	1891	2,12	964	1,47	55		-	-	699	865	1062	1291	1550	11,6	206	26	F	520	350	POE 22	C/V	DWG04	SM04	NEU6214GK	
											45		598	733	902	1107	1346	1620	1929												
NEU6214GK	10,0	1/2	200-230V 50Hz / 208-230V 60Hz 1 ~	CSR	HST	MBP	1939	2,4	974	1,57	55		-	-	697	877	1102	1371	1685	11,6	206	26	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214GK	
											45		607	719	890	1119	1408	1755	2161												
NEU6214GK	10,0	1/2	115-127V 60Hz 1 ~	CSIR	HST	MBP	1914	2,11	960	1,43	55		-	-	692	870	1099	1379	1710	11,2	206	42	F	520	350	POE 22	C/V	DWG04	SM04	NEU6214GK	
											45		600	721	897	1128	1415	1756	2153												
NEU6214GK	10,0	1/2	115-127V 60Hz 1 ~	CSR	HST	MBP	1969	2,38	966	1,55	55		-	-	724	897	1104	1344	1618	11,2	206	42	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214GK	
											45		623	747	918	1135	1399	1710	2067												
NEK6213GK	12,1	1/2	115V 60Hz 1~	CSIR	HST	MBP	1952	1,7	1050	1,21	55		-	-	799	965	1148	1348	1568	11,6	206	51	F	520	350	POE 22	C/V	DWG04	SM04	NEK6213GK	
											45		634	786	963	1166	1393	1421	1921												
NEK6213GK	12,1	1/2	115V 60Hz 1~	CSR	HST	MBP	2066	1,96	1113	1,33	55		-	-	819	994	1196	1221	1671	11,6	206	51	F	520	350	POE 22	C/V	DWG04	SM06	NEK6213GK	
											45		647	804	990	1204	1445	1713	2008												
NEK6213GK	12,1	1/2	208-230V 60Hz 1 ~	CSIR	HST	MBP	2035	1,84	1039	1,22	55		-	-	815	987	1180	1390	1621	11,9	206	30	F	520	350	POE 22	C/V	DWG04	SM04	NEK6213GK	
											45		654	813	998	1207	1438	1693	1971												
NEK6213GK	12,1	1/2	208-230V 60Hz 1 ~	CSR	HST	MBP	2114																								

...FOLLOW

R404A/R507 • MBP - M/HBP • 60Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - ARI540 -6,7 °C / 48,9 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-20	-15	-10	-5	0	5	10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
NT6217GK(V)	12,6	3/4	208-230V 60Hz 1 ~	CSR	HST	MBP	2238	2,6	1115	1,53	55		-	-	846	1041	1260	1503	1769	17	220	27	F	520	450	POE 22	C/V	DWG16	SM23	NT6217GK(V)
NT6217GK(V)	12,6	3/4	115V 60Hz 1~	CSIR	HST	MBP	2163	2,2	1030	1,26	45		677	851	1060	1304	1582	1896	2244	17	220	50	F	520	450	POE 22	C/V	DWG16	SM20	NT6217GK(V)
											55		-	-	773	949	1153	1384	1641											
NT6217GK(V)	12,6	3/4	115V 60Hz 1~	CSR	HST	MBP	2251	2,68	1072	1,54	45		726	819	974	1192	1471	1813	2216	17	220	50	F	520	450	POE 22	C/V	DWG16	SM23	NT6217GK(V)
											55		-	-	774	992	1256	1567	1924											
NEU6220GK	14,3	3/4	115-127V 60Hz 1 ~	CSR	HST	MBP	2592	1,98	1340	1,42	45		656	811	1017	1273	1581	1938	2347	11,5	206	57	F	520	350	POE 22	C/V	DWG04	SM06	NEU6220GK
											55		-	-	991	1220	1494	1813	2176											
NEU6220GK	14,3	3/4	208-230V 60Hz 1 ~	CSR	HST	MBP	2652	2,07	1358	1,41	45		851	1026	1258	1545	1887	2286	2740	11,5	206	34	F	520	350	POE 22	C/V	DWG04	SM06	NEU6220GK
											55		-	-	997	1229	1520	1880	2320											
NT6220GK(V)	14,5	3/4	208-230V 60Hz 1 ~	CSIR	HST	MBP	2406	1,98	1247	1,38	45		855	1033	1263	1555	1919	2365	2905	16,9	220	26,5	F	520	450	POE 22	C/V	DWG16	SM20	NT6220GK(V)
											55		-	-	955	1165	1400	1663	1957											
NT6220GK(V)	14,5	3/4	115V 60Hz 1~	CSR	HST	MBP	2490	2,34	1250	1,52	45		769	962	1187	1447	1742	2075	2449	17	220	54,5	F	520	450	POE 22	C/V	DWG17	SM21	NT6220GK(V)
											55		-	-	918	1138	1383	1653	1949											
NT6220GK(V)	14,5	3/4	208-230V 60Hz 1 ~	CSR	HST	MBP	2566	2,36	1283	1,57	45		752	966	1208	1477	1773	2097	2448	16,9	220	26,5	F	520	450	POE 22	C/V	DWG16	SM23	NT6220GK(V)
											55		-	-	936	1186	1482	1825	2214											
NT6222GK(V)	17,4	3/4	208-230V 60Hz 1 ~	CSIR	HST	MBP	2928	1,88	1475	1,14	45		757	950	1203	1516	1889	2323	2818	17,2	220	33,7	F	520	450	POE 22	C/V	DWG16	SM20	NT6222GK(V)
											55		-	-	1166	1425	1708	2012	2331											
NT6222GK(V)	17,4	3/4	208-230V 60Hz 1 ~	CSR	HST	MBP	3051	2,3	1537	1,4	45		952	1185	1462	1779	2129	2506	2905	17,2	220	33,7	F	520	450	POE 22	C/V	DWG16	SM23	NT6222GK(V)
											55		-	-	1185	1459	1766	2100	2459											
NT6222GK(V)	17,4	3/4	115V 60Hz 1~	CSR	HST	MBP	3040	2,39	1579	1,58	45		975	1231	1532	1873	2253	2665	3108	17	220	70	F	520	450	POE 22	C/V	DWG17	SM23	NT6222GK(V)
											55		-	-	1276	1570	1899	2263	2661											
NT6222GK(V)	17,4	3/4	200-240V 50Hz / 230V 60Hz 1 ~	CSIR	HST	MBP	2965	2,06	-	-	45		988	1273	1598	1964	2370	2816	3303	17	220	37	F	520	450	POE 22	C/V	DWG16	SM20	NT6222GK(V)
											55		-	-	-	-	-	-	-											
NT6224GKV	20,4	1	208-230V 60Hz 1 ~	CSR	HST	MBP	3512	2,25	1808	1,55	45		-	-	1392	1690	2023	2392	2804	16,8	220	36	F	520	450	POE 22	C/V	DWG16	SM23	NT6224GKV
											55		1134	1409	1724	2083	2488	2940	3447											
NT6224GKV	20,4	1	115V 60Hz 1~	CSR	HST	MBP	3612	2,3	1859	1,55	45		-	-	1399	1714	2068	2460	2893	16,9	234	77	F	520	450	POE 22	C/V	DWG17	SM26	NT6224GKV
											55		1144	1419	1744	2120	2543	3014	3533											
NTU6232G5V	20,4	1	200-230V 60Hz 3 ~	3PHASE	HST	MBP	3982	2,8	2043	1,77	45		-	-	1504	1846	2231	2645	3100	18,4	250	36	F	520	650	POE 22	C/V	DWG19	SM27	NTU6232G5V
											55		1264	1595	1966	2387	2863	3407	3950											
NTU6232GKV	20,4	1	115V 60Hz 1~	CSR	HST	MBP	4056	2,7	2052	1,68	45		-	-	1550	1908	2310	2762	3268	18,3	250	93	F	520	650	POE 22	C/V	DWG19	SM26	NTU6232GKV
											55		1298	1645	2037	2480	2977	3534	4154											
NTU6232GKV	20,4	1	208-230V 60Hz 1 ~	CSR	HST	MBP	3968	2,8	2068	1,71	45		-	-	1559	1907	2271	2652	3049	18,1	250	46	F	520	650	POE 22	C/V	DWG19	SM26	NTU6232GKV
											55		1234	1596	1995	2430	2900	3405	3944											
NJ9226GK	21,7	1	208-230V 60Hz 1 ~	CSR	HST	M/HBP	3708	2,2	2742	2,19	45		-	-	1364	1718	2110	2542	3013	20,7	265	34	F	800	750	POE 22	C/V	DWG14	SM17	NJ9226GK
											55		1088	1391	1754	2176	2655	3189	3780											
NJ9226G5	21,7	1	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	M/HBP	3801	2,5	2811	2,38	45		-	-	1236	1554	1911	2307	2743	19	265	10	F	800	750	POE 22	C/V	DWG14	SM18	NJ9226G5
											55		947	1223	1556	1942	2382	2873	3419											
NT6226GK(V)	22,4	1	115V 60Hz 1~	CSR	HST	MBP	3884	2,12	1969	1,44	45		-	-	1457	1798	2207	2686	3234	17,5	234	77	F	520	450	POE 22	C/V	DWG17	SM26	NT6226GK(V)
											55		1212	1512	1874	2303	2798	3358	3984											
NT6226GK(V)	22,4	1	208-230V 60Hz 1 ~	CSR	HST	MBP	3734	1,93	2009	1,48	45		-	-	1493	1822	2189	2595	3039	17,5	234	43	F	520	450	POE 22	C/V	DWG17	SM21	NT6226GK(V)
											55		1220	1529	1886	2292	2745	3246	3796											
NTU6234G5V	23,7	1 1/4	200-230V 60Hz 3 ~	3PHASE	HST	MBP	4574	2,67	2404	1,76	45		-	-	1766	2156	2588	3066	3592	18,3	250	36	F	520	650	POE 22	C/V	DWG19	SM27	NTU6234G5V
											55		1492	1875	2306	2789	3326	3919	4573											
NTU6234GKV	23,7	1 1/4	115V 60Hz 1~	CSR	HST	MBP	4621	2,72	2411	1,77	45		-	-	1772	2165	2613	3121	3695	18,4	250	81	F	520	650	POE 22	C/V	DWG19	SM26	NTU6234GKV
											55		1506	1885	2320	2814	3376	4009	4719											
NTU6234GKV	23,7	1 1/4	208-230V 60Hz 1 ~	CSR	HST	MBP	4557	2,71	2407	1,7	45		-	-	1830	2237	2685	3175	3709	18,1	250	46	F	520	650	POE 22	C/V	DWG19	SM26	NTU6234GKV
											55		1538	1945	2400	2905	3460	4066	4726											
NJ9232GK	26,1	1 1/4	208-230V 60Hz 1 ~	CSR	HST	M/HBP	4704	2,4	2215	1,46	45		-	-	1564	1963	2406	2894	3426	21,5	277	47	F	800	750	POE 22	C/V	DWG14	SM16	NJ9232GK
											55		1296	1677	2119	2622	3185	3809	4494											
NJ9232G5	26,1	1 1/4	380-420V 50Hz / 440-480V 60Hz 3 ~	3PHASE	HST	M/HBP	4716	2,5	3488	2,47	45		-	-	1464	1845	2276	2754	3282	20,4	277	13	F	800	750	POE 22	C/V	DWG14	SM18	NJ9232G5
											55		1116	1444	1840	2305	2835	3429	4090											
NTU6238G5V	26,2	1 1/2	200-230V 60Hz 3 ~	3PHASE	HST	MBP	4877	2,49	2670	1,76	45		-	-	1978	2395	2846	3330	3845	18,3	250	36	F	520	650	POE 22	C/V	DWG19	SM27	NTU6238G5V
											55		1671	2092	2561	3078	3640	4246	4894											
NTU6238GKV	26,2	1 1/2	208-230V 60Hz 1 ~	CSR	HST	MBP	5072	2,66	2703	1,71	45		-	-	1965	2426	2972	3614	4365	18,3	250	51	F	520	650	POE 22	C/V	DWG19	SM26	NTU6238GKV
											55		1736	2146	2621	3171	3808	4544	5387											
NTU6240GKV	27,8	1 1/2	208-230V 60Hz 1 ~	CSR	HST	MBP	5333	2,58	2841	1,7	45		-	-	2062	2499	3049	3760	4679	18,3	250	51	F	520	650	POE 22	C/V	DWG19	SM26	NTU6240GKV
											55		1790	2223	2695	3254	3947	4822	5926											
NTU6240G5V	27,8	1 1/2	200-230V 60Hz 3 ~	3PHASE	HST	MBP	52																							

R290 • LBP - L/MBP • 50Hz - EU portfolio

REFRIGERANT LBP 3PHASE 230V 50/60Hz											COOLING CAPACITY EN12900																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - EN12900 -35 °C / 40 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-40	-35	-30	-25	-20	-15	-10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
EMT2117U	4,5	1/5	220-240V 50Hz 1 ~	CSIR	HST	LBP	184	1,37	123	1,13	55		-	-	120	155	195	242	296	7,8	166	7,7	S	-	180	POE 22	C	DWG01	SM05	EMT2117U
										45		84	112	145	184	230	283	345												
EMC3117U	4,0	1/5	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	197	1,83	-	-	55		-	-	-	-	-	-	-	8,2	171	4,8	F	270	150	POE 10	C	DWG01	SM01-02	EMC3117U
										45		-	-	-	-	-	-	-												
EMC3119U	4,5	1/4	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	236	1,86	112	1,62	55		-	95	121	157	201	255	318	8,2	171	6,8	F	270	150	POE 10	C	DWG01	SM01-02	EMC3119U
										45		-	105	144	189	243	303	370												
EMT2121U	5,6	1/4	220-240V 50Hz 1 ~	CSIR	HST	LBP	265	1,46	159	1,23	55		-	-	156	200	252	311	379	7,8	166	7,7	S	-	180	POE 22	C	DWG01	SM05	EMT2121U
										45		110	145	188	238	297	364	440												
EMC3121U	5,5	1/4	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	271	1,88	160	1,59	55		-	-	-	-	-	-	-	8,2	171	6,6	F	270	150	POE 10	C	DWG01	SM01-02	EMC3121U
										45		-	-	-	-	-	-	-												
EMT2125U	6,0	1/3	220-240V 50Hz 1 ~	CSIR	HST	LBP	301	1,47	177	1,2	55		-	-	176	225	282	348	422	7,8	166	9,8	F	520	180	POE 22	C/V	DWG01	SM05	EMT2125U
										45		124	162	209	265	330	403	486												
EMC3125U	6,1	1/3	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	305	1,88	181	1,6	55		-	-	-	-	-	-	-	8,2	171	6,6	F	270	150	POE 10	C	DWG01	SM01-02	EMC3125U
										45		-	-	-	-	-	-	-												
EMT2130U	6,8	1/3	220-240V 50Hz 1 ~	CSIR	HST	LBP	340	1,42	196	1,12	55		-	-	196	251	315	389	472	8	166	12,4	F	520	180	POE 22	C/V	DWG01	SM05	EMT2130U
										45		137	180	233	295	367	450	543												
EMC3130U	6,9	1/3	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	349	1,84	229	1,57	55		-	-	-	-	-	-	-	8,2	171	6,6	F	270	150	POE 10	C	DWG01	SM01-02	EMC3130U
										45		-	-	-	-	-	-	-												
EMC3134U	8,0	1/2	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	417	1,85	301	1,52	55		-	179	229	290	362	446	541	8,2	171	10,3	F	270	150	POE 10	C	DWG01	SM01-02	EMC3134U
										45		-	216	269	337	420	518	631												
EMX3134U	8,0	1/2	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	406	1,65	-	-	55		-	-	-	-	-	-	-	7,6	-	10,5	F		150	POE 22	C			EMX3134U
										45		-	-	-	-	-	-	-												
EMC3140U	9,0	1/2	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	459	1,77	260	1,42	55		-	-	265	337	421	519	629	8,2	171	10,3	F	270	150	POE 10	C	DWG01	SM01-02	EMC3140U
										45		-	245	312	394	490	601	727												
EMX3140U	9,5	1/2	220-240V 50Hz 1 ~	RSIR	LST	L/MBP	482	1,39	-	-	55		-	-	-	-	-	-	-	7,9	-	12,5	F		150	POE 22	C			EMX3140U
										45		-	-	-	-	-	-	-												
NEK2134U	10,0	1/2	220-240V 50Hz 1 ~	CSIR	HST	LBP	449	1,36	271	1,21	55		-	-	269	338	423	523	639	11	200	14	F	520	350	POE 22	C/V	DWG03	SM05	NEK2134U
										45		208	252	315	395	494	611	746												
NEU1140U	10,0	1/2	220-240V 50Hz 1 ~	RSCR	LST	LBP	490	1,61	270	1,38	55		-	-	-	-	-	-	-	10,7	200	16	F	520	350	POE 22	C/V	DWG03	SM01	NEU1140U
										45		-	-	-	-	-	-	-												
NEU2140U	10,0	1/2	220-240V 50Hz 1 ~	CSIR	HST	LBP	485	1,49	265	1,26	55		-	-	-	-	-	-	-	10,5	200	14	F	520	350	POE 22	C/V	DWG03	SM05	NEU2140U
										45		-	-	-	-	-	-	-												
NEK1150U	13,5	1/2	220-240V 50Hz 1 ~	RSIR	LST	LBP	571	1,22	333	0,99	55		-	-	337	429	538	661	801	11,6	206	24,3	F	520	350	POE 22	C	DWG03	SM03	NEK1150U
										45		237	309	398	506	630	773	933												
NEK2150U	13,5	1/2	220-240V 50Hz 1 ~	CSIR	HST	LBP	581	1,29	334	1,06	55		-	-	339	435	550	683	835	11,6	206	19,5	F	520	350	POE 22	C/V	DWG03	SM05	NEK2150U
										45		237	309	403	515	650	804	979												
EHU2155U*	12,2	3/4	220-240V 50Hz 1 ~	CSIR	HST	LBP	603	1,52	341	1,23	-		-	-	-	-	-	-	-	10,2	191	ud	F	520	270	POE22	C/V	UD	SM07	EHU2155U*
										-		-	-	-	-	-	-	-												
EHX2155U*	12,2	3/4	220-240V 50Hz 1 ~	CSIR	HST	LBP	608	1,63	342	1,32	-		-	-	-	-	-	-	-	10,2	191	ud	F	520	270	POE22	C/V	UD	SM07	EHX2155U*
										-		-	-	-	-	-	-	-												
NEU2155U	13,5	3/4	220-240V 50Hz 1 ~	CSIR	HST	LBP	626	1,42	364	1,21	55		-	-	384	487	605	737	883	11,1	200	17,5	F	520	350	POE 22	C/V	DWG03	SM05	NEU2155U
										45		266	345	445	565	704	863	1041												
NEU2155U	13,5	3/4	220-240V 50Hz 1 ~	CSR	HST	LBP	639	1,56	384	1,35	55		-	-	385	492	617	760	921	11,1	200	17,5	F	520	350	POE 22	C/V	DWG03	SM06	NEU2155U
										45		270	351	452	573	715	878	1062												
NEK2160U	16,8	3/4	220-240V 50Hz 1 ~	CSR	HST	LBP	729	1,44	427	1,2	55		-	-	428	547	688	848	1030	11,9	206	18	F	520	350	POE 22	C/V	DWG03	SM06	NEK2160U
										45		306	395	508	646	808	995	1206												
NEU2168U	16,8	3/4	220-240V 50Hz 1 ~	CSR	HST	LBP	788	1,53	457	1,27	55		-	-	455	584	738	917	1121	11,6	206	21	F	520	350	POE 22	C/V	DWG03	SM06	NEU2168U
										45		319	416	540	689	865	1068	1296												
NEU2178U	18,7	1	220-240V 50Hz 1 ~	CSR	HST	LBP	905	1,52	509	1,25	55		-	-	505	639	796	976	1179	11,6	206	21	F	520	350	POE 22	C/V	DWG04	SM10	NEU2178U
										45		358	463	594	751	934	1144	1380												
NT2170U	20,4	3/4	220-240V 50Hz 1 ~	CSIR	HST	LBP	816	1,31	478	1,09	55		-	-	470	608	770	955	1162	17,2	220	6	F	520	450	POE 22	C/V	DWG16	SM19	NT2170U
										45		333	441	577	740	932	1150	1395												
NT2170U	20,4	3/4	220-240V 50Hz 1 ~	CSR	HST	LBP	831	1,44	480	1,16	55		-	-	476	620	788	981	1196	17,2	220	25	F	520	450	POE 22	C/V	DWG16	SM23	NT2170U
										45		327	441	583	753	951	1176	1430												
NT2180U	22,4	1	220-240V 50Hz 1 ~	CSIR	HST	LBP	931	1,34	550	1,12	55		-	-	536	693	874	1077	1302	18,2	234	35	F	520	450	POE 22	C/V	DWG16	SM19	NT2180U
										45		380	501	653	835	1047	1290	1563												
NT2180U	22,4	1	220-240V 50Hz 1 ~	CSR	HST	LBP	935	1,46	563	1,23	55		-	-	536	697	886	1101	1344	18,2	234	35	F	520	450	POE 22	C/V	DWG16	SM23	NT2180U
										45		388	507	659	844	1062	1312	1595												
NT2210U	27,8	1 1/4	220-240V 50Hz 1 ~	CSR	HST	LBP	1186	1,41	689	1,17	55		-	-	677	875	1108	1374	1675	18,5	234	33	F	520	450	POE 22	C/V	DWG17	SM26	NT2210U
										45		482	626	813	1041	1310	1620	1969												
NTX2211U*	27,8	1 1/4	220-240V 50Hz 1 ~	CSR	HST	LBP	1317	1,54	754	1,27	55		-	-	743	953	1195	1469	1775	17,8	234									

* MODEL UNDER DEVELOPMENT

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R290 • LBP - L/MBP • 50Hz - BR portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		CONDENSING TEMPERATURE °C		COOLING CAPACITY ASHRAE LBP							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W			EVAPORATING TEMPERATURE °C W												CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
											-35	-30	-25	-20	-15	-10	-5											
EMI50UER	3,00	1/6	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	128	1,28	55		67	92	119	147	178	212	248	8,1	171	9,2	S/F	520	160	AB 32	C	DWG10	SM07	EMI50UER
EMI70UER	4,08	1/5	220-240V 50/60Hz 1 ~	RSIR/CSIR	LST	L/MBP	176	1,17	55		98	128	163	203	250	305	368	8,1	171	9,7	S/F	520	160	AB 32	C	DWG10	SM07	EMI70UER
EMI90UEX	4,99	1/4+	220-240V 50Hz 1 ~	CSIR	HST	L/MBP	229	1,28	55		116	185	214	230	262	334	474	8,1	171	11,8	F	520	160	AB 32	C/V	DWG10	SM07	EMI90UEX
FFU130UAX	6,76	1/3+	220-240V 50/60Hz 1 ~	CSIR	HST	L/MBP	319	1,49	55		182	225	287	367	465	578	708	10	201	39	F	520	280	AB 32	C/V	DWG09	SM08	FFU130UAX
FFU160UAX	7,95	1/2	220-240V 50Hz 1 ~	CSIR	HST	L/MBP	399	1,45	55		227	298	376	465	568	688	831	10	201	21	F	520	280	AB 32	C/V	DWG09	SM08	FFU160UAX

R290 • MBP • 50Hz - EU portfolio

NEUE FIDUCIAL											COOLING CAPACITY EN12900																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - EN12900 -10 °C / 45 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL	
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-20	-15	-10	-5	0	5						10	CHARGE cm³		TYPE	EXTERNAL VIEW REFERENCE		WIRING DIAGRAM REFERENCE
EMX6144U*	4,5	1/4	220-240V 50/60Hz 1 ~	CSIR	HST	MBP	639	2,68	344	1,94	55 45		- 228	- 282	291 346	355 520	428 505	509 600	598 705	7,7	171	UD	S/F	270	150	POE 10	C/V	DWG01	SM29	EMX6144U*
EMX6152U	5,2	1/4	220-240V 50/60Hz 1 ~	CSIR	HST	MBP	712	2,79	381	1,96	55 45		- 247	- 307	316 378	388 451	470 556	563 663	666 782	7,7	171	11	S/F	270	150	POE 10	C/V	DWG01	SM29	EMX6152U*
EMX6165U	6,1	1/3	220-240V 50/60Hz 1 ~	CSIR	HST	MBP	837	2,72	451	1,97	55 45		- 298	- 367	378 451	461 548	556 659	662 783	780 920	7,7	171	UD	F	270	150	POE 10	C/V	DWG01	SM29	EMX6165U*
EMX6181U	6,9	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	975	2,9	532	2,11	55 45		- 352	- 443	454 537	544 641	647 760	768 901	914 1068	8	171	16	F	270	150	POE 10	C/V	DWG03	SM29	EMX6181U
EMX6210U	9,0	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	1266	2,68	690	2,04	55 45		- 463	- 570	588 696	711 840	849 1003	1003 1185	1172 1386	8,1	171	16	F	270	150	POE 10	C/V	DWG03	SM29	EMX6210U
NEK6181U	7,3	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	949	2,46	489	1,71	55 45		- 310	- 387	397 482	491 594	600 723	723 871	860 1036	10,4	187	12	F	520	350	POE 22	C/V	DWG03	SM05	NEK6181U
NEU5181U	7,3	1/3	220-240V 50Hz 1 ~	RSCR	LST	MBP	1021	2,94	595	2,26	55 45		- -	- -	- -	- -	- -	- -	- -	10	187	16	F	520	350	POE 22	C/V	DWG03	SM01	NEU5181U
NEU6181U	7,3	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	1000	2,7	574	2,02	55 45		- -	- -	- -	- -	- -	- -	- -	10	187	13	F	520	350	POE 22	C/V	DWG03	SM05	NEU6181U
NEK6210U	8,8	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	1169	2,55	654	1,91	55 45		- 401	- 492	509 605	625 739	757 895	908 1072	1076 1272	10,7	200	16,1	F	520	350	POE 22	C/V	DWG03	SM05	NEK6210U
NEU6210U	8,8	1/3	220-240V 50Hz 1 ~	CSIR	HST	MBP	1231	2,66	645	1,8	55 45		- 419	- 523	543 648	668 792	812 957	973 1143	1154 1349	10,7	200	20	F	520	350	POE 22	C/V	DWG03	SM05	NEU6210U
EHU6212U*	10,6	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1457	2,6	811	2,03	- -	- -	- -	- -	- -	- -	- -	- -	- -	10,2	191	UD	F	520	270	POE22	C/V	UD	SM07	EHU6212U*
NEU6212U	10,0	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1386	2,61	793	1,96	55 45		- 522	- 644	667 791	819 962	995 1157	1195 1377	1419 1621	11,1	200	20,5	F	520	350	POE 22	C/V	DWG03	SM29	NEU6212U
NEU6212U	10,0	1/2	220-240V 50Hz 1 ~	CSR	HST	MBP	1397	2,79	800	2,09	55 45		- 523	- 652	683 803	833 974	1006 1165	1201 1378	1420 1611	11,1	200	20,5	F	520	350	POE 22	C/V	DWG03	SM06	NEU6212U
EHU6214U*	12,2	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1651	2,56	923	2,02	- -	- -	- -	- -	- -	- -	- -	- -	- -	10,2	191	UD	F	520	270	POE22	C/V	UD	SM07	EHU6214U*
NEK6214U	12,1	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1512	2,28	880	1,91	55 45		- 574	- 710	746 870	882 1055	1023 1374	1170 1499	1323 1758	11,7	206	17	F	520	350	POE 22	C/V	DWG03	SM05	NEK6214U
NEK6214U	12,1	1/2	220-240V 50Hz 1 ~	CSR	HST	MBP	1571	2,61	893	2,05	55 45		- 594	- 731	746 892	882 1077	1023 1285	1170 1516	1323 1770	11,6	206	17	F	520	350	POE 22	C/V	DWG03	SM06	NEK6214U
NEU6214U	12,1	1/2	220-240V 50Hz 1 ~	CSIR	HST	MBP	1645	2,47	936	1,96	55 45		- 619	- 763	796 934	969 1133	1167 1361	1388 1616	1634 1899	11,2	200	18	F	520	350	POE 22	C/V	DWG03	SM05	NEU6214U
NEU6214U	12,1	1/2	220-240V 50Hz 1 ~	CSR	HST	MBP	1682	2,75	944	2,11	55 45		- 624	- 770	807 943	981 1143	1179 1369	1401 1623	1648 1903	11,2	200	18	F	520	350	POE 22	C/V	DWG03	SM06	NEU6214U
NEK6217U	14,3	3/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	1820	2,21	1018	1,73	55 45		- 681	- 833	875 1018	1060 1233	1271 1481	1508 1759	1771 2068	11,6	206	24	F	520	350	POE 22	C/V	DWG03	SM05	NEK6217U
NEK6217U	14,3	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	1885	2,54	1051	1,94	55 45		- 702	- 861	893 1051	1085 1273	1306 1526	1556 1810	1834 2124	11,6	206	24	F	520	350	POE 22	C/V	DWG03	SM06	NEK6217U
NEU6217U	14,3	3/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	1903	2,35	1032	1,83	55 45		- 692	- 846	876 1030	1061 1244	1271 1487	1504 1760	1762 2063	11,6	206	21	F	520	350	POE 22	C/V	DWG03	SM05	NEU6217U
NEU6217U	14,3	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	1967	2,76	1058	2,04	55 45		- 704	- 865	902 1058	1095 1283	1315 1541	1561 1830	1835 2151	11,6	206	21	F	520	350	POE 22	C/V	DWG03	SM06	NEU6217U
NEU6220U	16,8	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	2292	2,6	1317	2,09	55 45		- 925	- 1144	1097 1396	1324 1682	1579 2007	1867 2372	2189 2781	11,6	206	22	F	520	350	POE 22	C/V	DWG03	SM06	NEU6220U
NT6220U	17,4	3/4	220-240V 50Hz 1 ~	CSIR	HST	MBP	2202	2,45	1193	1,76	55 45		- 757	- 954	995 1193	1236 1472	1506 1791	1803 2150	2129 2549	17	220	30	F	520	450	POE 22	C/V	DWG16	SM19	NT6220U
NT6220U	17,4	3/4	220-240V 50Hz 1 ~	CSR	HST	MBP	2250	2,79	1184	1,89	55 45		- 702	- 906	927 1135	1157 1409	1446 1747	1815 2169	2283 2695	17	220	30	F	520	450	POE 22	C/V	DWG16	SM23	NT6220U
NT6222U	20,4	1	220-240V 50Hz 1 ~	CSIR	HST	MBP	2537	2,37	1372	1,74	55 45		- 865	- 1095	1118 1372	1400 1695	1726 2060	2097 2465	2505 2907	17	220	30	F	520	450	POE 22	C/V	DWG16	SM19	NT6222U
NT6222U	20,4	1	220-240V 50Hz 1 ~	CSR	HST	MBP	2635	2,77	1412	1,92	55 45		- 897	- 1132	1177 1412	1471 1735	1803 2104	2174 2513	2581 2965	17	220	30	F	520	450	POE 22	C/V	DWG16	SM23	NT6222U
NT6224U	22,4	1	220-240V 50Hz 1 ~	CSR	HST	MBP	2843	2,73	1558	2,11	55 45		- 966	- 1239	1274 1557	1583 1920	1938 2321	2336 2761	2773 3232	17,2	220	26	F	520	450	POE 22	C/V	DWG16	SM23	NT6224U
NT6230U	27,8	1 1/4	220-240V 50Hz 1 ~	CSR	HST	MBP	3621	2,63	1935	1,93	55 45		- 1240	- 1561	1623 1939	1998 2376	2437 2871	2850 3350	3350 3810	17,4	243	39	F	520	450	POE 22	C/V	DWG17	SM21	NT6230U
NTX6233U*	27,8	1 1/4	220-240V 50Hz 1 ~	CSR	HST	MBP	3803	2,78	2070	2,07	55 45		- 1383	- 1710	1780 2092	2161 2528	259 3017	3066 3557	3587 4148	17,8	243	UD	F	520	450	POE 22	C/V	UD	SM21	NTX6233U*
NJX6244US	38,0	2	400V 50Hz / 440V 60Hz 3 ~	3PHASE	HST	MBP	5205	2,7	2737	2,01	55 45		- 1834	- 2273	2362 2801	2891 3418	3514 4124	4229 4918	5038 5801	21,8	277	22	F	800	750	POE 22	C/V	DWG14	SM18	NJX6244US

* MODEL UNDER DEVELOPMENT

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R290 • LBP • 60Hz - EU portfolio

											COOLING CAPACITY ARI 540																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - ARI 540 -23,3 °C / 48,9 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-40	-35	-30	-25	-20	-15	-10						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
EMC3121U	5,2	1/4	115-127V 60Hz 1~	RSCR	LST	L/MBP	294	1,77	-	-	55		-	-	-	-	-	-	-	6,8		14,9	S/F		150	POE 10	C			EMC3121U
											45		-	-	-	-	-	-	-											
EMC3125U	5,9	1/4	115-127V 60Hz 1~	RSCR	LST	L/MBP	345	1,75	-	-	55		-	-	-	-	-	-	-	6,8		18,4	S/F		150	POE 10	C			EMC3125U
											45		-	-	-	-	-	-	-											
EMC3130U	6,9	1/3	115-127V 60Hz 1~	RSCR	LST	L/MBP	418	1,7	-	-	55		-	-	-	-	-	-	-	6,8		20,9	F		150	POE 10	C			EMC3130U
											45		-	-	-	-	-	-	-											
EMC3140U	6,9	1/3	115-127V 60Hz 1~	RSCR	LST	L/MBP	583	1,72	480	1,46	55		-	-	-	-	-	-	-	7,8		26,5	F		150	POE 10	C			EMC3140U
											45		-	-	-	-	-	-	-											
NEK2134U	10,0	1/2	115V 60Hz 1~	CSIR	HST	LBP	539	1,39	415	1,1	55		-	-	268	344	433	535	650	10,7	200	28	F	520	350	POE 22	C/V	DWG04	SM04	NEK2134U
											45		194	251	325	415	521	643	780											
NEU2140U	10,0	1/2	115-127V 60Hz 1 ~	CSIR	HST	LBP	576	1,47	449	1,14	55		-	-	284	365	464	580	715	10	187	30	F	520	350	POE 22	C/V	DWG04	SM04	NEU2140U
											45		204	265	344	441	558	692	845											
NEK2150U	13,5	1/2	115V 60Hz 1~	CSIR	HST	LBP	687	1,25	550	1,02	55		-	-	352	451	566	699	848	11,3	206	41,5	F	520	350	POE 22	C/V	DWG04	SM04	NEK2150U
											45		248	321	418	537	678	842	1029											
NEK2150U	13,5	1/2	115V 60Hz 1~	CSR	HST	LBP	708	1,38	554	1,11	55		-	-	353	455	575	716	875	11,3	206	41,5	F	520	350	POE 22	C/V	DWG04	SM06	NEK2150U
											45		255	332	430	551	693	858	1045											
EHX2155U*	12,2	3/4	115-127V 60Hz 1 ~	CSIR	HST	LBP	719	1,62	-	-			-	-	-	-	-	-	-	10,2	191	UD	F	520	270	POE22	C/V	UD	SM07	EHX2155U*
													-	-	-	-	-	-	-											
NEU2155U	13,5	3/4	115-127V 60Hz 1 ~	CSIR	HST	LBP	758	1,44	600	1,14	55		-	-	374	485	618	773	951	11	200	40	F	520	350	POE22	C/V	DWG04	SM04	NEU2155U
											45		261	347	455	585	738	913	1111											
NEU2155U	13,5	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	766	1,56	608	1,22	55		-	-	383	497	633	791	970	11	200	40	F	520	350	POE 22	C/V	DWG04	SM06	NEU2155U
											45		260	344	455	591	753	941	1153											
NEU2168U	16,8	3/4	115-127V 60Hz 1 ~	CSR	HST	LBP	950	1,51	748	1,19	55		-	-	483	623	787	977	1191	11,6	206	49	F	520	350	POE22	C/V	DWG04	SM06	NEU2168U
											45		324	426	562	733	938	1178	1453											
NEU2168U	16,8	3/4	208-230V 60Hz 1 ~	CSIR	HST	LBP	911	1,36	736	1,1	55		-	-	472	608	769	955	1166	11,6	206	30	F	520	350	POE 22	C/V	DWG04	SM04	NEU2168U
											45		330	439	575	737	925	1139	1380											
NEU2168U	16,8	3/4	208-230V 60Hz 1 ~	CSR	HST	LBP	933	1,52	748	1,21	55		-	-	483	623	788	977	1191	11,6	206	30	F	520	350	POE 22	C/V	DWG04	SM06	NEU2168U
											45		346	447	578	739	931	1153	1406											
NT2160U(V)	17,4	3/4	208-230V 60Hz 1 ~	CSIR	HST	LBP	828	1,34	604	1,00	55		-	-	401	515	650	806	982	16,8	220	28	F	520	450	POE 22	C/V	DWG16	SM20	NT2160U(V)
											45		298	382	492	626	786	971	1179											
NT2160UV	17,4	3/4	115V 60Hz 1~	CSR	HST	LBP	827	1,42	638	1,1	55		-	-	400	521	667	837	1031	16,5	220	54,4	F	520	450	POE 22	C/V	DWG17	SM21	NT2160UV
											45		300	379	490	633	807	1013	1250											
NEU2178U	18,7	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1052	1,5	846	1,21	55		-	-	533	689	873	1083	1321	11,6	206	29	F	520	350	POE 22	C/V	DWG04	SM10	NEU2178U
											45		372	491	640	820	1029	1269	1538											
NEU2178U	18,7	1	115-127V 60Hz 1 ~	CSR	HST	LBP	1054	1,47	841	1,21	55		-	-	551	703	880	1082	1308	11,6	206	51	F	520	350	POE 22	C/V	DWG04	SM10	NEU2178U
											45		392	512	661	838	1043	1275	1535											
NT2170U(V)	20,4	3/4	208-230V 60Hz 1 ~	CSIR	HST	LBP	921	1,3	672	0,98	55		-	-	446	573	726	903	1104	17	220	30	F	520	450	POE 22	C/V	DWG16	SM20	NT2170U(V)
											45		325	419	544	698	883	1097	1340											
NT2170UV	20,4	3/4	115V 60Hz 1~	CSR	HST	LBP	970	1,38	772	1,12	55		-	-	495	641	818	1026	1265	16,5	220	55	F	520	450	POE 22	C/V	DWG17	SM21	NT2170UV
											45		372	474	613	787	997	1243	1525											
NT2180UV	22,4	1	208-230V 60Hz 1 ~	CSR	HST	LBP	1021	1,41	840	1,15	55		-	-	535	695	886	1107	1360	16,7	220	30	F	520	450	POE22	C/V	DWG17	SM26	NT2180UV
											45		396	506	656	845	1074	1341	1648											
NT2180UV	22,4	1	115V 60Hz 1~	CSR	HST	LBP	1048	1,38	832	1,12	55		-	-	534	691	876	1089	1330	16,5	220	54,5	F	520	450	POE 22	C/V	DWG17	SM21	NT2180UV
											45		396	509	659	844	1065	1323	1616											
NT2210UV	27,8	1 1/4	208-230V 60Hz 1 ~	CSR	HST	LBP	1281	1,42	1051	1,12	55		-	-	671	863	1093	1360	1665	17,8	234	37	F	520	450	POE22	C/V	DWG17	SM26	NT2210UV
											45		494	621	798	1024	1301	1627	2003											
NT2210UV	27,8	1 1/4	115V 60Hz 1~	CSR	HST	LBP	1322	1,39	1060	1,11	55		-	-	680	872	1104	1374	1684	17,8	234	67	F	520	450	POE 22	C/V	DWG17	SM26	NT2210UV
											45		514	651	833	1063	1338	1661	2029											
NJX2215US	38,0	2	400V 50Hz / 440V 60Hz 3 ~	3PHASE	HST	LBP	2011	1,5	1127	1,25	55		-	-	-	-	-	-	-	21,8	277	23	F	800	750	POE 22	C/V	DWG14	SM18	NJX2215US*
											45		-	-	-	-	-	-	-											

* MODEL UNDER DEVELOPMENT

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R290 • L/MBP • 60Hz - BR portfolio

MODEL	DISPL. cm ³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		CONDENSING TEMPERATURE		COOLING CAPACITY ASHRAE LBP							WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W			EVAPORATING TEMPERATURE °C W												CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
									°C		-35	-30	-25	-20	-15	-10	-5											
EMI50UER	3,00	1/6	115-127V 60Hz 1 ~	RSIR/CSIR	LST/HST	L/MBP	152	1,32	55		76	103	139	182	232	290	355	8,1	171	12,7	F	520	160	AB 32	C	DWG10	SM07	EMI50UER
EMI50UER	3,00	1/6	220-240V 50/60 Hz 1 ~	RSIR/CSIR	LST	L/MBP	152	1,33	55		76	103	139	182	232	290	355	8,1	171	9,2	F	520	160	AB 32	C	DWG10	SM07	EMI50UER
EMI70UER	4,08	1/5	115-127V 60Hz 1 ~	CSIR	LST	L/MBP	205	1,27	55		106	143	191	249	318	397	49	8,1	171	19,6	S/F	520	160	AB 32	C	DWG10	SM07	EMI70UER
EMI70UER	4,08	1/5	220-240V 50/60 Hz 1 ~	RSIR/CSIR	LST	L/MBP	210	1,30	55		106	143	191	249	318	397	49	8,1	171	9,4	S/F	520	160	AB 32	C	DWG10	SM07	EMI70UER
EMI90UEX	4,99	1/4+	115-127V 60Hz 1 ~	CSIR	HST	L/MBP	277	1,37	55		160	207	264	330	408	499	603	8,1	171	31	F	520	160	AB 32	C/V	DWG10	SM07	EMI90UEX
EMI90UEX	4,99	1/4+	220V 60Hz 1 ~	CSIR	HST	L/MBP	277	1,33	55		144	210	277	344	409	472	531	8,1	171	12	F	520	160	AB 32	C/V	DWG10	SM07	EMI90UEX
EM2X3121U	5,54	1/3	115-127V 60Hz 1 ~	RSCR	LST	L/MBP	333	1,74	55		168	225	292	367	451	546	650	8,2	171	10	S/F	520	130	POE 22	C	DWG10	SM07	EM2X3121U
EM2X3125U	6,09	1/3+	115-127V 60Hz 1 ~	RSCR	LST	L/MBP	361	1,70	55		198	258	330	413	510	621	748	8,2	171	12,6	S/F	520	130	POE 22	C	DWG10	SM07	EM2X3125U
FFU130UAX	6,76	1/3+	115-127V 60Hz 1 ~	CSIR	HST	L/MBP	399	1,51	55		236	288	361	454	568	704	-	10	201	39	F	520	280	AB 32	C/V	DWG09	SM08	FFU130UAX
FFU130UAX	6,76	1/3+	220-240V 50/60 Hz 1 ~	CSIR	HST	L/MBP	399	1,55	55		230	295	368	452	553	675	825	10	201	19	F	520	280	AB 32	C/V	DWG09	SM08	FFU130UAX
FFU160UAX	7,95	1/2	115-127V 60Hz 1 ~	CSIR	HST	L/MBP	489	1,54	55		236	288	361	454	568	704	-	10	201	41,5	F	520	280	AB 32	C/V	DWG09	SM08	FFU160UAX
FFU160UAX	7,95	1/2	220V 60Hz 1 ~	CSIR	HST	L/MBP	489	1,54	55		230	295	368	452	553	675	825	10	201	25,6	F	520	280	AB 32	C/V	DWG09	SM08	FFU160UAX

R290 • MBP • 60Hz - EU portfolio

											COOLING CAPACITY ARI 540																	
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - ARI540 +6,7 °C / 48,9 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W					WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-20	-15	-10	-5	0						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
EMX6144U*	4,5	1/4	220-240V 50/60Hz 1 ~	CSIR	HST	MBP	767	2,63	UD	UD	55		-	-	-	-	-	7,7	171	UD	S/F	270	150	POE 10	C/V	DWG01	SM29	EMX6144U*
											45		-	-	-	-	-											
EMX6152U*	5,2	1/4	220-240V 50/60Hz 1 ~	CSIR	HST	MBP	841	2,81	UD	UD	55		-	-	-	-	-	7,7	171	11	S/F	270	150	POE 10	C/V	DWG01	SM29	EMX6152U*
											45		-	-	-	-	-											
EMX6165U*	6,1	1/3	220-240V 50/60Hz 1 ~	CSIR	HST	MBP	987	2,62	UD	UD	55		-	-	-	-	-	7,7	171	UD	F	270	150	POE 10	C/V	DWG01	SM29	EMX6165U*
											45		-	-	-	-	-											
NEK6152U	5,4	1/4	115V 60Hz 1 ~	CSIR	HST	MBP	862	2,44	440	1,47	55		-	-	345	421	507	9,8	187	25	F	520	350	POE 22	C/V	DWG04	SM04	NEK6152U
											45		264	335	418	512	616											
NEK6165U	6,2	1/4	115V 60Hz 1 ~	CSIR	HST	MBP	992	2,41	505	1,5	55		-	-	404	488	586	10	187	28	F	520	350	POE 22	C/V	DWG04	SM04	NEK6165U
											45		318	395	486	593	714											
NEU6181U	7,3	1/3	115-127V 60Hz 1 ~	CSIR	HST	MBP	1197	2,7	633	1,72	55		-	-	495	611	744	10	187	30	F	520	350	POE 22	C/V	DWG04	SM04	NEU6181U
											45		388	487	605	742	897											
NEK6210U	8,8	1/3	115V 60Hz 1 ~	CSIR	HST	MBP	1368	2,48	717	1,6	55		-	-	570	698	843	10,6	200	37	F	520	350	POE 22	C/V	DWG04	SM04	NEK6210U
											45		445	556	685	831	996											
NEK6213U	12,1	1/2	115V 60Hz 1 ~	CSIR	HST	MBP	1841	2,13	998	1,48	55		-	-	781	949	1137	11,4	206	44	F	520	350	POE 22	C/V	DWG04	SM04	NEK6213U
											45		613	757	930	1132	1364											
NEU6214U	12,1	1/2	208-230V 60Hz 1 ~	CSIR	HST	MBP	1945	2,39	1073	1,66	55		-	-	841	1031	1250	11,1	206	23	F	520	350	POE 22	C/V	DWG04	SM04	NEU6214U
											45		663	815	1000	1220	1472											
NEU6214U	12,1	1/2	208-230V 60Hz 1 ~	CSR	HST	MBP	1977	2,71	1089	1,81	55		-	-	852	1050	1283	11,1	206	23	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214U
											45		677	827	1012	1233	1489											
NEU6214U	12,1	1/2	115-127V 60Hz 1 ~	CSIR	HST	MBP	1989	2,46	1085	1,74	55		-	-	865	1051	1261	11,5	206	42	F	520	350	POE 22	C/V	DWG04	SM04	NEU6214U
											45		678	836	1022	1234	1474											
NEU6214U	12,1	1/2	115-127V 60Hz 1 ~	CSR	HST	MBP	2021	2,68	1097	1,86	55		-	-	873	1060	1273	11,5	206	42	F	520	350	POE 22	C/V	DWG04	SM06	NEU6214U
											45		685	845	1034	1251	1496											
NEU6217U	14,3	3/4	208-230V 60Hz 1 ~	CSIR	HST	MBP	2258	2,25	1265	1,66	55		-	-	-	-	-	11,6	206	29	F	520	350	POE 22	C/V	DWG04	SM04	NEU6217U
											45		-	-	-	-	-											
NEU6217U	14,3	3/4	208-230V 60Hz 1 ~	CSR	HST	MBP	2342	2,63	1290	1,83	55		-	-	-	-	-	11,6	206	29	F	520	350	POE 22	C/V	DWG04	SM06	NEU6217U
											45		-	-	-	-	-											
NEU6217U	14,3	3/4	115-127V 60Hz 1 ~	CSIR	HST	MBP	2266	2,24	1261	1,67	55		-	-	965	1185	1449	11,6	206	45	F	520	350	POE 22	C/V	DWG04	SM04	NEU6217U
											45		793	955	1164	1422	1727											
NEU6217U	14,3	3/4	115-127V 60Hz 1 ~	CSR	HST	MBP	2332	2,53	1278	1,82	55		-	-	989	1216	1489	11,6	206	45	F	520	350	POE 22	C/V	DWG04	SM06	NEU6217U
											45		793	971	1193	1459	1770											
NT6217UV	14,5	1/2	115V 60Hz 1 ~	CSIR	HST	MBP	2103	2,53	1060	1,66	55		-	-	781	977	1209	16,2	220	44	F	520	450	POE 22	C/V	DWG16	SM20	NT6217UV
											45		558	749	978	1247	1557											
NT6217UV	14,5	1/2	115V 60Hz 1 ~	CSR	HST	MBP	2178	2,81	1073	1,79	55		-	-	790	1016	1296	16,2	220	44	F	520	450	POE 22	C/V	DWG16	SM23	NT6217UV
											45		577	754	977	1250	1574											
NT6220UV	17,4	3/4	115V 60Hz 1 ~	CSR	HST	MBP	2594	2,8	1287	1,79	55		-	-	996	1224	1479	16,6	220	54,5	F	520	450	POE 22	C/V	DWG17	SM21	NT6220UV
											45		771	952	1195	1501	1870											
NT6222UV	20,4	3/4	115V 60Hz 1 ~	CSR	HST	MBP	3023	2,73	1522	1,78	55		-	-	1181	1476	1798	16,5	220	54,5	F	520	450	POE 22	C/V	DWG17	SM21	NT6222UV
											45		923	1146	1433	1785	2202											
NTX6222UV*	20,4	3/4	115V 60Hz 1 ~	CSR	HST	MBP	3323	2,84	1743	1,96	55				1348	1679	2056	16,5	220	UD	F	520	450	POE 22	C/V	UD	SM26	NTX6222UV*
											45		1003	1297	1638	2026	2460											
NT6224UV	22,4	1	208-230V 60Hz 1 ~	CSR	HST	MBP	3379	2,69	1739	1,82	55		-	-	1355	1673	2028	16,8	220	33,7	F	520	450	POE 22	C/V	DWG16	SM23	NT6224UV
											45		1041	1315	1634	1995	2401											
NTX6225UV*	22,4	1	208-230V 60Hz 1 ~	CSR	HST	MBP	3663	2,9	1969	2,00	55		-	-	-	-	-	16,5	220	UD	F	520	UD	UD	C/V	UD	SM26	NTX6225UV*
											45		-	-	-	-	-											
NJX6244US	38,0	2	400V 50Hz / 440V 60Hz 3 ~	3PHASE	HST	MBP	5976	2,51	UD	UD	55		-	-	-	-	-	21,8	277	22	F	800	750	POE 22	C/V	DWG14	SM18	NJX6244US
											45		-	-	-	-	-											

* MODEL UNDER DEVELOPMENT

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R600a • LBP - L/MBP • 50Hz - EU portfolio

											COOLING CAPACITY CECOMAF																		
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		RATED POINT - CECOMAF -25 °C / 55 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W			-30	-25	-20	-15	-10	-5						CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
EMX20CLC	4,0	1/14	220-240V 50Hz 1 ~	RSCR	LST	LBP	63	1,66	48	1,3	55		36	49	64	82	102	126	7,1	166	2,1	S	-	150	AB 5	C	DWG01	SM01	EMX20CLC
											45		44	58	76	96	119	146											
EMX26CLC	5,2	1/12	220-240V 50Hz 1 ~	RSCR	LST	LBP	81	1,68	60	1,32	55		43	59	80	104	133	165	7,1	166	-	S	-	150	AB 5	C	DWG01	SM01	EMX26CLC
											45		53	72	96	124	156	192											
EMX32CLC	6,0	1/10	220-240V 50Hz 1 ~	RSCR	LST	LBP	92	1,72	69	1,35	55		49	69	92	119	151	189	7,3	166	3,3	S	-	150	AB 5	C	DWG01	SM01	EMX32CLC
											45		64	86	111	141	176	218											
EMX3109Y	6,2	1/10	100V 50Hz / 100-127V 60Hz 1 ~	RSIR/RSCR	LST	L/MBP	100	1,68	-	-	55		-	-	-	-	-	-	7,7	171	6,8	S/F	270	150	AB 5	C/V	DWG01	SM00-SM01	EMX3109Y
											45		-	-	-	-	-	-											
EMC40CLT	7,2	1/8	220-240V 50Hz 1 ~	RSCR	LST	LBP	117	1,79	87	1,4	55		78	107	142	187	233	260	7,7	171	3,4	S	-	150	AB 5	C	DWG01	SM02	EMC40CLT
											45		88	118	154	198	248	300											
EMC46CLT	8,0	1/7	220-240V 50Hz 1 ~	RSCR	LST	LBP	133	1,8	98	1,37	55		88	119	158	203	256	280	7,1	166	-	S	-	150	AB 2	C	DWG01	SM02	EMC46CLT
											45		95	129	169	215	269	310											
EMX3113Y	9,0	1/7	100V 50Hz / 100-127V 60Hz 1 ~	RSCR	LST	L/MBP	155	1,75	-	-	55		-	-	-	-	-	-	8	171	11,6	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3113Y
											45		-	-	-	-	-	-											
EMX55CLC	9,0	1/6	220-240V 50Hz 1 ~	RSCR	LST	LBP	156	1,74	117	1,37	55		87	117	154	197	245	303	7,6	166	-	S	-	150	AB 5	C	DWG01	SM01	EMX55CLC
											45		102	135	175	222	277	339											
EMX3115Y	10,6	1/5	100V 50Hz / 100-127V 60Hz 1 ~	RSCR	LST	L/MBP	184	1,67	-	-	55		-	-	-	-	-	-	7,7	166	14,1	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3115Y
											45		-	-	-	-	-	-											
EMX66CLC	10,6	1/5	220-240V 50Hz 1 ~	RSCR	LST	LBP	183	1,73	137	1,37	55		101	137	178	227	284	348	7,4	166	6,4	S	-	150	AB 5	C	DWG01	SM01	EMX66CLC
											45		122	160	207	261	323	394											
EMX70CLC	11,1	1/5	220-240V 50Hz 1 ~	RSCR	LST	LBP	191	1,71	143	1,34	55		103	143	184	233	290	360	7,4	166	6	S	-	150	AB 5	C	DWG01	SM01	EMX70CLC
											45		123	164	210	263	327	403											
EMX3118Y	12,2	1/5	100V 50Hz / 100-127V 60Hz 1 ~	RSCR	LST	L/MBP	212	1,66	-	-	55		-	-	-	-	-	-	7,7	166	14,1	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3118Y
											45		-	-	-	-	-	-											
EMY3118Y	12,2	1/5	220-240V 50Hz 1 ~	RSIR	LST	L/MBP	212	1,49	157	1,16	55		-	-	-	-	-	-	7,7	171	7,8	S/F	270	150	AB 5	C/V	DWG01	SM00	EMY3118Y
											45		-	-	-	-	-	-											
EMY3118Y	12,2	1/5	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	213	1,58	158	1,23	55		-	-	-	-	-	-	7,6	171	7,8	S/F	270	150	AB 5	C/V	DWG01	SM01	EMY3118Y
											45		-	-	-	-	-	-											
EMX3118Y	12,2	1/5	220-240V 50Hz 1 ~	RSCR	LST	L/MBP	214	1,72	159	1,34	55		-	-	-	-	-	-	7,9	171	7,5	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3118Y
											45		-	-	-	-	-	-											
EMX80CLT	12,2	1/5	220-240V 50Hz 1 ~	RSCR	LST	LBP	213	1,73	162	1,36	55		118	162	207	265	331	406	7,9	171	7,5	S	-	150	AB 5	C	DWG01	SM02	EMX80CLT
											45		139	185	240	305	380	464											
NBY1118Y	14,3	1/4	220-240V 50Hz 1 ~	RSCR	LST	LBP	244	1,74	183	1,38	55		138	183	234	299	375	464	10,6	195	11	S	-	280	AB 5	C	DWG02	SM02	NBY1118Y
											45		159	206	266	339	427	529											

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R600a • LBP - L/MBP • 50Hz - BR portfolio

									COOLING CAPACITY ASHRAE LBP																			
MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W						WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL	
							CAPACITY W	EFFICIENCY W/W			-35	-30	-25	-20	-15	-10						-5	CHARGE cm³		TYPE	EXTERNAL VIEW REFERENCE		WIRING DIAGRAM REFERENCE
EMX20CLC	3,97	1/12	220-240V 50Hz 1 ~	RSCR	LST	LBP	63	1,54	55		34	47	54	75	97	123	152	7,8	170	2	S	-	150	AB 5	C	DWG10	SM07	EMX20CLC
EMT23CLP	4,5	1/12	220-240V 50Hz 1 ~	RSIR	LST	LBP	78	1,34	55		38	53	70	91	115	144	-	7,2	158	2,7	S/F	520	180	MIN 10	C	DWG10	SM07	EMT23CLP
EMI30CNP	4,99	1/10	220V 50/60Hz 1 ~	RSIR	LST	L/MBP	76	1,16	55		31	48	68	91	119	152	192	7,1	166	3,7	S	-	160	MIN 32	C	DGW10	SM07	EMI30CNP
EMI40CNP	6,36	1/8	220V 50/60Hz 1 ~	RSIR	LST	L/MBP	100	1,18	55		49	68	91	119	153	195	245	7	166	5	S	-	160	MIN 32	C	DGW10	SM07	EMI40CNP
EMT40CLP	7,23	1/8	220-240V 50Hz 1 ~	RSIR/RSCR	LST	LBP	119	1,36	55		54	79	108	142	182	229	284	7,4	158	4,3	S	-	180	AB 5	C	DWG10	SM07	EMT40CLP
EMX46CLC	7,96	1/8	220-240V 50Hz 1 ~	RSCR	LST	LBP	138	1,71	55		68	95	127	165	211	264	325	7,4	166	3,7	S	-	180	AB 5	C	DWG10	SM07	EMX46CLC
EMT56CLP	9,04	1/6	220-240V 50Hz 1 ~	RSIR/RSCR	LST	LBP	155	1,35	55		77	106	143	188	240	301	369	7,7	166	5,5	S	-	180	AB 5	C	DWG10	SM07	EMT56CLP
EMYE70CLP	10,61	1/5	220V 50/60Hz 1 ~	RSIR	LST	LBP	182	1,32	55		-	-	-	-	-	-	-	7,6	200	8,2	S	-	180	AB 5	C	DWG10	SM07	EMYE70CLP
EMX70CLC	11,14	1/4	220-240V 50Hz 1 ~	RSCR	LST	LBP	191	1,67	55		105	135	174	223	283	355	438	8,6	166	4,9	S	-	180	AB 5	C	DWG10	SM07	EMX70CLC
EGAS80CLP	11,14	1/4	220V 50/60Hz 1 ~	RSIR	LST	LBP	190	1,44	55		94	128	171	224	290	370	467	10,4	201	7,3	S		280	AB 5	C	DWG09	SM09	EGAS80CLP
EGYS80CLP	11,14	1/4	220-240V 50Hz 1 ~	RSIR	LST	LBP	199	1,73	55		108	141	181	230	290	365	458	11	201	8,1	S		280	AB 5	C	DWG09	SM09	EGYS80CLP
EGYS90CLP	12,21	1/4+	220-240V 50Hz 1 ~	RSIR	LST	LBP	215	1,69	55		118	153	198	255	324	407	505	10,9	201	8,8	S		280	AB 5	C	DWG09	SM09	EGYS90CLP
EGYS90CLP	12,21	1/4+	220-240V 50/60 Hz 1 ~	RSIR	LST	LBP	217	1,71	55		109	151	198	253	321	403	-	10,9	201	8,8	S	-	280	AB 5	C	DWG09	SM09	EGYS90CLP
EGAS100CLP	13,54	1/3	220V 50/60Hz 1 ~	RSIR	LST	LBP	232	1,33	55		126	163	215	280	359	454	564	10,4	201	10,3	S		280	AB 5	C	DWG09	SM09	EGAS100CLP
EGX100CLC	13,54	1/3	220-240V 50Hz 1 ~	RSCR	LST	LBP	248	1,87	55		111	160	207	258	320	397	497	11,2	201	4,9	S		280	AB 5	C	DWG09	SM09	EGX100CLC

R600a • HBP • 50Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE 7,2 °C / 54,4 °C		RATED POINT - EN12900 5 °C / 50 °C		COOLING CAPACITY EN12900								WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W											CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
													-15	-10	-5	0	5	10											
EMT30CDP	4,5	1/12	220-240V 50Hz 1 ~	RSIR	LST	HBP	256	2,53	246	2,65	55		-	125	155	191	232	278	7,2	158	3,7	S	-	180	POE 22	C	DWG01	SM00	EMT30CDP
											45		113	140	176	213	258	310											
EMU5125Y	4,5	1/12	220-240V 50Hz 1 ~	RSIR/RSCR	LST	HBP	267	2,88	244	2,82	55		-	120	151	187	228	274	7	158	3,7	S	-	150	AB 5	C	DWG01	SM00-SM01	EMU5125Y
											45		111	140	174	214	259	310											
EMY5125Y	4,5	1/8	220-240V 50Hz 1 ~	RSIR/RSCR	LST	HBP	274	3,01	-	-	55		-	-	-	-	-	-	7,3	166	3,1	S	-	150	AB 5	C	DWG01	SM00-SM01	EMY5125Y
											45		-	-	-	-	-	-											
EMT45CDP	6,8	1/8	220-240V 50Hz 1 ~	RSIR	LST	HBP	389	2,56	360	2,47	55		-	169	215	267	326	395	7,7	166	5,8	S	-	180	POE 22	C	DWG01	SM00	EMT45CDP
											45		153	195	243	299	365	443											
EMY5135Y	7,2	1/8	220-240V 50Hz 1 ~	RSIR	LST	HBP	417	2,79	-	-	55		-	-	-	-	-	-	7,7	171	5	S	-	150	AB 5	C	DWG01	SM00	EMY5135Y
											45		-	-	-	-	-	-											
EMY6135Y	7,2	1/8	220-240V 50Hz 1 ~	CSIR	HST	HBP	414	2,65	-	-	55		-	-	-	-	-	-	7,1	166	6	S	-	150	AB 5	C	DWG01	SM29	EMY6135Y
											45		-	-	-	-	-	-											
EMT6144Y	9,1	1/5	220-240V 50Hz 1 ~	CSIR	HST	HBP	543	2,48	486	2,41	55		-	250	310	377	455	543	7,8	166	7,7	F	520	180	POE 22	C/V	DWG01	SM05	EMT6144Y
											45		223	282	350	427	515	614											
NEK6160Y	12,1	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	677	2,53	606	2,43	55		-	294	372	464	567	678	10,6	187	12,4	F	520	350	POE 22	C/V	DWG03	SM05	NEK6160Y
											45		267	338	425	528	641	764											
NEK6170Y	14,3	1/4	220-240V 50Hz 1 ~	CSIR	HST	HBP	809	2,47	720	2,38	55		-	358	449	554	674	807	10,6	187	12,4	F	520	350	POE 22	C/V	DWG03	SM05	NEK6170Y
											45		326	412	512	630	764	913											
NBY5170Y	14,3	1/4	220-240V 50Hz 1 ~	RSCR	LST	HBP	842	3,1	753	2,99	55		-	-	-	-	-	-	10,8	206	15	S	-	350	AB 5	C/V	DWG02	SM01	NBY5170Y
											45		-	-	-	-	-	-											
NEK6187Y	16,8	1/3	220-240V 50Hz 1 ~	CSIR	HST	HBP	907	2,39	805	2,29	55		-	391	494	613	749	774	11	200	16,1	F	520	350	POE 22	C/V	DWG03	SM05	NEK6187Y
											45		359	457	572	705	856	336											

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R600a • LBP - L/MBP • 60Hz - EU portfolio

MODEL	DISPL. cm³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		COOLING CAPACITY ASHRAE								WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m³/h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W											CHARGE cm³	TYPE		EXTERNAL VIEW REFERENCE	WIRING DIAGRAM REFERENCE	
											-30	-25	-20	-15	-10	-5											
EMX3109Y	6,2	1/10	100V 50Hz / 100-127V 60Hz 1 ~	RSIR/RSCR	LST	L/MBP	125	1,76	55		80	108	144	187	237	295	7,7	171	8,2	S/F	270	150	AB 5	C/V	DWG01	SM32	EMX3109Y
									45		88	117	154	199	252	312											
EMX60CLC	9,0	1/7	115-127V 60Hz 1 ~	RSIR/RSCR	LST	LBP	181	1,67	55		124	163	211	269	337	418	7,6	171	12	S	-	150	AB 5	C	DWG01	SM00-SM01	EMX60CLC
									45		132	173	223	283	354	437											
EMX3113Y	9,0	1/7	100V 50Hz / 100-127V 60Hz 1 ~	RSCR	LST	L/MBP	185	1,74	55		119	161	213	275	347	429	8	171	13,8	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3113Y
									45		127	171	225	289	362	445											
EMX3115Y	10,6	1/6	100V 50Hz / 100-127V 60Hz 1 ~	RSCR	LST	L/MBP	213	1,69	55		145	187	242	311	392	486	7,7	166	16,7	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3115Y
									45		154	200	258	329	413	510											
EMX3118Y	12,2	1/5	100V 50Hz / 100-127V 60Hz 1 ~	RSCR	LST	L/MBP	242	1,64	55		169	223	291	373	468	577	7,7	166	16,7	S/F	270	150	AB 5	C/V	DWG01	SM01	EMX3118Y
									45		179	237	308	393	492	604											

Note: Return gas temperature in EN12900 conditions for EM and NE series is 32°C for NT and NJ series is 20°C

R600a • LBP - L/MBP - L/M/HBP • 60Hz - BR portfolio


MODEL	DISPL. cm ³	HP	VOLTAGE/FREQUENCY	MOTOR TYPE	TORQUE	APPLICATION	RATED POINT - ASHRAE -23,3 °C / 54,4 °C		COOLING CAPACITY ASHRAE LBP										WEIGHT kg	MAX HEIGHT A mm	LRA A	COOLING TYPE	FAN AIR FLOW m ³ /h	OIL		EXP DEVICE	DRAWINGS		MODEL
							CAPACITY W	EFFICIENCY W/W	CONDENSING TEMPERATURE °C		EVAPORATING TEMPERATURE °C W							CHARGE cm ³						TYPE	EXTERNAL VIEW REFERENCE		WIRING DIAGRAM REFERENCE		
											-35	-30	-25	-20	-15	-10	-5												
EMX20CLC	3,97	1/12	115 - 127V 60Hz 1 ~	RSCR	LST	LBP	77	1,56	55		51	69	90	115	147	-	-	7,8	170	3,7	S	-	180	AB 5	C	DWG10	SM07	EMX20CLC	
EMT30CDP	4,5	1/8	100V 50/60 Hz 1 ~	RSIR	LST	L/M/HBP	94	1,42	-		-	-	-	-	-	-	-	7,2	170	7,7	S	-	180	MIN 10	C	DWG10	SM07	EMT30CDP	
EMI30CNP	4,99	1/10	220V 50/60 Hz 1 ~	RSIR	LST	L/MBP	94	1,22	55		61	85	113	145	183	226	-	7,1	166	3,5	S	-	160	MIN 32	C	DWG10	SM07	EMI30CNP	
EMI40CNP	6,36	1/8	220V 50/60 Hz 1 ~	RSIR	LST	L/MBP	120	1,25	55		81	109	144	186	236	296	-	7	166	4,5	S	-	160	MIN 32	C	DWG10	SM07	EMI40CNP	
EMU40CLP	5,96	1/8	220V 50/60 Hz 1 ~	RSIR/RSCR	LST	LBP	120	1,34	55		82	110	142	181	227	-	-	8,6	165	7,7	S	-	180	AB 5	C	DWG10	SM07	EMU40CLP	
EMU40CLP	5,96	1/8	115 - 127V 60Hz 1 ~	RSIR/RSCR	LST	LBP	115	1,25	55		78	106	140	181	228	283	-	8,6	165	7,3	S	-	180	AB 5	C	DWG10	SM07	EMU40CLP	
EMU60CLP	9,04	1/6	115-127V 60Hz 1 ~	RSIR	LST	LBP	175	1,47	55		91	121	156	199	253	319	-	7,4	170	10,5	S	-	180	AB 5	C	DWG10	SM07	EMU60CLP	
EMU60CLP	9,04	1/6	220V 60 Hz 1 ~	RSIR	LST	LBP	175	1,41	55		89	120	158	204	261	331	414	8,6	170	7,4	S	-	180	AB 5	C	DWG10	SM07	EMU60CLP	
EMYE70CLP	10,61	1/5	115-127V 60Hz 1 ~	RSIR	LST	LBP	203	1,50	55		107	143	185	241	306	387	482	7,7	200	14,5	S	-	180	AB 5	C	DWG10	SM07	EMYE70CLP	
EMYE70CLP	10,61	1/5	220V 50/60 Hz 1 ~	RSIR	LST	LBP	203	1,46	55		-	-	-	-	-	-	-	7,6	200	7,8	S	-	180	AB 5	C	DWG10	SM07	EMYE70CLP	
EGAS80CLP	11,14	1/4	115-127V 60Hz 1 ~	RSIR/RSCR	LST	LBP	245	1,58	55		124	173	227	288	362	451	558	10,3	200	18	S	-	280	AB 5	C	DWG09	SM09	EGAS80CLP	
EGAS80CLP	11,14	1/4	220V 60 Hz 1 ~	RSIR/RSCR	LST	LBP	243	1,57	55		119	168	223	287	362	452	-	10,4	200	7,3	S	-	280	AB 5	C	DWG09	SM09	EGAS80CLP	
EGAS80CLP	11,14	1/4	220V 50/60 Hz 1 ~	RSIR	LST	LBP	242	1,59	55		125	173	226	287	361	448	-	10,4	200	7,3	S	-	280	AB 5	C	DWG09	SM09	EGAS80CLP	
EGYS90CLP	12,21	1/4+	115-127V 60Hz 1 ~	RSCR	LST	LBP	267	1,71	55		137	190	249	317	400	499	621	11,2	200	24,1	S	-	280	AB 5	C	DWG09	SM09	EGYS90CLP	
EGYS90CLP	12,21	1/4+	220-240V 50/60 Hz 1 ~	RSIR	LST	LBP	265	1,67	55		132	183	243	313	396	495	613	11	200	8	S	-	280	AB 5	C	DWG09	SM09	EGYS90CLP	
EGAS100CLP	13,54	1/3	220V 50/60 Hz 1 ~	RSIR	LST	LBP	297	1,53	55		157	205	274	362	466	582	-	10,4	200	10,3	S	-	280	AB 5	C	DWG09	SM09	EGAS100CLP	

EXTERNAL VIEWS & WIRING DIAGRAMS




EXTERNAL VIEWS

DWG01 – EM Series European Base Plate



	Ø mm	material
S - Suction	6.10 - 6.20	Cu
P - Process	5.92 - 6.08	Cu
	6.10 - 6.20	Cu
D - Discharge	4.90 - 5.02	Cu
	5.10 - 5.20	Cu
	6.10 - 6.20	Cu


DWG02/03 - NB / NE SERIES European Base Plate



	Ø mm	material
S - Suction	6.10 - 6.20	Cu
P - Process	6.10 - 6.20	Cu
S - Discharge	4.98 - 5.02	Cu


	Ø mm	material
S - Suction	6.10 - 6.20	Cu
P - Process	6.10 - 6.20	Cu
S - Discharge	6.10 - 6.20	Cu

DWG04 - NE / VNE SERIES Universal Base Plate



	Ø mm	material
S - Suction	8.03 - 8.10	Cu
P - Process	6.45 - 6.55	Cu
D - Discharge	6.45 - 6.55	Cu


DWG10 - EM SERIES Universal Base Plate




	Ø mm	Material
Suction	6,5	copper
Process	6,5	copper
Discharge	4,9	copper

	Ø mm	Material
Suction	8,2	copper
Process	6,5	copper
Discharge	6,5	copper

DWG09 - EG / F / VEG SERIES




DWG15 - NT SERIES




	Ø mm	material
S - Suction	9.80 - 9.87	Cu
P - Process	6.42 - 6.50	Cu
D - Discharge	6.42 - 6.50	Cu

DWG14 - NJ SERIES



	Ø mm	material
S - Suction	9.80 - 9.87	Cu
	12.77 - 12.85	Cu
P - Process	6.42 - 6.50	Cu
D - Discharge	6.42 - 6.50	Cu
	8.00 - 8.08	Cu


DWG16 - NT SERIES




	Ø mm	material
S - Suction	9.80 - 9.87	Cu
P - Process	6.42 - 6.50	Cu
D - Discharge	6.42 - 6.50	Cu

EXTERNAL VIEWS


DWG17 - NT SERIES



	Ø mm	material
S - Suction	9.80 - 9.87	Cu
P - Process	6.42 - 6.50	Cu
D - Discharge	6.42 - 6.50	Cu




DWG22 - VES SERIES




	Ø mm	Ø in	material
S - SUCTION	6.10-6.20	0.24	Cu
P - PROCESS	6.10-6.20	0.24	Cu
D - DISCHARGE	4.98-5.02	3/16	Cu


DWG19 - NTU SERIES



	Ø mm	material
S - Suction	12.77 - 12.85	Cu
P - Process	6.42 - 6.50	Cu
D - Discharge	9.80 - 9.87	Cu



DWG23 - VEM SERIES



	Ø mm	Ø in	material
S - SUCTION	6.10-6.20	0.24	Cu
P - PROCESS	6.10-6.20	0.24	Cu
D - DISCHARGE	4.98-5.02	3/16	Cu



<http://refrigerationclub.com/wiring-diagrams-videos-for-europe/>





WIRING DIAGRAMS KEY



	OVERLOAD PROTECTOR		PTC START DEVICE`
	OVERLOAD PROTECTOR		INTEGRATED PTC DEVICE
	CURRENT START RELAY		CURRENT START RELAY WITH CAPACITOR CONNECTIONS
	3CR CURRENT START RELAY		3ARR3 START RELAY (VOLTAGE).
	RUN CAPACITOR		RUN CAPACITOR (MANDATORY - NOT SUPPLIED)
	OPTIONAL RUN CAPACITOR		START CAPACITOR
	FAN		PUSH BUTTON
	LAMP		SINGLE PHASE MOTOR
	3-PHASE MOTOR		THERMOSTAT
	LOW-HIGH PRESSURE SWITCH		PILOT CIRCUIT 24 OR 220 V
	EARTH CONNECTION		COMMON (INTERNAL OVERLOAD PROTECTOR)
	3-PHASE SUPPLY		START
	SINGLE PHASE SUPPLY		
	COMMON		
	RUN		
	TERMINAL BLOCK		BROWN CABLE
	WHITE CABLE		BLACK CABLE
	BLUE CABLE		RED CABLE
	YELLOW-GREEN CABLE		CONNECTIONS TO BE MADE BY THE CUSTOMER (NOT SUPPLIES)
	CONNECTIONS SUPPLIED		

WIRING DIAGRAMS



SM00 - EMT/NE SERIES RSIR PTC European Version



SM01 - EMT/NE SERIES RSCR PTC European Version




SM02 - EMT/NE SERIES RSCR TSD European Version




WIRING DIAGRAMS


SM03 - EMT/NE SERIES RSIR Terminal Board & Start Device




SM04 - EMT/NE SERIES CSIR American Version




SM05 - EMT/NE SERIES CSIR Terminal Board & Start Device




SM06 - NE SERIES CSR Box



SM07 - EM/EMI




SM08 - F COMPRESSORS




(*) Valid only for CSIR version

WIRING DIAGRAMS


SM09 - EG



SM10 - NE CSR Box




SM14 - NJ CSIR Box




(*) Valid only for CSIR version


SM15 - NJ PSC



SM16 - NJ SERIES CSR Box (Internal Overload Protector)




SM17 - NJ CSR Box (External Overload Protector)




WIRING DIAGRAMS


SM18 - NJ SERIES 3-Phase (Internal Overload Protector)




SM19 - NT SERIES CSIR Terminal Board




SM20 - NT SERIES CSIR – American Version




SM21 - NT SERIES CSR Box



SM23 - NT SERIES CSR Box




SM26 - NT SERIES CSR Box (Internal Overload Protector)




WIRING DIAGRAMS


SM27 - NT SERIES 3-Phase (Internal + External Overload Protector)



SM29 - EMX SERIES CSIR TERMINAL BOARD & START DEVICE & 4TM




SM32 - EM RSCR PTC & 4TM




WIRING DIAGRAMS


CON01 - VEMY6 / VEG (Drop-in)




CON02 - VEM / VEG (Frequency)




CON03 - VEMY6 / VEG (Serial)




CON04 - VEM (Frequency)



CON05 - VEM (Serial)





CON06 - VEM (Drop-in)





WIRING DIAGRAMS



CON07 - VNE (Drop-in)





CON08 - VNE (Frequency)





CON09 - VNE (Serial)




CON10 - VEG (Drop-in)



CON11 - VEG (Frequency)





www.embraco.com